

PRODUCT DATA SHEET

Sika® Colma Cleaner

Solvent-based cleaning agent for substrates and tools

DESCRIPTION

Sika® Colma Cleaner is a grease-free solvent specially formulated for the pre-cleaning of bond faces and the cleaning of tools and equipment.

USES

Sika® Colma Cleaner is designed for cleaning surfaces prior to bonding and for cleaning of tools and equipment such as light metals and alloys, steel and stainless steel.

CHARACTERISTICS / ADVANTAGES

- Easy to use
- Very powerful, fast cleaning

PRODUCT INFORMATION

Composition	One-Component, solvent-based cleaner
Packaging	1 l can , 6 cans per box 20 l Pail
Shelf life	Sika® Colma Cleaner has a shelf life of 24 months from the date of production, if it is stored in undamaged, original, sealed packaging, and if the storage conditions are met.
Storage conditions	Sika® Colma Cleaner shall be stored in dry conditions, where it is protected from direct sunlight and at temperatures between +5 °C and +25 °C.
Colour	Transparent
Density	0.85 kg/l approx. (ISO 1128-1)
Flash point	14 °C approx. (ISO 13736)
Viscosity	1 mPa*s approx. (ISO 3219)

APPLICATION INFORMATION

Consumption	50 ml/m ² approx.
Ambient air temperature	+5 °C to +40 °C, min. 3 °C above dew point temperature
Substrate temperature	+5 °C to +40 °C
Flash-off time	Minimum 15 minutes

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER INFORMATION

- Safety Data Sheet
- Pre-treatment Chart Sealing and Bonding

IMPORTANT CONSIDERATIONS

Sika® Colma Cleaner shall not be used on porous substrates.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

APPLICATION METHOD / TOOLS

Soak a clean rag or lint-free paper towel in Sika® Colma Cleaner and clean the bonding areas to remove surface contamination. Tightly reseal the container immediately after each use.

After a flash-off time of 15 minutes apply the appropriate Primer or Aktivator and respect relevant flash-off times again.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Australia Pty Limited

ABN 12 001 342 329

aus.sika.com

Tel: 1300 22 33 48

SikaColmaCleaner-en-AU-(04-2023)-1-4.pdf

Product Data Sheet
Sika® Colma Cleaner
April 2023, Version 01.04
020516020000000001

