

SAFETY DATA SHEET

Sika® Aktivator PRO



Version 2.0

SDS Number: 000000125402

Revision Date: 16.11.2019

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sika® Aktivator PRO
Product code : 000000125402
Type of product : liquid

Recommended use of the chemical and restrictions on use

Product use : Pretreatment agent

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.
55 Elizabeth Street
Wetherill Park, NSW 2164
Telephone : +61 2 9725 11 45
Telefax : +61 2 9725 33 30
Emergency telephone number : +61 1800 033 111

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2
Skin corrosion/irritation : Category 2
Serious eye damage/eye irritation : Category 1
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)
Aspiration hazard : Category 1
Long-term (chronic) aquatic hazard : Category 2

GHS label elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P210 Keep away from heat/sparks/open flames/hot surfaces.



No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
 P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
 P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
 P331 Do NOT induce vomiting.
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.
 P362 Take off contaminated clothing and wash before reuse.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
 P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (%)
Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha	64742-49-0	>= 60 - <= 100
bis(trimethoxysilylpropyl)amine	82985-35-1	>= 3 - < 10
3-trimethoxysilylpropane-1-thiol	4420-74-0	< 1

SAFETY DATA SHEET

Sika® Aktivator PRO



Version 2.0

SDS Number: 000000125402

Revision Date: 16.11.2019

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Risk of serious damage to the lungs (by aspiration).
irritant effects
Aspiration may cause pulmonary oedema and pneumonitis.
Excessive lachrymation
Dermatitis
Loss of balance
Vertigo
See Section 11 for more detailed information on health effects and symptoms.
May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye damage.
May cause drowsiness or dizziness.
- Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : Water
High volume water jet
- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Do not allow run-off from fire fighting to enter drains or water courses.

SAFETY DATA SHEET

Sika® Aktivator PRO



Version 2.0

SDS Number: 000000125402

Revision Date: 16.11.2019

- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons.
- Environmental precautions : Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.



Conditions for safe storage : Store in original container.
 Store in cool place.
 Keep in a well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.
 Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha	64742-49-0	TWA	900 mg/m ³	AU OEL

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
methanol	67-56-1	TWA	200 ppm 262 mg/m ³	AU OEL
	Further information: Skin absorption			
		STEL	250 ppm 328 mg/m ³	AU OEL
	Further information: Skin absorption			

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

SAFETY DATA SHEET

Sika® Aktivator PRO



Version 2.0

SDS Number: 000000125402

Revision Date: 16.11.2019

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: colourless
Odour	: hydrocarbon-like
Odour Threshold	: No data available
pH	: No data available
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: ca. -4 °C (25 °F) Method: closed cup
Evaporation rate	: No data available
Flammability	: No data available
Upper explosion limit	: 7 %(V)
Lower explosion limit	: 0.6 %(V)
Vapour pressure	: 60 hPa (45 mmHg)
Relative vapour density	: No data available
Density	: ca. 0.7 g/cm ³ (20 °C (68 °F) ())
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: ca. 2 mPa.s (20 °C)
Viscosity, kinematic	: < 20.5 mm ² /s (40 °C)
Explosive properties	: No data available
Molecular weight	: No data available
Volatile organic compounds	: Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

SAFETY DATA SHEET

Sika® Aktivator PRO



Version 2.0

SDS Number: 000000125402

Revision Date: 16.11.2019

Volatile organic compounds (VOC) content:
95.8 %

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: methanol

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

bis(trimethoxysilylpropyl)amine:

Acute oral toxicity : LD50 Oral (Rat): 3,780 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 11,865 mg/kg

3-trimethoxysilylpropane-1-thiol:

Acute oral toxicity : LD50 Oral (Rat): 1,701 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): 2,583 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

SAFETY DATA SHEET

Sika® Aktivator PRO



Version 2.0

SDS Number: 000000125402

Revision Date: 16.11.2019

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

bis(trimethoxysilylpropyl)amine:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 130 mg/l
Exposure time: 96 h

NOEC (Oncorhynchus mykiss (rainbow trout)): 100 mg/l

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h

3-trimethoxysilylpropane-1-thiol:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 12.3 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 6.7 mg/l
aquatic invertebrates Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemi-

SAFETY DATA SHEET

Sika® Aktivator PRO



Version 2.0

SDS Number: 000000125402

Revision Date: 16.11.2019

cal or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1866
Proper shipping name : Resin solution
Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

UN number : UN 1866
Proper shipping name : RESIN SOLUTION
(n-heptane)
Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number : UN 1866
Proper shipping name : RESIN SOLUTION
Class : 3
Packing group : II
Labels : 3
Hazchem Code : •3YE

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

SAFETY DATA SHEET

Sika® Aktivator PRO



Version 2.0

SDS Number: 000000125402

Revision Date: 16.11.2019

Standard for the Uniform Scheduling of Medicines and Poisons : No poison schedule number allocated

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

Prohibition/Licensing Requirements : There is no applicable prohibition or notification/licensing requirements, including for carcinogens under Commonwealth, State or Territory legislation.

The components of this product are reported in the following inventories:

AICS : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Date format : dd.mm.yyyy

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.