Sikadur-300 Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.07.2020

 2.1
 04.06.2022
 000000207639
 Date of first issue: 16.03.2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikadur-300 Part A

Product code : 000000207639

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street

Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45 Telefax : +61 2 9725 33 30 Emergency telephone num- : +61 1800 033 111

ber

Recommended use of the chemical and restrictions on use

Product use : Sealant/adhesive

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion/irritation : Category 2

Serious eye damage/eye irri-

tation

Category 2A

Skin sensitisation : Category 1

Short-term (acute) aquatic

hazard

Category 2

Long-term (chronic) aquatic

hazard

Category 2

GHS label elements

Hazard pictograms





Signal word : Warning

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Sikadur-300 Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.07.2020

 2.1
 04.06.2022
 000000207639
 Date of first issue: 16.03.2015

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical ad-

vice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ at-

tention.

P362 Take off contaminated clothing and wash before reuse.

P391 Collect spillage.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
reaction product: bisphenol-A-(epichlorhydrin);	25068-38-6	>= 60 -<= 100
epoxy resin (number average molecular weight		
≤ 700)		

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

Sikadur-300 Part A



Version Date of last issue: 08.07.2020 Revision Date: SDS Number: 000000207639 04.06.2022 Date of first issue: 16.03.2015 2.1

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

irritant effects sensitising effects Allergic reactions **Excessive lachrymation**

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms. Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

Notes to physician Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

Hazardous combustion prod: :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

ods

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Hazchem Code •3Z

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : Use personal protective equipment. tive equipment and emergency procedures

Deny access to unprotected persons.

Environmental precautions

: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

Soak up with inert absorbent material (e.g. sand, silica gel,

Sikadur-300 Part A



Date of last issue: 08.07.2020 Version Revision Date: SDS Number: 000000207639 04.06.2022 Date of first issue: 16.03.2015 2.1

containment and cleaning up acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Advice on safe handling Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Handle in accordance with good industrial hygiene and safety Hygiene measures

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage Keep container tightly closed in a dry and well-ventilated

Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Appropriate engineering

controls

Use adequate ventilation and/or engineering controls to pre-

vent exposure to vapours.

Personal protective equipment

Respiratory protection : No special measures required.

> Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Hand protection : Chemical-resistant, impervious gloves complying with an

> approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Follow AS/NZS 1337.1

Recommended: Butyl rubber/nitrile rubber gloves.

Sikadur-300 Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.07.2020

 2.1
 04.06.2022
 000000207639
 Date of first issue: 16.03.2015

Contaminated gloves should be removed.

Eye protection : Safety glasses

Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working

clothing, long trousers) Follow AS 2210:3

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : yellow

Odour : very faint

Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing :

point

Boiling point/boiling range : No data available

Flash point : ca. 266 °C (511 °F)

(Method: closed cup)

No data available

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : 0.001 hPa

Relative vapour density : No data available

Density : ca. 1.16 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Sikadur-300 Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.07.2020

 2.1
 04.06.2022
 000000207639
 Date of first issue: 16.03.2015

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : $> 20.5 \text{ mm2/s} (40 ^{\circ}\text{C} (104 ^{\circ}\text{F}))$

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control)

Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : see section 7.

No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular

weight ≤ 700):

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Sikadur-300 Part A



Version Date of last issue: 08.07.2020 Revision Date: SDS Number: 000000207639 Date of first issue: 16.03.2015 04.06.2022 2.1

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular

weight ≤ 700):

: LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Toxicity to fish

Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l

aquatic invertebrates

Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Sikadur-300 Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.07.2020

 2.1
 04.06.2022
 000000207639
 Date of first issue: 16.03.2015

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(epoxy resin)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo : 964

aircraft)

Packing instruction (passen- :

964

ger aircraft)
IATA-DGR

Transport in accordance with special regulation A 197

IMDG-Code

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(epoxy resin)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

IMDG-Code

Transport in accordance with 2.10.2.7 of the IMDG-Code

Sikadur-300 Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.07.2020

 2.1
 04.06.2022
 000000207639
 Date of first issue: 16.03.2015

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(epoxy resin)

Class : 9
Packing group : III
Labels : 9
Hazchem Code : •3Z

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : Schedule 5

Scheduling of Medicines and

Poisons

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements

Not applicable

There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions.

The components of this product are reported in the following inventories:

AICS : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date : 04.06.2022 Date format : dd.mm.yyyy

Full text of other abbreviations

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

Sikadur-300 Part A



2.1 04.06.2022 000000207639 Date of first issue: 16.03. EC50 : Half maximal effective concentration GHS : Globally Harmonized System IATA : International Air Transport Association	2015	
GHS : Globally Harmonized System		
GHS : Globally Harmonized System		
·		
IATA : International Air Transport Association		
IMDG : International Maritime Code for Dangerous Goods		
LD50 : Median lethal dosis (the amount of a material, given all at	Median lethal dosis (the amount of a material, given all at	
once, which causes the death of 50% (one half) of a group o	f	
test animals)		
LC50 : Median lethal concentration (concentrations of the chemical	n	
air that kills 50% of the test animals during the observation		
period)		
MARPOL : International Convention for the Prevention of Pollution from		
Ships, 1973 as modified by the Protocol of 1978		
OEL : Occupational Exposure Limit		
PBT : Persistent, bioaccumulative and toxic		
PNEC : Predicted no effect concentration		
REACH : Regulation (EC) No 1907/2006 of the European Parliament		
and of the Council of 18 December 2006 concerning the Reg		
istration, Evaluation, Authorisation and Restriction of Chemi-		
cals (REACH), establishing a European Chemicals Agency		
SVHC : Substances of Very High Concern		
vPvB : Very persistent and very bioaccumulative		

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN