Sanitized Tile & Grout Sealer



Version Revision Date: Date of last issue: -SDS Number:

100000031649 Date of first issue: 19.04.2022 19.04.2022 1.0

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sanitized Tile & Grout Sealer

Product code : 100000031649

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street

Wetherill Park. NSW 2164

Telephone : +61 2 9725 11 45 : +61 2 9725 33 30 Telefax : +61 1800 033 111 Emergency telephone num-

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

single exposure

Specific target organ toxicity - : Category 3 (Central nervous system)

repeated exposure

(Inhalation)

Specific target organ toxicity - : Category 1 (Central nervous system)

Aspiration hazard : Category 1

Short-term (acute) aquatic

hazard

Category 2

Long-term (chronic) aquatic

hazard

: Category 2

GHS label elements

Hazard pictograms







Signal word

Hazard statements H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs (Central nervous system)

through prolonged or repeated exposure if inhaled. H411 Toxic to aquatic life with long lasting effects.

Sanitized Tile & Grout Sealer



Version Revision Date: SDS Number: Date of last issue: -

1.0 19.04.2022 100000031649 Date of first issue: 19.04.2022

Precautionary statements

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equip-

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P260 Do not breathe mist or vapours.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection / force protection / heavier protection

tion/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P314 Get medical advice/ attention if you feel unwell.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Hydrocarbons, C9-C12, n-alkanes, isoalkanes,	64742-82-1	>= 60 -<= 100
cyclics, aromatics (2-25%)		

Sanitized Tile & Grout Sealer



Version Revision Date: SDS Number: Date of last issue: -

1.0 19.04.2022 100000031649 Date of first issue: 19.04.2022

Distillates (petroleum), hydro- treated light 64742-47-8 < 10

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.

Most important symptoms

and effects, both acute and

delayed

Risk of serious damage to the lungs (by aspiration).

Aspiration may cause pulmonary oedema and pneumonitis.

Loss of balance

Vertigo

See Section 11 for more detailed information on health effects

and symptoms.

May be fatal if swallowed and enters airways.

May cause drowsiness or dizziness.

Causes damage to organs through prolonged or repeated

exposure if inhaled.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

Water

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod- : No hazardous combustion products are known

Sanitized Tile & Grout Sealer



Version Revision Date: SDS Number: Date of last issue: -

1.0 19.04.2022 100000031649 Date of first issue: 19.04.2022

ucts

Specific extinguishing meth-

ods

Use water spray to cool unopened containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Hazchem Code : 3Y

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.
Remove all sources of ignition.

Deny access to unprotected persons.

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, ver-

miculite) and place in container for disposal according to local

/ national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Use explosion-proof equipment.

Keep away from heat/ sparks/ open flames/ hot surfaces. No

smoking.

Take precautionary measures against electrostatic discharg-

es.

Advice on safe handling

Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

products

Hygiene measures : Handle in accordance with good industrial hygiene and safety

Sanitized Tile & Grout Sealer



Version Revision Date: SDS Number: Date of last issue: -

1.0 19.04.2022 100000031649 Date of first issue: 19.04.2022

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
Components	O/10-110.	(Form of	ters / Permissible	Dasis
		`		
		exposure)	concentration	
Hydrocarbons, C9-C12, n-	64742-82-1	TWA	900 mg/m3	AU OEL
alkanes, isoalkanes, cyclics,				
aromatics (2-25%)				
Distillates (petroleum), hydro-	64742-47-8	TWA (Mist)	5 mg/m3	AU OEL
treated light		, ,		

Appropriate engineering

controls

Use adequate ventilation and/or engineering controls to pre-

vent exposure to vapours.

Avoid vapor formation.

Provide appropriate exhaust ventilation at places where va-

por is formed.

Personal protective equipment

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

organic vapor filter (Type A)

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Follow AS/NZS 1337.1

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Eye protection : Safety glasses

Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working

clothing, long trousers) Follow AS 2210:3

Protective clothing needs to be made of cotton.

Sanitized Tile & Grout Sealer



Version Revision Date: SDS Number: Date of last issue: -

1.0 19.04.2022 100000031649 Date of first issue: 19.04.2022

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : clear

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/range / Freezing :

noint

No data available

Boiling point/boiling range : No data available

Flash point : ca. 32 °C (90 °F)

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

7 %(V)

Lower explosion limit / Lower

flammability limit

0.5 %(V)

Vapour pressure : 3.9997 hPa

Relative vapour density : No data available

Density : ca. 0.8 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

: No data available

octanol/water

Auto-ignition temperature : 235 °C

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : No data available

Sanitized Tile & Grout Sealer



Version Revision Date: SDS Number: Date of last issue: -

1.0 19.04.2022 100000031649 Date of first issue: 19.04.2022

Oxidizing properties : No data available

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 94.84% w/w

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions. Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : see section 7.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Components:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Assessment : Repeated exposure may cause skin dryness or cracking.

Distillates (petroleum), hydro- treated light:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Sanitized Tile & Grout Sealer



Version Revision Date: SDS Number: Date of last issue: -

1.0 19.04.2022 100000031649 Date of first issue: 19.04.2022

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

: Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Sanitized Tile & Grout Sealer



Version Revision Date: SDS Number: Date of last issue: -

1.0 19.04.2022 100000031649 Date of first issue: 19.04.2022

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1300

Proper shipping name : Turpentine substitute

Class : 3 Packing group : III

Labels : Flammable Liquids

Packing instruction (cargo : 366

aircraft)

Packing instruction (passen- : 355

ger aircraft)

IMDG-Code

UN number : UN 1300

Proper shipping name : TURPENTINE SUBSTITUTE

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E

Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number : UN 1300

Proper shipping name : TURPENTINE SUBSTITUTE

Class : 3
Packing group : III
Labels : 3
Hazchem Code : 3Y

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : No poison schedule number allocated

Scheduling of Medicines and

Poisons

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

: Not applicable

Sanitized Tile & Grout Sealer



Version Revision Date: SDS Number: Date of last issue: -

1.0 19.04.2022 100000031649 Date of first issue: 19.04.2022

Prohibition/Licensing Requirements : There is no applicable prohibition,

authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions.

The components of this product are reported in the following inventories:

AIIC : All components are listed on the inventory, regulatory obliga-

tions/restrictions apply

SECTION 16. OTHER INFORMATION

Revision Date : 19.04.2022 Date format : dd.mm.yyyy

Full text of other abbreviations

AU OEL : Australia. Workplace Exposure Standards for Airborne Con-

taminants.

AU OEL / TWA : Exposure standard - time weighted average

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

est animals)

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

Sanitized Tile & Grout Sealer



Version Revision Date: SDS Number: Date of last issue: -

1.0 19.04.2022 100000031649 Date of first issue: 19.04.2022

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN