SikaGard[®]-6220



Version 3.0	Revision Date: 16.06.2023		SDS Number: 100000001474	Date of last issue: 11.09.2021 Date of first issue: 11.10.2016
SECTION ²	1. PRODUCT AND COM	IPA	NY IDENTIFICATION	
Produ	Product name		SikaGard [®] -6220	
Manu	facturer or supplier's d	etai	ils	
Comp	any	:	Sika Australia Pty. Ltd. 55 Elizabeth Street Wetherill Park, NSW 2164	
Telepł	none	:	+61 2 9725 11 45	
Emerg	gency telephone number	:	+61 1800 033 111	
Telefa	х	:	+61 2 9725 33 30	
Recor	nmended use of the ch	em	ical and restrictions on use	
	ct use	:	Surfaces protection	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification		
Flammable liquids	:	Category 3
Specific target organ toxicity - single exposure	:	Category 3 (Central nervous system)
Long-term (chronic) aquatic hazard	:	Category 3
GHS label elements		
Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	:	Prevention:
		P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment.

SikaGard®-6220



rsion Revision Date: 16.06.2023		SDS Number: 100000001474	Date of last issue: 11.09.2021 Date of first issue: 11.10.2016
		ment. P242 Use non-sparking too P243 Take action to prever P261 Avoid breathing mist P271 Use only outdoors or P273 Avoid release to the e	nt static discharges. or vapours. in a well-ventilated area. environment. es/ protective clothing/ eye protec-
		ly all contaminated clothing P304 + P340 + P312 IF INI and keep comfortable for b doctor if you feel unwell.	HALED: Remove person to fresh air reathing. Call a POISON CENTER/ : Use dry sand, dry chemical or
		tightly closed.	II-ventilated place. Keep container II-ventilated place. Keep cool.
		Disposal: P501 Dispose of contents/ disposal plant.	container to an approved waste
Other	hazards which do not	result in classification	
None	known.		

Substance / Mixture : Mixture

Components

General advice

Chemical name	CAS-No.	Concentration (% w/w)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes,	64742-48-9	>= 30 -< 60
cyclics, <2% aromatics		
Aromatic hydrocarbons, C9; Alkylbenzenes;	128601-23-0	>= 2.5 -< 10
C9-aromatics		
Sulfonic acids, petroleum, sodium salts	68608-26-4	< 10
ethylene glycol monobutyl ether	111-76-2	< 10

SECTION 4. FIRST AID MEASURES

: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.

SikaGard[®]-6220



Versio 3.0	on	Revision Date: 16.06.2023		SDS Number: 100000001474	Date of last issue: 11.09.2021 Date of first issue: 11.10.2016
If inhaled		:	Move to fresh air. Consult a physician after significa	nt exposure.	
In case of skin contact		:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.		
	In case o	f eye contact	:	Remove contact lenses. Keep eye wide open while rinsing If eye irritation persists, consult a	
	If swallow	ved	:	Clean mouth with water and drink Do not give milk or alcoholic beve Never give anything by mouth to a	rages.
		ortant symptoms ts, both acute and	:	No known significant effects or ha Loss of balance Vertigo See Section 11 for more detailed and symptoms. May cause drowsiness or dizzines	information on health effects
	Notes to	physician	:	Treat symptomatically.	

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	Water High volume water jet
Specific hazards during fire- fighting	:	Do not use a solid water stream as it may scatter and spread fire.
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
Specific extinguishing meth- ods	:	Use water spray to cool unopened containers.

SikaGard[®]-6220



Version 3.0	Revision Date: 16.06.2023		SDS Number: 100000001474	Date of last issue: 11.09.2021 Date of first issue: 11.10.2016	
	ial protective equipment efighters	:	In the event of fire, wear se	If-contained breathing apparatus.	
Hazc	Hazchem Code		•3Y		
Perso tive e	6. ACCIDENTAL RELEA		Use personal protective eq Remove all sources of ignit	ion.	
	gency procedures Environmental precautions :		Deny access to unprotected persons. Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.		
	ods and materials for inment and cleaning up	:	sorbent material, (e.g. sand	collect with non-combustible ab- d, earth, diatomaceous earth, ver- niner for disposal according to local section 13).	

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharg- es.
Advice on safe handling	:	Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
Conditions for safe storage	:	Store in original container.

SikaGard®-6220



Version	Revision Date: 16.06.2023	SDS Number:	Date of last issue: 11.09.2021
3.0		100000001474	Date of first issue: 11.10.2016
		Keep in a well-ventilated pla Containers which are opene kept upright to prevent leak Observe label precautions.	ed must be carefully resealed and

Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parame- ters / Permissible	Basis
		exposure)	concentration	
ethylene glycol monobutyl	111-76-2	TWA	20 ppm	AU OEL
ether			96.9 mg/m3	
	Further information	ation: Skin absor	rption	
		STEL	50 ppm 242 mg/m3	AU OEL

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
ethylene glycol mono- butyl ether	111-76-2	Butoxyace- tic acid (BAA)	Urine	End of shift (As soon as possible after ex- posure ceases)	200 mg/g Creatinine	ACGIH BEI
Appropriate engineerin controls	ver Ave Pro	nt exposure to bid vapor form	vapours. ation.	Ū.	ing controls to p	
Personal protective equ	uipment					
Perpiratory protection	· In (case of inadea	uato vontilat	ion woor roc	piratory protect	ion

Respiratory protection	Respirator exposure le working lim	inadequate ventilation wear respiratory protection. selection must be based on known or anticipated evels, the hazards of the product and the safe hits of the selected respirator. por filter (Type A)
Hand protection	approved s chemical p essary. Follow AS/ Recomme	resistant, impervious gloves complying with an standard should be worn at all times when handling roducts if a risk assessment indicates this is nec- NZS 1337.1 nded: Butyl rubber/nitrile rubber gloves. ited gloves should be removed.

SikaGard[®]-6220



Version 3.0	Revision Date: 16.06.2023		SDS Number: 100000001474	Date of last issue: 11.09.2021 Date of first issue: 11.10.2016
Еуе рі	rotection	:	Safety glasses	
Skin and body protection		:	Protective clothing (e.g. safe clothing, long trousers) Follow AS 2210:3 Protective clothing needs to	ety shoes, long-sleeved working be made of cotton.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	various
Odour	:	solvent-like
Odour Threshold	:	No data available
рН	:	Not applicable substance/mixture is non-polar/aprotic
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	ca. 165 - 181 °C (329 - 358 °F)
Flash point	:	ca. 38 °C (100 °F) (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	Upper flammability limit 10.0 %(V)
Lower explosion limit / Lower flammability limit	:	Lower flammability limit 0.6 %(V)
Vapour pressure	:	ca. 1 hPa (20 °C (68 °F))
Relative vapour density	:	No data available
Density	:	ca. 0.87 g/cm3 (20 °C (68 °F))

SikaGard®-6220



Versio 3.0	n Revision Date: 16.06.2023		SDS Number: 100000001474	Date of last issue: 11.09.2021 Date of first issue: 11.10.2016
S	Solubility(ies) Water solubility	:	insoluble	
	Solubility in other solvents	:	No data available	
Partition coefficient: n- octanol/water		:	No data available	
A	Auto-ignition temperature	:	255 °C	
C	Decomposition temperature	:	No data available	
٨	/iscosity Viscosity, dynamic	:	No data available	
	Viscosity, kinematic	:	> 20.5 mm2/s (40 °C (104 °F))	
E	Explosive properties	:	No data available	
C	Dxidizing properties	:	No data available	
١	/olatile organic compounds	:	Directive 2010/75/EU of 24 Nove emissions (integrated pollution pr Volatile organic compounds (VOC	evention and control)

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reac- tions	:	Stable under recommended storage conditions. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	see section 7.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

<u>Components:</u> Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

SikaGard®-6220



ersion .0	Revision Date: 16.06.2023	SDS Number: 100000001474	Date of last issue: 11.09.2021 Date of first issue: 11.10.2016
Acute	oral toxicity	: LD50 Oral (Rat): > 5,000	mg/kg
Acute	dermal toxicity	: LD50 Dermal (Rabbit): 3,	160 mg/kg
	ene glycol monobutyl oral toxicity	ether: : LD50 Oral: 1,200 mg/kg	
Skin d	corrosion/irritation		
Not cla	assified based on avail	able information.	
	us eye damage/eye iri assified based on avail		
Respi	ratory or skin sensitis	sation	
	sensitisation assified based on avail	able information.	
-	ratory sensitisation assified based on avail	able information.	
Chror	nic toxicity		
	cell mutagenicity assified based on avail	able information.	
	n ogenicity assified based on avail	able information.	
-	oductive toxicity assified based on avail	able information.	
	- single exposure ause drowsiness or diz	ziness.	
STOT	- repeated exposure		
Not cla	assified based on avail	able information.	
-	ation toxicity assified based on avail	able information.	
SECTION	12. ECOLOGICAL INF	ORMATION	
Ecoto	oxicity		
	-		
Hydro Toxici		Ikanes, isoalkanes, cyclics, < : EC50 (Daphnia magna (V Exposure time: 48 h	

Persistence and degradability

No data available

SikaGard[®]-6220



Version 3.0	Revision Date: 16.06.2023	SDS Number: 100000001474	Date of last issue: 11.09.2021 Date of first issue: 11.10.2016
	oaccumulative potential data available		
	bbility in soil data available		
Ot	her adverse effects		
Ad	oduct: ditional ecological infor- ation	An environmental hazard cannot unprofessional handling or dispo Harmful to aquatic life with long l	sal.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods Waste from residues :	Send to a licensed waste management company.
	The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemi- cal or used container.
Contaminated packaging :	Empty remaining contents. Dispose of as unused product.
	Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR		
UN/ID No.	:	UN 1139
Proper shipping name	:	Coating solution
Class	:	3
Packing group	:	III
Labels	:	Flammable Liquids
Packing instruction (cargo	:	366
aircraft)		
Packing instruction (passen-	:	355
ger aircraft)		
IMDG-Code		
UN number		UN 1139
Proper shipping name	:	COATING SOLUTION
Fibbel shipping hame	•	COATING SOLUTION

SikaGard®-6220



Version 3.0	Revision Date: 16.06.2023		SDS Number: 100000001474	Date of last issue: 11.09.2021 Date of first issue: 11.10.2016
Labels EmS (ng group s Code e pollutant	: no	E, <u>S-E</u> one.	
	•	-	nex II of MARPOL 73/78	and the IBC Code
	oplicable for product as nal Regulations	supplie	1.	
Class Packi Labels	er shipping name ng group		N 1139 DATING SOLUTION Y	
The tr upon t Trans	the properties of the u	s) provide npackage s may va	ed material as it is describ	tional purposes only, and solely based bed within this Safety Data Sheet. Ition, package sizes, and variations in
SECTION	15. REGULATORY IN	FORMA	ΓΙΟΝ	
Stand	y, health and environ ard for the Uniform duling of Medicines and	: No	egulations/legislation s	specific for the substance or mixture er allocated

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors	:	Not applicable
Prohibition/Licensing Requirements	:	There is no applicable prohibition, authorisation and restricted use requirements, including for carcino- gens referred to in Schedule 10 of the model WHS Act and Regula- tions.

The components of this product are reported in the following inventories:

: On the inventory, or in compliance with the inventory AICS

SECTION 16. OTHER INFORMATION

Poisons

Revision Date	: 16.06.2023	
Date format	: dd.mm.yyyy	
	10 / 11	

SikaGard®-6220



Version	Revision Date:	SDS Number:	Date of last issue: 11.09.2021
3.0	16.06.2023	10000001474	Date of first issue: 11.10.2016

ACGIH BEI AU OEL	:	ACGIH - Biological Exposure Indices (BEI) Australia. Workplace Exposure Standards for Airborne Con- taminants.
AU OEL / TWA	:	Exposure standard - time weighted average
AU OEL / STEL	:	Exposure standard - short term exposure limit
ADG	:	Australian Dangerous Goods Code.
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative
		·

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

AU / EN