Sikadur 42HP Part A



Version	Revision Date:	SDS Number:	Date of last issue: 29.01.2022
2.1	26.02.2022	00000211036	Date of first issue: 19.08.2018

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name	Sikadur 42HP Part A						
Product code	: 000000211036						
Manufacturer or supplier's o	details						
Company	: Sika Australia Pty. Ltd. 55 Elizabeth Street Wetherill Park, NSW 2164						
Telephone	: +61 2 9725 11 45						
Telefax	: +61 2 9725 33 30						
Emergency telephone num- ber	: +61 1800 033 111						
Recommended use of the chemical and restrictions on use							
Product use	: Sealing system						

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification		
Skin corrosion/irritation	:	Category 2
Serious eye damage/eye irri- tation	:	Category 2A
Skin sensitisation	:	Category 1
Short-term (acute) aquatic hazard	:	Category 2
Long-term (chronic) aquatic hazard	:	Category 2
GHS label elements		
Hazard pictograms	:	! ***
Signal word	:	Warning
Hazard statements	:	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	:	Prevention:
		P261 Avoid breathing mist or vapours.

Sikadur 42HP Part A



Version 2.1	Revision Date: 26.02.2022	SDS Number: 000000211036	Date of last issue: 29.01.2022 Date of first issue: 19.08.2018
		the workplace. P273 Avoid release to the o	clothing should not be allowed out of
		for several minutes. Removeasy to do. Continue rinsin P333 + P313 If skin irritatiovice/ attention. P337 + P313 If eye irritatiotention.	EYES: Rinse cautiously with water ve contact lenses, if present and
		Disposal: P501 Dispose of contents/ disposal plant.	container to an approved waste

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	25068-38-6	>= 60 -<= 100
reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	9003-36-5	>= 2.5 -< 10
bis(isopropyl)naphthalene	38640-62-9	>= 2.5 -< 10
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	>= 1 -< 10

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water.
	2 / 10

Sikadur 42HP Part A



Version 2.1	Revision Date: 26.02.2022		SDS Number: 000000211036	Date of last issue: 29.01.2022 Date of first issue: 19.08.2018
			If symptoms persist, call a physic	ian.
In cas	In case of eye contact		Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.	
lf swa	If swallowed		Clean mouth with water and drink Do not give milk or alcoholic beve Never give anything by mouth to a Obtain medical attention.	erages.
Most important symptoms and effects, both acute and delayed		:	irritant effects sensitising effects Allergic reactions Excessive lachrymation Dermatitis See Section 11 for more detailed and symptoms. Causes skin irritation. May cause an allergic skin reaction Causes serious eye irritation.	
Notes	to physician	:	Treat symptomatically.	

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
Specific extinguishing meth- ods	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Hazchem Code	:	•3Z

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :	Use personal protective equipment.
tive equipment and emer-	Deny access to unprotected persons.
gency procedures	

Sikadur 42HP Part A



Version 2.1	Revision Date: 26.02.2022		SDS Number: 000000211036	Date of last issue: 29.01.2022 Date of first issue: 19.08.2018
Envir	onmental precautions	:		ter or sanitary sewer system. rivers and lakes or drains inform
	Methods and materials for : containment and cleaning up		Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.	
SECTION	7. HANDLING AND ST	OR/	AGE	
	e on protection against nd explosion	:	Normal measures for preven	ntive fire protection.
Advid	e on safe handling	:	section 8). Do not get in eyes, on skin, For personal protection see Persons with a history of ski ma, allergies, chronic or rec not be employed in any prod used. Smoking, eating and drinkin plication area.	
Hygie	ene measures	:	Handle in accordance with g practice. When using do not eat or dr When using do not smoke. Wash hands before breaks	
Conc	litions for safe storage	:	place.	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplac Contains no substances with	ce control parameters occupational exposure limit values.
Appropriate engineering controls	: Use adequate ventilation and/or engineering controls to prevent exposure to vapours.
Personal protective equipn	nent
Respiratory protection	: No special measures required. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe
	4 / 10

Sikadur 42HP Part A



Versior 2.1	n Revision Date: 26.02.2022		SDS Number: 000000211036	Date of last issue: 29.01.2022 Date of first issue: 19.08.2018
Hand protection		:	working limits of the selected respirator. Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec- essary. Follow AS/NZS 1337.1 Recommended: Butyl rubber/nitrile rubber gloves. Contaminated gloves should be removed.	
E	ye protection	:	Safety glasses	
Skin and body protection		:	Protective clothing (e.g. safety sh clothing, long trousers) Follow AS 2210:3	oes, long-sleeved working

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	transparent
Odour	:	epoxy-like
Odour Threshold	:	No data available
рН	:	ca. 7.7
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	> 101 °C (214 °F) (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	0.01 hPa
Relative vapour density	:	No data available
Density	:	ca. 1.14 g/cm3 (20 °C (68 °F))
Solubility(ies) Water solubility	:	insoluble

Sikadur 42HP Part A



Version 2.1	Revision Date: 26.02.2022		SDS Number: 000000211036	Date of last issue: 29.01.2022 Date of first issue: 19.08.2018
5	Solubility in other solvents	:	No data available	
	ition coefficient: n-	:	No data available	
	nol/water p-ignition temperature	:	No data available	
Dec	omposition temperature	:	No data available	
	cosity /iscosity, dynamic	:	No data available	
٨	/iscosity, kinematic	:	> 20.5 mm2/s (40 °C (104 °F))
Exp	losive properties	:	No data available	
Oxic	dizing properties	:	No data available	
Vola	atile organic compounds	:	Directive 2010/75/EU of 24 No emissions (integrated pollution Volatile organic compounds (V	prevention and control)

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.	
Chemical stability	:	The product is chemically stable.	
Possibility of hazardous reac- tions	:	Stable under recommended storage conditions.	
Conditions to avoid	:	No data available	
Incompatible materials	:	see section 7.	
No decomposition if stored and applied as directed.			

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity Not classified based on available information.

Components:		
reaction product: bispheno weight ≤ 700):	I-A	(epichlorhydrin); epoxy resin (number average molecular
Acute oral toxicity	:	LD50 Oral (Rat): > 5,000 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 20,000 mg/kg
bis(isopropyl)naphthalene: Acute oral toxicity	:	LD50 Oral (Rat): > 3,900 mg/kg
		6 / 10

Sikadur 42HP Part A



Vers 2.1	ion	Revision Date: 26.02.2022		SDS Number: 000000211036	Date of last issue: 29.01.2022 Date of first issue: 19.08.2018
	Acute	inhalation toxicity	:	LC50 (Rat): > 5.64 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
	Acute	dermal toxicity	:	LD50 Dermal (Rat): > 4,500 r	ng/kg
		corrosion/irritation es skin irritation.			
		u s eye damage/eye irr es serious eye irritation.		on	
	Respi	ratory or skin sensitis	atio	on	
		sensitisation ause an allergic skin re	actio	on.	
	•	ratory sensitisation assified based on availa	able	information.	
	Chror	nic toxicity			
		cell mutagenicity assified based on availa	able	information.	
		n ogenicity assified based on availa	able	information.	
	•	ductive toxicity assified based on availa	able	information.	
		- single exposure assified based on availa	able	information.	
		- repeated exposure assified based on availa	able	information.	
	•	ation toxicity assified based on availa	able	information.	
SEC		12. ECOLOGICAL INF	ORI	MATION	
	Ecoto	xicity			
	reacti weigh	onents: on product: bispheno it ≤ 700): ty to fish	I-A- :	(epichlorhydrin); epoxy resir LC50 (Oncorhynchus mykiss Exposure time: 96 h	n (number average molecular (rainbow trout)): 2 mg/l

Exposure time: 48 h

EC50 (Daphnia magna (Water flea)): 1.8 mg/l

Toxicity to daphnia and other : aquatic invertebrates

Sikadur 42HP Part A



Version 2.1	Revision Date: 26.02.2022	SDS Number: 000000211036	Date of last issue: 29.01.2022 Date of first issue: 19.08.2018
Persi	stence and degradability	,	
	ta available		
	cumulative potential ta available		
	ity in soil ta available		
Other	adverse effects		
<u>Produ</u>	<u>uct:</u>		

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR		
UN/ID No.	:	UN 3082
Proper shipping name	:	Environmentally hazardous substance, liquid, n.o.s. (epoxy resin)
Class	:	9
Packing group	:	III
Labels	:	Miscellaneous
Packing instruction (cargo aircraft)	:	964
Packing instruction (passen- ger aircraft)	:	964
ĬATA-DGR		
Transport in accordance with	spe	cial regulation A 197

Sikadur 42HP Part A



Version 2.1	Revision Date: 26.02.2022		SDS Number: 000000211036	Date of last issue: 29.01.2022 Date of first issue: 19.08.2018
IMDG	i-Code			
	umber	:	UN 3082	
Prope	er shipping name		ENVIRONMENTALLY HAZ/ N.O.S. (epoxy resin)	ARDOUS SUBSTANCE, LIQUID,
Class		:	9	
Packi	ng group	:	111	
Label	S	:	9	
EmS	Code	:	F-A, S-F	
Marin	e pollutant	:	yes	
IMDG	-Code			
Trans	port in accordance wit	h 2.10	.2.7 of the IMDG-Code	
Trans	sport in bulk accordi	ng to A	Annex II of MARPOL 73/78	and the IBC Code
Not a	pplicable for product a	s supp	lied.	
Natio	nal Regulations			
ADG				
LIN pr	umbor		LINI 2092	

UN number	:	UN 3082
Proper shipping name	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
		N.O.S.
		(epoxy resin)
Class	:	9
Packing group	:	
Labels	:	9
Hazchem Code	:	•3Z

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : Schedule 5 Scheduling of Medicines and Poisons	
International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors	: Not applicable
Prohibition/Licensing Requirements	: There is no applicable prohibition, authorisation and restricted use requirements, including for carcino- gens referred to in Schedule 10 of the model WHS Act and Regula- tions.

The components of this product are reported in the following inventories:

AIIC : On the inventory, or in compliance with the inventory

Sikadur 42HP Part A



Version	Revision Date:	SDS Number:	Date of last issue: 29.01.2022
2.1	26.02.2022	00000211036	Date of first issue: 19.08.2018

SECTION 16. OTHER INFORMATION

Revision Date Date format	:	26.02.2022 dd.mm.yyyy
Full text of other abbreviations		
ADG	:	Australian Dangerous Goods Code.
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
ΙΑΤΑ	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

AU / EN