Sikabond SprayFix



Version Date of last issue: 18.09.2018 Revision Date: SDS Number: 000000620255 Date of first issue: 09.05.2018 13.05.2022 3.0

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikabond SprayFix

Product code : 000000620255

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street

Wetherill Park. NSW 2164

Telephone : +61 2 9725 11 45 Telefax : +61 2 9725 33 30 : +61 1800 033 111 Emergency telephone num-

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Aerosols Category 1

Skin corrosion/irritation Category 2

Reproductive toxicity Category 2

Specific target organ toxicity - : Category 3 (Central nervous system)

single exposure

Long-term (chronic) aquatic

hazard

: Category 3

GHS label elements

Hazard pictograms







Signal word Danger

Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child. H412 Harmful to aquatic life with long lasting effects.

Precautionary statements Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

Sikabond SprayFix



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.09.2018

 3.0
 13.05.2022
 000000620255
 Date of first issue: 09.05.2018

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing mist.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P332 + P313 If skin irritation occurs: Get medical advice/ attention

P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
dimethyl ether	115-10-6	>= 30 -< 60
2-methylpentane	107-83-5	>= 30 -< 60
Naphtha (petroleum), hydrotreated light; Low	64742-49-0	>= 10 -< 20
boiling point hydrogen treated naphtha		
3-methylpentane	96-14-0	< 10
2,3-dimethylbutane	79-29-8	>= 2.5 -< 10
n-hexane	110-54-3	>= 0.25 -< 2.5

SECTION 4. FIRST AID MEASURES

Sikabond SprayFix



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.09.2018

 3.0
 13.05.2022
 000000620255
 Date of first issue: 09.05.2018

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms

and effects, both acute and delayed

irritant effects Dermatitis

Loss of balance

Vertigo

See Section 11 for more detailed information on health effects

and symptoms. Causes skin irritation.

May cause drowsiness or dizziness.

Suspected of damaging fertility or the unborn child.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray jet

Dry powder

Foam

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod: :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

ods

Use water spray to cool unopened containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Sikabond SprayFix



Date of last issue: 18.09.2018 Version Revision Date: SDS Number: Date of first issue: 09.05.2018 13.05.2022 000000620255 3.0

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Hazchem Code 2YE

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment. Deny access to unprotected persons.

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Use explosion-proof equipment.

Keep away from heat/ sparks/ open flames/ hot surfaces. No

smoking.

Do not spray on a naked flame or any incandescent material. Take precautionary measures against electrostatic discharg-

es.

Advice on safe handling Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

products

Hygiene measures Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects.

Store in original container. Keep in a well-ventilated place.

Sikabond SprayFix



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.09.2018

 3.0
 13.05.2022
 000000620255
 Date of first issue: 09.05.2018

Observe label precautions.

Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
dimethyl ether	115-10-6	STEL	500 ppm 950 mg/m3	AU OEL
		TWA	400 ppm 760 mg/m3	AU OEL
2-methylpentane	107-83-5	TWA	500 ppm 1,760 mg/m3	AU OEL
		STEL	1,000 ppm 3,500 mg/m3	AU OEL
Naphtha (petroleum), hy- drotreated light; Low boiling point hydrogen treated naph- tha	64742-49-0	TWA	900 mg/m3	AU OEL
3-methylpentane	96-14-0	TWA	500 ppm 1,760 mg/m3	AU OEL
		STEL	1,000 ppm 3,500 mg/m3	AU OEL
2,3-dimethylbutane	79-29-8	TWA	500 ppm 1,760 mg/m3	AU OEL
		STEL	1,000 ppm 3,500 mg/m3	AU OEL
n-hexane	110-54-3	TWA	20 ppm 72 mg/m3	AU OEL

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
n-hexane	110-54-3	2,5- Hexanedi-	Ürine	End of shift	0.5 mg/l	ACGIH BEI
		one				

Appropriate engineering

controls

Use adequate ventilation and/or engineering controls to pre-

vent exposure to vapours.

Personal protective equipment

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

Sikabond SprayFix



Revision Date: Date of last issue: 18.09.2018 Version SDS Number: Date of first issue: 09.05.2018 13.05.2022 000000620255 3.0

essary.

Follow AS/NZS 1337.1

Safety glasses Eye protection

Skin and body protection Protective clothing (e.g. safety shoes, long-sleeved working

> clothing, long trousers) Follow AS 2210:3

Protective clothing needs to be made of cotton.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Colour opaque

Odour hydrocarbon-like

Odour Threshold No data available

Not applicable рΗ

Melting point/range / Freezing :

Boiling point/boiling range

No data available

Flash point 41 °C (106 °F)

(Method: closed cup)

No data available

Evaporation rate No data available

Flammability (solid, gas) No data available

Upper explosion limit / Upper

flammability limit

7.4 %(V)

Lower explosion limit / Lower :

flammability limit

1.1 %(V)

Vapour pressure 5100 hPa

Relative vapour density No data available

0.9 g/cm3 (20 °C (68 °F)) Density

Solubility(ies)

No data available Water solubility

Solubility in other solvents No data available

Partition coefficient: n-

octanol/water

No data available

Sikabond SprayFix



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.09.2018

 3.0
 13.05.2022
 000000620255
 Date of first issue: 09.05.2018

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 7 mm2/s (40 °C (104 °F))

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 99% w/w

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : see section 7.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

2,3-dimethylbutane:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Sikabond SprayFix



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.09.2018

 3.0
 13.05.2022
 000000620255
 Date of first issue: 09.05.2018

Respiratory sensitisation

Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Product:

Reproductive toxicity - As-

: Suspected human reproductive toxicant

sessment

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

Sikabond SprayFix



Revision Date: Date of last issue: 18.09.2018 Version SDS Number: 000000620255 Date of first issue: 09.05.2018 13.05.2022 3.0

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging Empty remaining contents.

> Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

: UN 1950 UN/ID No.

Proper shipping name : Aerosols, flammable

Class : 2.1

: Not assigned by regulation Packing group

: Flammable Gas Labels : 203

Packing instruction (cargo

aircraft)

Packing instruction (passen- : 203

ger aircraft)

IMDG-Code

UN number UN 1950 Proper shipping name **AEROSOLS**

Class 2.1

Packing group Not assigned by regulation

Labels 2.1 EmS Code F-D, S-U Marine pollutant no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number UN 1950 Proper shipping name **AEROSOLS**

Class 2.1

Packing group Not assigned by regulation

Labels 2.1 2YE Hazchem Code

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet.

Sikabond SprayFix



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.09.2018

 3.0
 13.05.2022
 000000620255
 Date of first issue: 09.05.2018

Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : No poison schedule number allocated

Scheduling of Medicines and

Poisons

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements

Not applicable

There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions

The components of this product are reported in the following inventories:

AIIC : Listed introduction

AICS : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date : 13.05.2022 Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

AU OEL : Australia. Workplace Exposure Standards for Airborne Con-

taminants

AU OEL / TWA : Exposure standard - time weighted average AU OEL / STEL : Exposure standard - short term exposure limit

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration
GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Sikabond SprayFix



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.09.2018

 3.0
 13.05.2022
 000000620255
 Date of first issue: 09.05.2018

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN