

PRODUCT DATA SHEET

Sika AnchorFix® Static Mixers / Nozzles

AnchorFix® resin mixing and application accessory

DESCRIPTION

Sika AnchorFix® Static Mixers / Nozzles are fixed onto each AnchorFix® product to achieve the correct mixing of the 2-part cartridge anchoring adhesive and application into drilled anchoring holes.

USES

- Mixing of resin
- Application into drill anchoring holes

CHARACTERISTICS / ADVANTAGES APPROVALS / CERTIFICATES

All Sika AnchorFix® Static Mixers / Nozzles are referenced in the corresponding approvals of each Sika AnchorFix® product

PRODUCT INFORMATION

Packaging	5 per bag.
Appearance and colour	Transparent
Shelf life	Unlimited
Storage conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +35 °C. Always refer to packaging.
SYSTEM INFORMATION	
System structure	The following system products must be used: Sika AnchorFix® 1 anchoring adhesive Sika AnchorFix® Static Mixers / Nozzles

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

- Do not use other types of static mixer nozzles, only
- use Sika AnchorFix® static mixer nozzles.

 Do not cut and reduce length of static mixer nozzle as this will affect the mixing performance.
- Only use Sika AnchorFix® anchoring adhesives with Sika AnchorFix® Static Mixers / Nozzles.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

APPLICATION METHOD / TOOLS

Before the Sika AnchorFix® adhesive is applied, screw the correct static mixer nozzle onto each Sika Anchor-Fix® Cartridge after removing the cartridge cap. It is essential the correct mixing nozzle is used with the Sika AnchorFix® chemical anchoring systems at all times. Use of non-approved mixing nozzles may insufficiently mix the product, vary the consumption and reduce performance.

When Sika AnchorFix® Static Mixers / Nozzles has been fixed into position, pump gun at least 2 times until both parts are extruded as one consistant colour. Do not use this material. Release the gun pressure and clean the static mixer opening with a cloth. For Sika AnchorFix® anchoring adhesive installation procedure, refer to the individual Product Data Sheets and any associated further documentation.

CLEANING OF EQUIPMENT

Once used Sika AnchorFix® Static Mixers / Nozzles cannot be cleaned

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product

Product Data Sheet

Sika AnchorFix® Static Mixers / Nozzles April 2023, Version 02.01 020205020000000003



LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Australia Pty Limited

ABN 12 001 342 329 aus.sika.com Tel: 1300 22 33 48

Sika Anchor Fix Static Mixers Nozzles-en-AU- (04-2023)-2-1.pdf

