

**BUILDING TRUST** 

### PRODUCT DATA SHEET

# Sika® Cleaner PCA

### Cleaning pad and primer applicator

### TYPICAL PRODUCT DATA

Chemical base	Open-pore, expanded melamine resin
Colour (CQP001-1)	Light grey
Application method	Dry scrub or wet scrub with Sika® CleanGlass or
	Sika® Cleaner G+P

### **DESCRIPTION**

Sika® Cleaner PCA is a smart cleaning pad based on melamine foam. It is used for removal of contamination or cleaning of windshields and other surfaces.

Additionally it can be used to apply certain  $Sika^{\otimes}$  Primers.

### **PRODUCT BENEFITS**

- Quick, clean and simple way to remove contamination and label residues.
- Suitable as primer applicator
- EHS friendly

### AREAS OF APPLICATION

Sika® Cleaner PCA is designed for the removal of contamination on ceramic frits or glass. It can also be used for the removal of label residues and other kinds of contamination.

Sika® Cleaner PCA is well suited to apply Sika® Primers used in the Automotive Glass Replacement business.

This product is suitable for experienced professional users only. Tests with actual substrates and conditions have to be performed to ensure adhesion and material compatibility.

## PRODUCT DATA SHEET

**Sika® Cleaner PCA**Version 02.01 (03 - 2023), en\_AU
01940000030020000

### METHOD OF APPLICATION

To remove the contamination from windshields, use Sika® CleanGlass respectively Sika® Cleaner G+P or an equivalent non-antistatic glass cleaner to wet the surface and detect contamination. Start scrubbing the bond area with Sika® Cleaner PCA. For heavy contamination Sika® Cleaner PCA can be used dry to increase effectivness.

Always consider that it is designed for single use application only.

Wipe the Sika® CleanGlass off and allow the surface to dry completely before the next step in surface preparation is performed.

#### **IMPORTANT NOTE**

Compatibility with the current substrate has to be verified prior to the application. Before using Sika® Cleaner PCA on sensitive surfaces (e.g. plastics, etc.) it is recommended to test a small, possibly non-visible area of the base material.

Prior to adhesive application the surface has to be pre-treated according to Sika's surface preparation recommendations.

### **FURTHER INFORMATION**

The information herein is offered for general guidance only. Advice on specific applications is available on request from the Technical Department of Sika Industry.

### PACKAGING INFORMATION

Вс	X	168	pieces

### **BASIS OF PRODUCT DATA**

All technical data stated in this document are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### **DISCLAIMER**

The information, and, in particular, the recommendations relating to the application and enduse of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika® Cleaner PCA Version 02.01 (03 - 2023), en\_AU 019400000030020000 Sika Australia Pty Limited ABN 12 001 342 329 aus.sika.com Tel: 1300 22 33 48

