Sika® Primer-207



Version Date of last issue: -Revision Date: SDS Number:

10000005704 Date of first issue: 05.04.2022 05.04.2022 1.0

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sika® Primer-207

Product code : 10000005704

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street

Wetherill Park. NSW 2164

Telephone : +61 2 9725 11 45 +61 2 9725 33 30 Telefax : +61 1800 033 111 Emergency telephone num-

Recommended use of the chemical and restrictions on use

Product use : Pretreatment agent, Product is not intended for consumer use

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2

Serious eye damage/eye irri-

tation

: Category 2A

Skin sensitisation : Category 1

single exposure

Specific target organ toxicity - : Category 3 (Central nervous system)

GHS label elements

Hazard pictograms





Signal word Danger

Hazard statements H225 Highly flammable liquid and vapour.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Precautionary statements Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking. P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

Sika® Primer-207



Version Revision Date: SDS Number: Date of last issue: -

1.0 05.04.2022 100000005704 Date of first issue: 05.04.2022

P241 Use explosion-proof electrical/ ventilating/ lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing mist or vapours.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
ethyl acetate	141-78-6	>= 30 -< 60
butanone	78-93-3	>= 30 -< 60
aromatic polyisocyanate	53317-61-6	>= 1 -< 10
tris(p-isocyanatophenyl) thiophosphate	4151-51-3	0 -< 10

Sika® Primer-207



Version Revision Date: SDS Number: Date of last issue: -

1.0 05.04.2022 100000005704 Date of first issue: 05.04.2022

Tris(3-(trimethoxysilyI)propyI)isocyanurate26115-70-80 -< 10</th>4,4'-methylenediphenyl diisocyanate101-68-80 -< 1</td>

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

and effects, b

irritant effects

sensitising effects Allergic reactions

Excessive lachrymation

Loss of balance

Vertigo

See Section 11 for more detailed information on health effects

and symptoms.

May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: Water

High volume water jet

Specific hazards during fire-

fighting

Do not use a solid water stream as it may scatter and spread

fire.

Sika® Primer-207



Date of last issue: -Version Revision Date: SDS Number:

Date of first issue: 05.04.2022 05.04.2022 10000005704 1.0

Hazardous combustion prod- :

No hazardous combustion products are known

Specific extinguishing meth-

ods

Use water spray to cool unopened containers.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Hazchem Code •3YE

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emergency procedures

Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons.

Environmental precautions Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Use explosion-proof equipment.

Keep away from heat/ sparks/ open flames/ hot surfaces. No

smoking.

Take precautionary measures against electrostatic discharg-

es.

Advice on safe handling Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

Sika® Primer-207



Version Revision Date: SDS Number: Date of last issue: -

1.0 05.04.2022 100000005704 Date of first issue: 05.04.2022

products

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.

Store in cool place.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
ethyl acetate	141-78-6	STEL	400 ppm 1,440 mg/m3	AU OEL
		TWA	200 ppm 720 mg/m3	AU OEL
butanone	78-93-3	STEL	300 ppm 890 mg/m3	AU OEL
		TWA	150 ppm 445 mg/m3	AU OEL
tris(p-isocyanatophenyl) thio- phosphate	4151-51-3	TWA	0.02 mg/m3 (NCO)	AU OEL
	Further information: Sensitiser			
		STEL	0.07 mg/m3 (NCO)	AU OEL
4,4'-methylenediphenyl diiso- cyanate	101-68-8	TWA	0.02 mg/m3 (NCO)	AU OEL
	Further information: Category 2 (Carc. 2) Suspected human carcinogen, Sensitiser			
		STEL	0.07 mg/m3 (NCO)	AU OEL

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type	Control parame-	Basis
·		(Form of	ters / Permissible	
		exposure)	concentration	
methanol	67-56-1	TWA	200 ppm	AU OEL
			262 mg/m3	
	Further information: Skin absorption			
		STEL	250 ppm	AU OEL

Sika® Primer-207



Version Revision Date: SDS Number: Date of last issue: -

1.0 05.04.2022 100000005704 Date of first issue: 05.04.2022

328 mg/m3

Biological occupational exposure limits

Components	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
butanone	78-93-3	methyl ethyl	Urine	End of	2 mg/l	ACGIH
		ketone		shift (As		BEI
				soon as		
				possible		
				after ex-		
				posure		
				ceases)		

Appropriate engineering

controls

Use adequate ventilation and/or engineering controls to pre-

vent exposure to vapours.

Avoid vapor formation.

Provide appropriate exhaust ventilation at places where va-

por is formed.

Personal protective equipment

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

organic vapor filter (Type A)

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Follow AS/NZS 1337.1

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Eye protection : Safety glasses

Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working

clothing, long trousers) Follow AS 2210:3

Protective clothing needs to be made of cotton.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : black

Odour : solvent-like

Odour Threshold : No data available

pH : Not applicable substance/mixture is non-soluble (in water)

Sika® Primer-207



Version Date of last issue: -Revision Date: SDS Number:

Date of first issue: 05.04.2022 05.04.2022 10000005704 1.0

Melting point/range / Freezing : No data available

Boiling point/boiling range > 70 °C (158 °F)

-4 °C (25 °F) Flash point

(Method: closed cup)

Evaporation rate No data available

Flammability (solid, gas) No data available

Upper explosion limit / Upper

flammability limit

: 11.5 %(V)

Lower explosion limit / Lower : 1.8 %(V)

flammability limit

Vapour pressure : 99.9915 hPa

Relative vapour density No data available

Density ca. 0.97 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility insoluble

No data available Solubility in other solvents :

Partition coefficient: n-

octanol/water

No data available

: 427 °C Auto-ignition temperature

Decomposition temperature : No data available

Viscosity

: ca. 15 mPa.s (20 °C (68 °F)) Viscosity, dynamic

Viscosity, kinematic < 20.5 mm2/s (40 °C (104 °F))

Explosive properties No data available

Oxidizing properties No data available

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 68.05% w/w

SECTION 10. STABILITY AND REACTIVITY

Reactivity No dangerous reaction known under conditions of normal use.

Chemical stability The product is chemically stable.

Sika® Primer-207



Version Revision Date: SDS Number: Date of last issue: -

1.0 05.04.2022 100000005704 Date of first issue: 05.04.2022

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions. Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Avoid moisture.

Incompatible materials : Strong acids and oxidizing agents

Hazardous decomposition

products

methanol

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

ethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): ca. 1,600 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

butanone:

Acute oral toxicity : LD50 Oral (Rat): 3,300 mg/kg

Acute inhalation toxicity : LC50 (Rat): 36 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

aromatic polyisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

tris(p-isocyanatophenyl) thiophosphate:

Acute oral toxicity : LD50 Oral (Rat): > 675 mg/kg

Remarks: see user defined free text

Acute inhalation toxicity : LC50 (Rat): 5.721 mg/l

Exposure time: 4 h
Test atmosphere: dust/mist

Tris(3-(trimethoxysilyI)propyI)isocyanurate:

Acute oral toxicity : LD50 Oral (Rat): 1,713 mg/kg

4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Sika® Primer-207



Version Revision Date: SDS Number: Date of last issue: -

1.0 05.04.2022 100000005704 Date of first issue: 05.04.2022

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Toxicology data for the components

Information given is based on data on the components and

the toxicology of similar products.

Based on available data, the classification criteria are not met.

Sika® Primer-207



Version Revision Date: SDS Number: Date of last issue: -

1.0 05.04.2022 100000005704 Date of first issue: 05.04.2022

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

: There is no data available for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1866
Proper shipping name : Resin solution

Class : 3 Packing group : II

Labels : Flammable Liquids

Packing instruction (cargo

aircraft)

Packing instruction (passen-

: 353

364

ger aircraft)

IMDG-Code

Sika® Primer-207



Version Revision Date: SDS Number: Date of last issue: -

1.0 05.04.2022 100000005704 Date of first issue: 05.04.2022

UN number : UN 1866

Proper shipping name : RESIN SOLUTION

Class : 3
Packing group : II
Labels : 3

EmS Code : F-E, <u>S-E</u> Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number : UN 1866

Proper shipping name : RESIN SOLUTION

Class : 3
Packing group : II
Labels : 3
Hazchem Code : •3YE

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : Schedule 5

Scheduling of Medicines and

Poisons

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements

Not applicable

There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions.

The components of this product are reported in the following inventories:

AIIC : All components are listed on the inventory, regulatory obliga-

tions/restrictions apply

SECTION 16. OTHER INFORMATION

Revision Date : 05.04.2022 Date format : dd.mm.yyyy

Sika® Primer-207



Date of last issue: -Version Revision Date: SDS Number:

05.04.2022 10000005704 Date of first issue: 05.04.2022 1.0

Full text of other abbreviations

ACGIH BEI ACGIH - Biological Exposure Indices (BEI)

Australia. Workplace Exposure Standards for Airborne Con-AU OEL

taminants.

Exposure standard - time weighted average AU OEL / TWA Exposure standard - short term exposure limit AU OEL / STEL

Australian Dangerous Goods Code. ADG

European Agreement concerning the International Carriage of **ADR**

Dangerous Goods by Road

CAS Chemical Abstracts Service **DNEL** Derived no-effect level

EC50 Half maximal effective concentration GHS Globally Harmonized System

IATA International Air Transport Association

IMDG International Maritime Code for Dangerous Goods

LD50 Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

Occupational Exposure Limit **OEL**

PBT Persistent, bioaccumulative and toxic Predicted no effect concentration **PNEC**

Regulation (EC) No 1907/2006 of the European Parliament **REACH**

> and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

Substances of Very High Concern **SVHC**

vPvB Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN