SikaGard[®]-6220 S



Versior 2.0	n Revision Date: 23.01.2025	SDS Number: 10000001473		Date of last issue: 11.09.2021 Date of first issue: 11.09.2021
SECT	ION 1. PRODUCT AND COM	IPA	NY IDENTIFICATION	
Ρ	roduct name	:	SikaGard [®] -6220 S	
м	lanufacturer or supplier's de	eta	ils	
С	ompany	:	Sika Australia Pty. Ltd. 55 Elizabeth Street Wetherill Park, NSW 2164	
Т	elephone	:	+61 2 9725 11 45	
E	mergency telephone number	:	+61 1800 033 111	
Т	elefax	:	+61 2 9725 33 30	
	ecommended use of the ch roduct use		ical and restrictions on use Surfaces protection	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification		
Aerosols	:	Category 1
Skin corrosion/irritation	:	Category 2
Specific target organ toxicity - single exposure	:	Category 3 (Central nervous system)
Long-term (chronic) aquatic hazard	:	Category 2
GHS label elements Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H315 Causes skin irritation. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

:

SikaGard®-6220 S



Version 2.0	Revision Date: 23.01.2025	SDS Number: 10000001473	Date of last issue: 11.09.2021 Date of first issue: 11.09.2021
		P210 Keep away from heat, hot and other ignition sources. No sr P211 Do not spray on an open fl P251 Do not pierce or burn, even P261 Avoid breathing mist. P264 Wash skin thoroughly after P271 Use only outdoors or in a v P273 Avoid release to the enviro P280 Wear protective gloves.	noking. ame or other ignition source. n after use. handling. well-ventilated area.
		Response: P302 + P352 IF ON SKIN: Wash P304 + P340 + P312 IF INHALE and keep comfortable for breathing doctor if you feel unwell. P332 + P313 If skin irritation occurs tion. P362 + P364 Take off contamination reuse. P391 Collect spillage.	D: Remove person to fresh air ing. Call a POISON CENTER/ urs: Get medical advice/ atten-
		Storage:	
		P403 + P233 Store in a well-ven tightly closed. P405 Store locked up. P410 + P412 Protect from sunlig tures exceeding 50 °C/ 122 °F.	
		Disposal:	
		P501 Dispose of contents/ conta disposal plant.	iner to an approved waste
11			

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
butane	106-97-8	>= 10 -< 30
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	64742-49-0	>= 25 -< 30
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	>= 10 -< 20
isobutane	75-28-5	< 10
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified	64742-95-6	>= 0.25 -< 2.5
Sulfonic acids, petroleum, sodium salts	68608-26-4	< 10

SikaGard[®]-6220 S



Version 2.0	Revision Date: 23.01.2025		SDS Number: 100000001473		Date of last issue: 11.09.2021 Date of first issue: 11.09.2021
ethyle	ene glycol monobutyl eth	ner	111-76-2		< 10
SECTION	4. FIRST AID MEASUR	RES			
Gene	eral advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to		doctor in attendance.
lf inha	aled	:	Move to fresh air.		
In cas	se of skin contact	:	Take off contaminated clothin Wash off with soap and plent If symptoms persist, call a ph	y of v	vater.
In cas	se of eye contact	:	Remove contact lenses. Keep eye wide open while rin If eye irritation persists, consu		
lf swa	allowed	:	Clean mouth with water and o Do not give milk or alcoholic b Never give anything by mouth Obtain medical attention.	bever	ages.
	important symptoms offects, both acute and red	:	irritant effects Dermatitis Loss of balance Vertigo See Section 11 for more deta and symptoms. Causes skin irritation. May cause drowsiness or diz:		
Notes	s to physician	:	Treat symptomatically.		

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Water spray jet Dry powder Foam Carbon dioxide (CO2)
Unsuitable extinguishing media	:	High volume water jet

SikaGard®-6220 S



Vers 2.0	on Revision Date: 23.01.2025		SDS Number: 100000001473	Date of last issue: 11.09.2021 Date of first issue: 11.09.2021
	Specific hazards during fire- fighting	:	Do not allow run-off from fire fighti courses.	ng to enter drains or water
	Hazardous combustion prod- ucts	:	No hazardous combustion produc	ts are known
	Specific extinguishing meth- ods	:	Use water spray to cool unopened Collect contaminated fire extinguis must not be discharged into drains Fire residues and contaminated fin be disposed of in accordance with	shing water separately. This s. re extinguishing water must
	Special protective equipment for firefighters	:	In the event of fire, wear self-conta	ained breathing apparatus.
	Hazchem Code	:	2YE	

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Deny access to unprotected persons.
Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Do not spray on a naked flame or any incandescent material. Take precautionary measures against electrostatic discharg- es.
Advice on safe handling	:	Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge

SikaGard®-6220 S



Version 2.0	Revision Date: 23.01.2025	SDS Number: 100000001473	Date of last issue: 11.09.2021 Date of first issue: 11.09.2021
		(which might cause ignitio Follow standard hygiene n products	n of organic vapours). neasures when handling chemical
Hygie	ne measures	practice. When using do not eat or When using do not smoke	
Condi	itions for safe storage	exposure and temperature	blace. S.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis	
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	AU OEL	
Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane	64742-49-0	TWA	900 mg/m3	AU OEL	
isobutane	75-28-5	STEL	1,000 ppm	ACGIH	
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified	64742-95-6	TWA	900 mg/m3	AU OEL	
ethylene glycol monobutyl ether	111-76-2	TWA	20 ppm 96.9 mg/m3	AU OEL	
	Further information: Skin absorption				
		STEL	50 ppm 242 mg/m3	AU OEL	

Biological occupational exposure limits

Components	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
ethylene glycol mono- butyl ether	111-76-2	Butoxyace- tic acid (BAA)	Urine	End of shift (As soon as possible after ex- posure	200 mg/g creatinine	ACGIH BEI

SikaGard®-6220 S



Vers 2.0	ion Revision Date: 23.01.2025		SDS Number: 100000001473	Date of last issue: 11.09.2021 Date of first issue: 11.09.2021
				ceases)
	Appropriate engineering controls	:	Use adequate ventilation vent exposure to vapours	and/or engineering controls to pre-
	Personal protective equipme	ent		
	Respiratory protection	:	Respirator selection must	tilation wear respiratory protection. be based on known or anticipated rds of the product and the safe ted respirator.
	Hand protection	:	approved standard should	vious gloves complying with an d be worn at all times when handling assessment indicates this is nec-
	Eye protection	:	Safety glasses	
	Skin and body protection	:	Protective clothing (e.g. s clothing, long trousers) Follow AS 2210:3 Protective clothing needs	afety shoes, long-sleeved working to be made of cotton.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	aerosol
Colour	:	various
Odour	:	hydrocarbon-like
Odour Threshold	:	No data available
рН	:	Not applicable substance/mixture is non-polar/aprotic
Melting point/ range / Freez- ing point	:	No data available
Initial boiling point and boiling range	:	-44.5 °C (-48.1 °F)
Flash point	:	ca97 °C (-143 °F)
		6 / 12

SikaGard[®]-6220 S



Versio 2.0	n Revision Date: 23.01.2025		SDS Number: 100000001473	Date of last issue: 11.09.2021 Date of first issue: 11.09.2021
			(Method: closed cup)	
E	Evaporation rate	:	No data available	
F	Flammability (solid, gas)	:	No data available	
	Jpper explosion limit / Upper lammability limit	:	Upper flammability limit 10.9 %(V)	
	Lower explosion limit / Lower lammability limit	:	Lower flammability limit 0.6 %(V)	
١	/apour pressure	:	4,100 hPa (20 °C (68 °F))	
F	Relative vapour density	:	No data available	
[Density	:	ca. 0.66 g/cm3 (20 °C (68 °F))	
S	Solubility(ies) Water solubility	:	insoluble	
	Solubility in other solvents	:	No data available	
	Partition coefficient: n- octanol/water	:	No data available	
ŀ	Auto-ignition temperature	:	> 200 °C (> 392 °F)	
[Decomposition temperature	:	No data available	
١	Viscosity Viscosity, dynamic	:	No data available	
	Viscosity, kinematic	:	< 20.5 mm2/s (40 °C (104 °F))	
E	Explosive properties	:	No data available	
(Oxidizing properties	:	No data available	
	Volatile organic compounds	:	Directive 2010/75/EU of 24 Nove emissions (integrated pollution pr Volatile organic compounds (VOC	evention and control)

SECTION 10. STABILITY AND REACTIVITY

 Reactivity
 : No dangerous reaction known under conditions of normal use.

 Chemical stability
 : The product is chemically stable.

SikaGard®-6220 S



Version 2.0	Revision Date: 23.01.2025		SDS Number: 10000001473	Date of last issue: 11.09.2021 Date of first issue: 11.09.2021
Possil tions	bility of hazardous reac-	:	Stable under recommended	storage conditions.
Condi	itions to avoid	:	Heat, flames and sparks.	
Incom	patible materials	:	see section 7.	
Hazar produ	dous decomposition cts	:	No hazardous decompositio	n products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

Hydrocarbons, C9-C11, n-all	kan	es, isoalkanes, cyclics, <2% aromatics:
Acute oral toxicity	:	LD50 Oral (Rat): > 5,000 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): 3,160 mg/kg

ethylene glycol monobutyl ether:

Acute oral toxicity : LD50 Oral: 1,200 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Chronic toxicity

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

SikaGard®-6220 S



/ersion 2.0	Revision Date: 23.01.2025	SDS Number: 100000001473	Date of last issue: 11.09.2021 Date of first issue: 11.09.2021
Repro	oductive toxicity		
Not cla	assified due to lack of da	ata.	
STOT	- single exposure		
May c	ause drowsiness or dizz	iness.	
	- repeated exposure	-1-	
	assified due to lack of da	ata.	
-	ation toxicity		
INOT CI	assified due to lack of da	ata.	
SECTION	12. ECOLOGICAL INFO	ORMATION	
Ecoto	oxicity		
Comp	oonents:		
	ocarbons, C6-C7, n-alka ty to fish	anes, isoalkanes, cyclics, < : LL50 (Oncorhynchus my Exposure time: 96 h	5% n-hexane: /kiss (rainbow trout)): 12.51 mg/l
Toxici		kanes, isoalkanes, cyclics, : EC50 (Daphnia magna (Exposure time: 48 h	
	stence and degradabili	ty	
No da	ta available		
	cumulative potential ta available		
Mobil	ity in soil		
No da	ta available		
Other	adverse effects		
Produ	ict:		
	onal ecological infor-	: An environmental hazard unprofessional handling Toxic to aquatic life with	
Globa	I warming potential		
		ntergovernmental Panel on tion on Climate Change (UN	Climate Change (IPCC) of the United NFCCC)
Comp	oonents:		
butan 20-yea 100-ye 500-ye	e: ar global warming potent ear global warming poten ear global warming poten	ntial: 0.006 ntial: 0.002	
	spheric lifetime: 0.019 yr tive efficiency: 0 Wm2pp		

SikaGard®-6220 S



Version	Revision Date:	SDS Number:	Date of last issue: 11.09.2021
2.0	23.01.2025	10000001473	Date of first issue: 11.09.2021

Further information: Miscellaneous compounds

propane:

20-year global warming potential: 0.072 100-year global warming potential: 0.02 500-year global warming potential: 0.006 Atmospheric lifetime: 0.036 yr Radiative efficiency: 0 Wm2ppb Further information: Miscellaneous compounds

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods Waste from residues	:	Send to a licensed waste management company.
		The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemi- cal or used container.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product.
		Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR UN/ID No. Proper shipping name Class Packing group Labels Packing instruction (cargo aircraft) Packing instruction (passen- ger aircraft)	 UN 1950 Aerosols, flammable 2.1 Not assigned by regulation Flammable Gas 203
IMDG-Code UN number Proper shipping name Class Packing group	UN 1950 AEROSOLS 2.1 Not assigned by regulation
	10 / 12

SikaGard®-6220 S



Version 2.0	Revision Date: 23.01.2025		SDS Number: 100000001473	Date of last issue: 11.09.2021 Date of first issue: 11.09.2021
Labels EmS Co Marine	ode pollutant		2.1 F-D, S-U no	
•	ort in bulk according	-	Innex II of MARPOL 73/78 a lied.	nd the IBC Code
Nationa	al Regulations			
Class Packing Labels Hazche	shipping name	:	Not assigned by regulation	

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Therapeutic Goods (Poisons : Standard) Instrument	publication to check	for s	ber allocated (Please use the original specific uses, specific conditions or nt apply for this chemical)
International Chemical Weapons Schedules of Toxic Chemicals an	· · · · · · · · · · · · · · · · · · ·	:	Not applicable
Prohibition/Licensing Requirement		:	There is no applicable prohibition, authorisation and restricted use requirements, including for carcino- gens referred to in Schedule 10 of the model WHS Act and Regula- tions.

The components of this product are reported in the following inventories:

AICS

: On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date	: 23.01.2025
Date format	: dd.mm.yyyy

Full text of other abbreviations

SikaGard®-6220 S



Version 2.0	Revision Date: 23.01.2025		SDS Number: 100000001473	Date of last issue: 11.09.2021 Date of first issue: 11.09.2021
ACGIH ACGIH AU OEL		:	USA. ACGIH Threshold Limit Values (TLV) ACGIH - Biological Exposure Indices (BEI) Australia. Workplace Exposure Standards for Airborne Con- taminants.	
ACGIH / AU OEL AU OEL ADG ADR	/ TWA	:	Short-term exposure limit Exposure standard - time weighted average Exposure standard - short term exposure limit Australian Dangerous Goods Code. European Agreement concerning the International Carriage of	
CAS DNEL EC50 GHS		:	Dangerous Goods by Road Chemical Abstracts Service Derived no-effect level Half maximal effective concentrat Globally Harmonized System	
IATA IMDG LD50		:	International Air Transport Association International Maritime Code for Dangerous Goods Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)	
LC50		:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)	
MARPO	DL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978	
OEL PBT PNEC REACH		:	Occupational Exposure Limit Persistent, bioaccumulative and to Predicted no effect concentration Regulation (EC) No 1907/2006 of	the European Parliament
SVHC vPvB		:	and of the Council of 18 December istration, Evaluation, Authorisation cals (REACH), establishing a Eur Substances of Very High Concern Very persistent and very bioaccur	n and Restriction of Chemi- opean Chemicals Agency n

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

AU / EN