

SAFETY DATA SHEET

Sikagard®-680 S Betoncolor colorless



Version
1.0

Revision Date:
10.10.2024

SDS Number:
000000003787

Date of last issue: -
Date of first issue: 10.10.2024

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikagard®-680 S Betoncolor colorless

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.
55 Elizabeth Street
Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45

Emergency telephone number : +61 1800 033 111

Telefax : +61 2 9725 33 30

Recommended use of the chemical and restrictions on use

Product use : Surfaces protection

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Serious eye damage/eye irritation : Category 1

Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

Specific target organ toxicity - repeated exposure : Category 1

Long-term (chronic) aquatic hazard : Category 2

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

SAFETY DATA SHEET

Sikagard®-680 S Betoncolor colorless



Version
1.0

Revision Date:
10.10.2024

SDS Number:
000000003787

Date of last issue: -
Date of first issue: 10.10.2024

H336 May cause drowsiness or dizziness.
H372 Causes damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

:

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P314 Get medical advice/ attention if you feel unwell.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

SAFETY DATA SHEET

Sikagard®-680 S Betoncolor colorless



Version
1.0

Revision Date:
10.10.2024

SDS Number:
000000003787

Date of last issue: -
Date of first issue: 10.10.2024

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Hydrocarbons, C9, aromatics	64742-95-6	≥ 30 -< 60
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	64742-82-1	≥ 10 -< 20
2-methoxy-1-methylethyl acetate	108-65-6	< 10
2-methylpropan-1-ol	78-83-1	≥ 3 -< 10
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	< 10

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : irritant effects
Cough
Respiratory disorder
Excessive lachrymation
Loss of balance
Vertigo
See Section 11 for more detailed information on health effects and symptoms.
Causes serious eye damage.
May cause respiratory irritation.

SAFETY DATA SHEET

Sikagard®-680 S Betoncolor colorless



Version
1.0

Revision Date:
10.10.2024

SDS Number:
000000003787

Date of last issue: -
Date of first issue: 10.10.2024

May cause drowsiness or dizziness.
Causes damage to organs through prolonged or repeated exposure.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : Water
High volume water jet
- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Use water spray to cool unopened containers.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Hazchem Code : •3Y

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.
- Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

SAFETY DATA SHEET

Sikagard®-680 S Betoncolor colorless



Version
1.0

Revision Date:
10.10.2024

SDS Number:
000000003787

Date of last issue: -
Date of first issue: 10.10.2024

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Use explosion-proof equipment.
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Take precautionary measures against electrostatic discharges.

Advice on safe handling : Do not breathe vapours or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Follow standard hygiene measures when handling chemical products

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.
Keep in a well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrocarbons, C9, aromatics	64742-95-6	TWA	900 mg/m3	AU OEL

SAFETY DATA SHEET

Sikagard®-680 S Betoncolor colorless



Version
1.0

Revision Date:
10.10.2024

SDS Number:
000000003787

Date of last issue: -
Date of first issue: 10.10.2024

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	64742-82-1	TWA	900 mg/m3	AU OEL
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 274 mg/m3	AU OEL
	Further information: Skin absorption			
		STEL	100 ppm 548 mg/m3	AU OEL
2-methylpropan-1-ol	78-83-1	TWA	50 ppm 152 mg/m3	AU OEL

Appropriate engineering controls : Use adequate ventilation and/or engineering controls to prevent exposure to vapours.
Avoid vapor formation.
Provide appropriate exhaust ventilation at places where vapor is formed.

Personal protective equipment

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor filter (Type A)

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Follow AS/NZS 1337.1
Recommended: Butyl rubber/nitrile rubber gloves.
Contaminated gloves should be removed.

Eye protection : Safety glasses

Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working clothing, long trousers)
Follow AS 2210:3
Protective clothing needs to be made of cotton.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : clear

SAFETY DATA SHEET

Sikagard®-680 S Betoncolor colorless



Version
1.0

Revision Date:
10.10.2024

SDS Number:
000000003787

Date of last issue: -
Date of first issue: 10.10.2024

Odour	: solvent-like, aromatic
Odour Threshold	: No data available
pH	: Not applicable substance/mixture is non-polar/aprotic
Melting point/ range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: ca. 25 °C (77 °F) (Method: closed cup)
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: 6.5 %(V)
Lower explosion limit / Lower flammability limit	: 0.6 %(V)
Vapour pressure	: 4.9996 hPa
Relative vapour density	: No data available
Density	: ca. 0.9 g/cm ³ (20 °C (68 °F))
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: 235 °C
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 20.5 mm ² /s (40 °C (104 °F))
Explosive properties	: No data available

SAFETY DATA SHEET

Sikagard®-680 S Betoncolor colorless



Version
1.0

Revision Date:
10.10.2024

SDS Number:
000000003787

Date of last issue: -
Date of first issue: 10.10.2024

Oxidizing properties : No data available

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 74.3% w/w

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reactions : Stable under recommended storage conditions.
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : see section 7.

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

Hydrocarbons, C9, aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 3,160 mg/kg

SAFETY DATA SHEET

Sikagard®-680 S Betoncolor colorless



Version
1.0

Revision Date:
10.10.2024

SDS Number:
000000003787

Date of last issue: -
Date of first issue: 10.10.2024

Skin corrosion/irritation

Not classified due to lack of data.

Components:

Hydrocarbons, C9, aromatics:

Assessment : Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Chronic toxicity

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified due to lack of data.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Hydrocarbons, C9, aromatics:

Toxicity to algae/aquatic plants : (Pseudokirchneriella subcapitata (green algae)): 2.6 - 2.9 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

Sikagard®-680 S Betoncolor colorless



Version
1.0

Revision Date:
10.10.2024

SDS Number:
000000003787

Date of last issue: -
Date of first issue: 10.10.2024

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Send to a licensed waste management company.

The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.

Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1263
Proper shipping name : Paint
Class : 3
Packing group : III

SAFETY DATA SHEET

Sikagard®-680 S Betoncolor colorless



Version
1.0

Revision Date:
10.10.2024

SDS Number:
000000003787

Date of last issue: -
Date of first issue: 10.10.2024

Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355
Environmentally hazardous : yes

IMDG-Code

UN number : UN 1263
Proper shipping name : PAINT

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : III
Labels : 3
Hazchem Code : •3Y
Environmentally hazardous : yes

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Therapeutic Goods (Poisons Standard) Instrument : Schedule 5 (Please use the original publication to check for specific uses, specific conditions or threshold limits that might apply for this chemical)

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors
Prohibition/Licensing Requirements : There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.

SAFETY DATA SHEET

Sikagard®-680 S Betoncolor colorless



Version
1.0

Revision Date:
10.10.2024

SDS Number:
000000003787

Date of last issue: -
Date of first issue: 10.10.2024

The components of this product are reported in the following inventories:

AIIC : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date : 10.10.2024

Date format : dd.mm.yyyy

Full text of other abbreviations

AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.

AU OEL / TWA : Exposure standard - time weighted average

AU OEL / STEL : Exposure standard - short term exposure limit

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road

CAS : Chemical Abstracts Service

DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)

LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)

MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic

PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

SAFETY DATA SHEET

Sikagard®-680 S Betoncolor colorless



Version
1.0

Revision Date:
10.10.2024

SDS Number:
000000003787

Date of last issue: -
Date of first issue: 10.10.2024

|| Changes as compared to previous version !

AU / EN