Sika Plastiment® 45



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 29.05.2022

 4.0
 08.10.2022
 100000015022
 Date of first issue: 06.12.2016

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sika Plastiment® 45

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45

Emergency telephone number : +61 1800 033 111

Telefax : +61 2 9725 33 30

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Serious eye damage/eye irri-

tation

Category 1

Short-term (acute) aquatic

hazard

Category 3

Long-term (chronic) aquatic

hazard

Category 3

GHS label elements

Hazard pictograms

T.S.

Signal word : Danger

Hazard statements : H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P273 Avoid release to the environment. P280 Wear eye protection/ face protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/ doctor.

Sika Plastiment® 45



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 29.05.2022

 4.0
 08.10.2022
 100000015022
 Date of first issue: 06.12.2016

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
1,1',1'-nitrilotripropan-2-ol	122-20-3	>= 3 -< 10
2-octyl-2H-isothiazole-3-one (OIT)	26530-20-1	>= 0.0025 -< 0.025

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

No known significant effects or hazards.

Excessive lachrymation

See Section 11 for more detailed information on health effects

and symptoms.

Causes serious eye damage.

Notes to physician : Treat symptomatically.

Sika Plastiment® 45



Date of last issue: 29.05.2022 Version Revision Date: SDS Number: 100000015022 Date of first issue: 06.12.2016 08.10.2022 4.0

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Hazardous combustion prod-

No hazardous combustion products are known

Specific extinguishing meth-

Standard procedure for chemical fires.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Deny access to unprotected persons.

Environmental precautions Try to prevent the material from entering drains or water

courses.

No special environmental precautions required.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Handle in accordance with good industrial hygiene and safety Hygiene measures

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

Sika Plastiment® 45



Version Revision Date: 4.0 08.10.2022

SDS Number: 100000015022

Date of last issue: 29.05.2022 Date of first issue: 06.12.2016

kept upright to prevent leakage.

Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Appropriate engineering

controls

Use adequate ventilation and/or engineering controls to pre-

vent exposure to vapours.

Personal protective equipment

Respiratory protection : No special measures required.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary

Follow AS/NZS 1337.1

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Eye protection : Safety glasses

Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working

clothing, long trousers) Follow AS 2210:3

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : light brown

Odour : characteristic

Odour Threshold : No data available

pH : ca. 8

Melting point/range / Freezing :

No data available

point

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Sika Plastiment® 45



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 29.05.2022

 4.0
 08.10.2022
 100000015022
 Date of first issue: 06.12.2016

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : 23 hPa

Relative vapour density : No data available

Density : ca. 1.06 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : soluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0.2% w/w

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

No hazards to be specially mentioned.

Conditions to avoid : No data available

Incompatible materials : see section 7.

No decomposition if stored and applied as directed.

Sika Plastiment® 45



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 29.05.2022

 4.0
 08.10.2022
 100000015022
 Date of first issue: 06.12.2016

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

1,1',1'-nitrilotripropan-2-ol:

Acute oral toxicity : LD50 Oral (Rat): ca. 4,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

1,1',1'-nitrilotripropan-2-ol:

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): > 500 mg/l

Sika Plastiment® 45



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 29.05.2022

 4.0
 08.10.2022
 100000015022
 Date of first issue: 06.12.2016

aquatic invertebrates Exposure time: 48 h

2-octyl-2H-isothiazole-3-one (OIT):M-Factor (Acute aquatic tox- : 100

icity)

M-Factor (Chronic aquatic : 100

toxicity)

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

There is no data available for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo : Not applicable

aircraft)

Packing instruction (passen-

ger aircraft)

Not applicable

3 --- --- ,

IMDG-Code

UN number : Not applicable Proper shipping name : Not applicable

Sika Plastiment® 45



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 29.05.2022

 4.0
 08.10.2022
 100000015022
 Date of first issue: 06.12.2016

Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
EmS Code : Not applicable
Marine pollutant : Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Hazchem Code : Not applicable

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : No poison schedule number allocated

Scheduling of Medicines and

Poisons

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements

Not applicable

 There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions.

The components of this product are reported in the following inventories:

AICS : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date : 08.10.2022 Date format : dd.mm.yyyy

Full text of other abbreviations

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

Sika Plastiment® 45



Version	Revision Date:		SDS Number:	Date of last issue: 29.05.2022	
4.0	08.10.2022		100000015022	Date of first issue: 06.12.2016	
CAS		:	Chemical Abstracts Service		
DNEL		:	Derived no-effect level		
EC50		:	Half maximal effective concentration	on	
GHS		:	Globally Harmonized System		
IATA		:	International Air Transport Association		
IMDG		:	International Maritime Code for Dangerous Goods		
LD50		:	Median lethal dosis (the amount of a material, given all at		
			once, which causes the death of 5	0% (one half) of a group of	
			test animals)	, , , , , , , , , , , , , , , , , , , ,	
LC50		:	Median lethal concentration (conce	entrations of the chemical in	
			air that kills 50% of the test animal	s during the observation	
			period)		
MARPO	L	:	International Convention for the Pr	evention of Pollution from	
			Ships, 1973 as modified by the Pro	otocol of 1978	
OEL		:	Occupational Exposure Limit		
PBT		:	Persistent, bioaccumulative and to	xic	
PNEC		:	Predicted no effect concentration		
REACH		:	Regulation (EC) No 1907/2006 of	the European Parliament	
_			and of the Council of 18 Decembe		
			istration, Evaluation, Authorisation		
			cals (REACH), establishing a Euro		
SVHC			Substances of Very High Concern		
vPvB		:	Very persistent and very bioaccum		
VI VD		•	very perelectoric and very bloaddan	ididii v o	

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN