Sikaflex®-400 Fire



Version Revision Date: Date of last issue: 31.03.2017 SDS Number: 100000010494 Date of first issue: 31.03.2017 20.11.2021 2.0

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikaflex®-400 Fire

Product code : 100000010494

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street

Wetherill Park. NSW 2164

Telephone : +61 2 9725 11 45 Telefax : +61 2 9725 33 30 : +61 1800 033 111 Emergency telephone num-

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Specific target organ toxicity - : Category 2

repeated exposure (Oral)

GHS label elements

Hazard pictograms

Signal word

H373 May cause damage to organs through prolonged or re-Hazard statements

peated exposure if swallowed.

Precautionary statements Prevention:

P260 Do not breathe mist or vapours.

Response:

P314 Get medical advice/ attention if you feel unwell.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Sikaflex®-400 Fire



Date of last issue: 31.03.2017 Version Revision Date: SDS Number: 100000010494 Date of first issue: 31.03.2017 20.11.2021 2.0

Chemical name	CAS-No.	Concentration (% w/w)
1,3,5-triazine-2,4,6(1H,3H,5H)-trione, com-	37640-57-6	>= 10 -< 30
pound with 1,3,5-triazine-2,4,6-triamine (1:1)		
tris(2-chloro-1-methylethyl) phosphate	13674-84-5	>= 10 -< 30
naphtha (petroleum), hydrotreated heavy	64742-48-9	0 -< 10
4,4'-methylenediphenyl diisocyanate	101-68-8	0 -< 1

SECTION 4. FIRST AID MEASURES

General advice Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

Remove contact lenses. In case of eye contact

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

No known significant effects or hazards.

See Section 11 for more detailed information on health effects

and symptoms.

May cause damage to organs through prolonged or repeated

exposure if swallowed.

Notes to physician Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Hazardous combustion prod- :

No hazardous combustion products are known

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Sikaflex®-400 Fire



Date of last issue: 31.03.2017 Version Revision Date: SDS Number: 100000010494 Date of first issue: 31.03.2017 2.0 20.11.2021

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment. Deny access to unprotected persons.

Environmental precautions Try to prevent the material from entering drains or water

courses.

If the product contaminates rivers and lakes or drains inform

respective authorities.

No special environmental precautions required.

Methods and materials for containment and cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Handle in accordance with good industrial hygiene and safety Hygiene measures

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage Keep container tightly closed in a dry and well-ventilated

place.

Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis	
naphtha (petroleum), hy- drotreated heavy	64742-48-9	TWA	900 mg/m3	AU OEL	
4,4'-methylenediphenyl diiso- cyanate	101-68-8	TWA	0.02 mg/m3 (NCO)	AU OEL	
	Further information: Category 2 (Carc. 2) Suspected human car-				

Sikaflex®-400 Fire



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 31.03.2017

 2.0
 20.11.2021
 100000010494
 Date of first issue: 31.03.2017

Appropriate engineering

controls

Use adequate ventilation and/or engineering controls to pre-

vent exposure to vapours.

Personal protective equipment

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Follow AS/NZS 1337.1

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Eye protection : Safety glasses

Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working

clothing, long trousers)

Follow AS 2210:3

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : grey

Odour : characteristic

Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

Flash point : ca. 101 °C (214 °F)

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Sikaflex®-400 Fire



Version Date of last issue: 31.03.2017 Revision Date: SDS Number: 100000010494 Date of first issue: 31.03.2017 20.11.2021 2.0

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : 0.01 hPa

Relative vapour density No data available

Density ca. 1.4 g/cm3 (23 °C (73 °F))

Solubility(ies)

Water solubility insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

No data available Auto-ignition temperature

Decomposition temperature : No data available

Viscosity

: No data available Viscosity, dynamic

Viscosity, kinematic > 20.5 mm2/s (40 °C (104 °F))

Explosive properties No data available

Oxidizing properties No data available

: Directive 2010/75/EU of 24 November 2010 on industrial Volatile organic compounds

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 1.82% w/w

SECTION 10. STABILITY AND REACTIVITY

: No dangerous reaction known under conditions of normal use. Reactivity

Chemical stability The product is chemically stable.

tions

Possibility of hazardous reac- : No hazards to be specially mentioned.

Conditions to avoid : No data available

Incompatible materials : see section 7.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Sikaflex®-400 Fire



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 31.03.2017

 2.0
 20.11.2021
 100000010494
 Date of first issue: 31.03.2017

Components:

4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if swallowed.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Sikaflex®-400 Fire



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 31.03.2017

 2.0
 20.11.2021
 100000010494
 Date of first issue: 31.03.2017

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

: There is no data available for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform

Scheduling of Medicines and

Poisons

: No poison schedule number allocated

Sikaflex®-400 Fire



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 31.03.2017

 2.0
 20.11.2021
 100000010494
 Date of first issue: 31.03.2017

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements

Not applicable

There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions

The components of this product are reported in the following inventories:

AIIC : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date : 20.11.2021 Date format : dd.mm.yyyy

Full text of other abbreviations

AU OEL : Australia. Workplace Exposure Standards for Airborne Con-

taminants.

AU OEL / TWA : Exposure standard - time weighted average AU OEL / STEL : Exposure standard - short term exposure limit

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Sikaflex®-400 Fire



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 31.03.2017

 2.0
 20.11.2021
 100000010494
 Date of first issue: 31.03.2017

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN