Sikafloor 376 Part A



Version 3.0	Revision Date: 11.08.2023	SDS Number: 000000121096	Date of last issue: 15.11.2019 Date of first issue: 16.08.2016
SECTION	1. PRODUCT AND COM	IPANY IDENTIFICATION	
Produ	ct name	Sikafloor 376 Part A	

Manufacturer	or	supp	lier's	detai	ls

:	Sika Australia Pty. Ltd. 55 Elizabeth Street Wetherill Park, NSW 2164
:	+61 2 9725 11 45
:	+61 1800 033 111
:	+61 2 9725 33 30
	:

Recommended use of the chemical and restrictions on use

Product use	: Polyurethane coating
	, , , , , , , , , , , , , , , , , , , ,

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification Flammable liquids	:	Category 4
Skin sensitisation	:	Category 1
Short-term (acute) aquatic hazard	:	Category 2
Long-term (chronic) aquatic hazard	:	Category 2
GHS label elements		
Hazard pictograms	:	!
Signal word	:	Warning
Hazard statements	:	H227 Combustible liquid. H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing mist or vapours. P272 Contaminated work clothing should not be allowed out of
		1/11

Sikafloor 376 Part A



Version 3.0	Revision Date: 11.08.2023	SDS Number: 000000121096	Date of last issue: 15.11.2019 Date of first issue: 16.08.2016
		the workplace. P273 Avoid release to the e P280 Wear protective glove tion/ face protection/ hearin	es/ protective clothing/ eye protec-
		Response:	
		vice/ attention. P362 + P364 Take off conta reuse.	n or rash occurs: Get medical ad- aminated clothing and wash it before :: Use dry sand, dry chemical or
		Storage: P403 Store in a well-ventila	ited place.
		Disposal: P501 Dispose of contents/ disposal plant.	container to an approved waste

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
6-methyl-2,4-bis(methylthio)phenylene-1,3-	106264-79-3	>= 10 -< 25
diamine		
Hydrocarbons, C9, aromatics	64742-95-6	>= 2.5 -< 10
N-methyl-2-pyrrolidone	872-50-4	0 -< 0.3

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	: Remove contact lenses. Keep eye wide open while rinsing.
	0/11

Sikafloor 376 Part A



Version 3.0	Revision Date: 11.08.2023		SDS Number: 000000121096	Date of last issue: 15.11.2019 Date of first issue: 16.08.2016
			If eye irritation persists, consult a	specialist.
lf swa	illowed	:	Clean mouth with water and drink Do not give milk or alcoholic beve Never give anything by mouth to Obtain medical attention.	erages.
Most important symptoms and effects, both acute and delayed		:	sensitising effects Allergic reactions See Section 11 for more detailed and symptoms. May cause an allergic skin reaction	
Notes	to physician	:	Treat symptomatically.	

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Carbon dioxide (CO2)
Unsuitable extinguishing media	:	Water
Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
Specific extinguishing meth- ods	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Hazchem Code	:	•3Z

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Deny access to unprotected persons.
Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

Sikafloor 376 Part A



Version	Revision Date:	SDS Number:	Date of last issue: 15.11.2019
3.0	11.08.2023	000000121096	Date of first issue: 16.08.2016

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
Conditions for safe storage	:	Store in original container. Keep in a well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Hydrocarbons, C9, aromatics	64742-95-6	TWA	900 mg/m3	AU OEL
N-methyl-2-pyrrolidone	872-50-4	STEL	75 ppm 309 mg/m3	AU OEL
	Further information	ation: Skin abso	rption	
		TWA	25 ppm 103 mg/m3	AU OEL

Biological occupational exposure limits

Components	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
N-methyl-2-pyrrolidone	872-50-4	5-Hydroxy-	Urine	End of	100 mg/l	ACGIH
		N-methyl-2-		shift (As	-	BEI

Sikafloor 376 Part A



Version 3.0	Revision Date: 11.08.2023		SDS Number: 000000121096	Date of last issue: 15.11.2019 Date of first issue: 16.08.2016
			pyrrolidone	soon as possible after ex- posure ceases)
Appro contro	priate engineering bls	:	Use adequate ventilation vent exposure to vapou	on and/or engineering controls to pre- irs.
Perso	nal protective equipm	ent		
Respir	atory protection	:	Respirator selection mu	rentilation wear respiratory protection. ust be based on known or anticipated zards of the product and the safe lected respirator.
Hand _I	protection	:	approved standard sho chemical products if a r essary. Follow AS/NZS 1337.1	pervious gloves complying with an uld be worn at all times when handling risk assessment indicates this is nec- ubber/nitrile rubber gloves. hould be removed.
Eye pr	otection	:	Safety glasses	
Skin a	nd body protection	:	clothing, long trousers) Follow AS 2210:3	. safety shoes, long-sleeved working ds to be made of cotton.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	viscous
Colour	:	various
Odour	:	amine-like
Odour Threshold	:	No data available
рН	:	ca. 7
Melting point/range / Freezing	:	No data available
point Boiling point/boiling range	:	No data available
Flash point	:	ca. 71 °C (160 °F) (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available

Sikafloor 376 Part A



Version 3.0	Revision Date: 11.08.2023		SDS Number: 000000121096	Date of last issue: 15.11.2019 Date of first issue: 16.08.2016
	r explosion limit / Upper nability limit	:	No data available	
	r explosion limit / Lower nability limit	:	No data available	
Vapou	ur pressure	:	0.01 hPa	
Relati	ve vapour density	:	No data available	
Densi	ty	:	ca. 1.76 g/cm3 (20 °C (68 °F))	
	ility(ies) ater solubility	:	insoluble	
So	lubility in other solvents	:	No data available	
	on coefficient: n- ol/water	:	No data available	
	ignition temperature	:	ca. 450 °C (842 °F)	
Decor	mposition temperature	:	No data available	
Visco: Vis	sity scosity, dynamic	:	ca. 4,200 mPa.s (20 °C (68 °F))	
Vis	scosity, kinematic	:	> 20.5 mm2/s (40 °C (104 °F))	
Explo	sive properties	:	No data available	
Oxidiz	zing properties	:	No data available	
Volati	le organic compounds	:	Directive 2010/75/EU of 24 Nove emissions (integrated pollution pr Volatile organic compounds (VO	revention and control)

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reac- tions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	see section 7.

Sikafloor 376 Part A



/ersion 3.0	Revision Date: 11.08.2023	SDS Number: 000000121096	Date of last issue: 15.11.2019 Date of first issue: 16.08.2016
SECTION '	11. TOXICOLOGICAL	INFORMATION	
	toxicity assified based on ava	lable information.	
Comp	onents:		
	hyl-2,4-bis(methylthi oral toxicity	o)phenylene-1,3-diamine: : LD50 Oral (Rat): 1,515	mg/kg
	ocarbons, C9, aromat oral toxicity	t ics: : LD50 Oral (Rat): > 2,00	0 mg/kg
Acute	dermal toxicity	: LD50 Dermal (Rabbit):	> 2,000 mg/kg
	hyl-2-pyrrolidone: oral toxicity	: LD50 Oral (Rat): 4,150	mg/kg
Acute	inhalation toxicity	: LC50 (Rat): 5.1 mg/l Exposure time: 4 h Test atmosphere: dust/l	mist
Acute	dermal toxicity	: LD50 Dermal (Rabbit):	> 5,000 mg/kg
	corrosion/irritation assified based on ava	lable information.	
	onents: carbons, C9, aromat sment		y cause skin dryness or cracking.
	u s eye damage/eye i assified based on ava		
Respi	ratory or skin sensit	isation	
	sensitisation ause an allergic skin r	eaction.	
-	ratory sensitisation assified based on avai	lable information.	
Chron	ic toxicity		
	cell mutagenicity assified based on avai	lable information.	
	nogenicity assified based on ava	lable information.	
	ductive toxicity assified based on avai	lable information.	
		7/11	

Sikafloor 376 Part A



Versio 3.0	on Revision Date: 11.08.2023	SDS Number: 000000121096	Date of last issue: 15.11.2019 Date of first issue: 16.08.2016
	STOT - single exposure Not classified based on available	information.	
	STOT - repeated exposure Not classified based on available	information.	
	Aspiration toxicity Not classified based on available	information.	
SECT	FION 12. ECOLOGICAL INFORM	MATION	
E	Ecotoxicity		
ŀ	Components: Hydrocarbons, C9, aromatics: Toxicity to algae/aquatic : plants	(Pseudokirchneriella subcapit mg/l Exposure time: 72 h	ata (green algae)): 2.6 - 2.9
	Persistence and degradability No data available		
	Bioaccumulative potential No data available		
	Mobility in soil No data available		
(Other adverse effects		
/	Product: Additional ecological infor- : mation	An environmental hazard cann unprofessional handling or dis Toxic to aquatic life with long la	posal.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods		
Waste from residues	:	The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemi- cal or used container. Send to a licensed waste management company.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

Sikafloor 376 Part A



VersionRevision Date:SDS Number:Date of last issue: 15.11.20193.011.08.2023000000121096Date of first issue: 16.08.2016

SECTION 14. TRANSPORT INFORMATION

International Regulations

UN/ID No.	:	UN 3082
Proper shipping name	:	Environmentally hazardous substance, liquid, n.o.s. (6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine)
Class	:	9
Packing group	•	
Labels	-	Miscellaneous
	:	964
Packing instruction (cargo aircraft)	•	904
Packing instruction (passen-	:	964
ger aircraft)		
Remarks	:	Transport in accordance with special regulation A 197
IMDG-Code		
UN number	:	UN 3082
Proper shipping name	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
		(6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine)
Class		9
• • • • • •	•	-
Packing group	•	
Labels	:	9
EmS Code	:	F-A, S-F
Marine pollutant	:	ves
Remarks	:	Transport in accordance with 2.10.2.7 of the IMDG-Code
	•	

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG	 UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
UN number	N.O.S.
Proper shipping name	(6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine)
Class	: 9
Packing group	: III
Labels	: 9
Hazchem Code	: •3Z

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Sikafloor 376 Part A



ersion)	Revision Date: 11.08.2023	SDS Number: Date of last issue: 15.11.2019 000000121096 Date of first issue: 16.08.2016			
	ard for the Uniform luling of Medicines and าร	: No poison schedule number allocated			
Sched	ational Chemical Weap lules of Toxic Chemica ition/Licensing Require				
	omponents of this pre	oduct are reported in the following inventories:			
AIIC : On the inventory, or in compliance with the inventory					
SECTION 16. OTHER INFORMATION					
	on Date	: 11.08.2023			
Date fo	ormat	: dd.mm.yyyy			
Full te	ext of other abbreviati	ons			
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)					
AU OE		Australia. Workplace Exposure Standards for Airborne Con-			
710 01		taminants.			
AU OF	EL / TWA	Exposure standard - time weighted average			
	EL / STEL	Exposure standard - short term exposure limit			
ADG		Australian Dangerous Goods Code.			
ADR		European Agreement concerning the International Carriage of			
ADIX		Dangerous Goods by Road			
CAS		Chemical Abstracts Service			
DNEL		Derived no-effect level			
EC50		Half maximal effective concentration			
GHS					
IATA		Globally Harmonized System			
IMDG		International Air Transport Association International Maritime Code for Dangerous Goods			
LD50		Median lethal dosis (the amount of a material, given all at			
LDSU		once, which causes the death of 50% (one half) of a group of			
		test animals)			
LC50		: Median lethal concentration (concentrations of the chemical in			
L030		air that kills 50% of the test animals during the observation			
		period) International Convention for the Prevention of Pollution from			
MARP	OL				
		Ships, 1973 as modified by the Protocol of 1978			
OEL		Occupational Exposure Limit			
PBT PNEC		Persistent, bioaccumulative and toxic			
		Predicted no effect concentration			
	REACH : Regulation (EC) No 1907/2006 of the European Parliamen				
	Н				
	Н	and of the Council of 18 December 2006 concerning the Reg-			
	Н				

Sikafloor 376 Part A



Version	Revision Date: 11.08.2023	SDS Number:	Date of last issue: 15.11.2019	
3.0		000000121096	Date of first issue: 16.08.2016	
			Substances of Very High Concern Very persistent and very bioaccumulative	

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

AU / EN