Sikaflex®-521 UV



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.09.2023

 4.0
 09.05.2025
 000000105772
 Date of first issue: 05.03.2018

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikaflex®-521 UV

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street

Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45

Emergency telephone number : +61 1800 033 111

Telefax : +61 2 9725 33 30

Recommended use of the chemical and restrictions on use

Product use : Sealant/adhesive

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|--|------------|-----------------------|
| distillates (petroleum), hydrotreated light paraf- | 64742-55-8 | 0 -< 10 |
| finic | | |
| Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'- | 77703-56-1 | >= 2.5 -< 10 |
| butyl- | | |
| trimethoxyvinylsilane | 2768-02-7 | 0 -< 1 |

SECTION 4. FIRST AID MEASURES

Sikaflex®-521 UV



Date of last issue: 22.09.2023 Version Revision Date: SDS Number: 09.05.2025 000000105772 Date of first issue: 05.03.2018 4.0

General advice No hazards which require special first aid measures.

If inhaled Move to fresh air.

Take off contaminated clothing and shoes immediately. In case of skin contact

Wash off with soap and plenty of water.

Flush eyes with water as a precaution. In case of eye contact

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

No known significant effects or hazards.

See Section 11 for more detailed information on health effects

and symptoms.

Treat symptomatically. Notes to physician

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Hazardous combustion prod- :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

Standard procedure for chemical fires.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : For personal protection see section 8.

tive equipment and emer-

gency procedures

Environmental precautions No special environmental precautions required.

Sikaflex®-521 UV



Date of last issue: 22.09.2023 Version **Revision Date:** SDS Number: 09.05.2025 000000105772 Date of first issue: 05.03.2018 4.0

Methods and materials for containment and cleaning up Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Advice on safe handling For personal protection see section 8.

No special handling advice required.

Follow standard hygiene measures when handling chemical

products

Hygiene measures When using do not eat or drink.

When using do not smoke.

Conditions for safe storage Keep container tightly closed in a dry and well-ventilated

place.

Store in accordance with local regulations.

Materials to avoid No special restrictions on storage with other products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|---|------------|-------------------------------------|--|--------|
| distillates (petroleum), hy- drotreated light paraffinic | 64742-55-8 | TWA (Mist) | 5 mg/m3 | AU OEL |

Occupational exposure limits of decomposition products

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|------------|---------------|--------------------------------------|--|--------|
| methanol | 67-56-1 | TWA | 200 ppm 262 mg/m3 | AU OEL |
| | Further infor | Further information: Skin absorption | | |
| | | STEL | 250 ppm 328 mg/m3 | AU OEL |

Appropriate engineering

controls

Use adequate ventilation and/or engineering controls to pre-

vent exposure to vapours.

Sikaflex®-521 UV



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.09.2023

 4.0
 09.05.2025
 000000105772
 Date of first issue: 05.03.2018

Personal protective equipment

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Follow AS/NZS 1337.1

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Eye protection : Safety glasses

Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working

clothing, long trousers) Follow AS 2210:3

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : various

Odour : slight

Odour Threshold : No data available

pH : Not applicable

Melting point/ range / Freez-

ing point

No data available

Boiling point/boiling range : No data available

Flash point : $> 101 \, ^{\circ}\text{C} \, (> 214 \, ^{\circ}\text{F})$

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Sikaflex®-521 UV



SDS Number: Version **Revision Date:** Date of last issue: 22.09.2023 09.05.2025 000000105772 Date of first issue: 05.03.2018 4.0

Upper explosion limit / Upper :

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure 0.01 hPa

Relative vapour density No data available

ca. 1.40 g/cm3 (20 °C (68 °F)) Density

Solubility(ies)

Water solubility insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature No data available

Decomposition temperature No data available

Viscosity

Viscosity, dynamic Not applicable

Not applicable Viscosity, kinematic

Explosive properties No data available

Oxidizing properties No data available

Volatile organic compounds Directive 2010/75/EU of 24 November 2010 on industrial and

livestock rearing emissions (integrated pollution prevention

and control)

Volatile organic compounds (VOC) content: 0% w/w

SECTION 10. STABILITY AND REACTIVITY

No dangerous reaction known under conditions of normal use. Reactivity

Chemical stability The product is chemically stable.

tions

Possibility of hazardous reac- : No hazards to be specially mentioned.

Sikaflex®-521 UV



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.09.2023

 4.0
 09.05.2025
 000000105772
 Date of first issue: 05.03.2018

Conditions to avoid : No data available

Incompatible materials : see section 7.

Hazardous decomposition

products

No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

trimethoxyvinylsilane:

Acute oral toxicity : LD50 Oral (Rat): ca. 7,120 mg/kg

Acute inhalation toxicity : LC50: ca. 16.8 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Acute dermal toxicity : LD50: 3,540 mg/kg

Skin corrosion/irritation

Not classified due to lack of data.

Components:

distillates (petroleum), hydrotreated light paraffinic:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Chronic toxicity

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Sikaflex®-521 UV



Version Revision Date: SDS Number: Date of last issue: 22.09.2023 09.05.2025 000000105772 Date of first issue: 05.03.2018 4.0

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Urea, N, N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: EC50 (Raphidocelis subcapitata (freshwater green alga)): >

100 mg/l

Exposure time: 72 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

: There is no data available for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

Sikaflex®-521 UV



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.09.2023

 4.0
 09.05.2025
 000000105772
 Date of first issue: 05.03.2018

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo : Not applicable

aircraft)

Packing instruction (passen: :

ger aircraft)

Not applicable

IMDG-Code

UN number Not applicable Not applicable Proper shipping name Not applicable Class Subsidiary risk Not applicable Not applicable Packing group Not applicable Labels **EmS Code** Not applicable Marine pollutant Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Hazchem Code : Not applicable

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Therapeutic Goods (Poisons : Schedule 7 (Please use the original publication to check for Standard) Instrument : specific uses specific and itings or threshold limits that mig

Standard) Instrument specific uses, specific conditions or threshold limits that might

apply for this chemical)

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements : There is no applicable prohibition,

Sikaflex®-521 UV



Date of last issue: 22.09.2023 Version Revision Date: SDS Number: 09.05.2025 000000105772 Date of first issue: 05.03.2018 4.0

> authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.

The components of this product are reported in the following inventories:

AIIC : All components are listed on the inventory, regulatory obliga-

tions/restrictions apply

SECTION 16. OTHER INFORMATION

Revision Date 09.05.2025

Date of last issue 22.09.2023

Date format dd.mm.yyyy

Full text of other abbreviations

SVHC

AU OEL Australia. Workplace Exposure Standards for Airborne Con-

taminants.

AU OEL / TWA Exposure standard - time weighted average AU OEL / STEL Exposure standard - short term exposure limit

Australian Dangerous Goods Code. **ADG**

ADR European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS Chemical Abstracts Service Derived no-effect level DNEL

Half maximal effective concentration EC50 Globally Harmonized System

GHS

International Air Transport Association IATA

International Maritime Code for Dangerous Goods **IMDG**

LD50 Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

MARPOL International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

Occupational Exposure Limit OEL

PBT Persistent, bioaccumulative and toxic **PNEC** Predicted no effect concentration

Regulation (EC) No 1907/2006 of the European Parliament **REACH**

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

Substances of Very High Concern

Very persistent and very bioaccumulative vPvB

Sikaflex®-521 UV



Version 4.0

Revision Date: 09.05.2025

SDS Number: 000000105772

Date of last issue: 22.09.2023 Date of first issue: 05.03.2018

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN