SikaGrout®-300PT AU



Version SDS Number: Date of last issue: 16.07.2021 Revision Date: 000000609451 Date of first issue: 04.01.2016 23.06.2022 4.0

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SikaGrout®-300PT AU

Product code : 000000609451

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street

Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45 Telefax : +61 2 9725 33 30 : +61 1800 033 111 Emergency telephone num-

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion/irritation : Category 2

Serious eye damage/eye irri- : Category 1

tation

Skin sensitisation : Category 1

Carcinogenicity (Inhalation) : Category 1A

single exposure

Specific target organ toxicity - : Category 3 (Respiratory system)

GHS label elements

Hazard pictograms







Signal word Danger

Hazard statements H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation. H350 May cause cancer by inhalation.

Precautionary statements **Prevention:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P261 Avoid breathing dust.

SikaGrout®-300PT AU



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 16.07.2021

 4.0
 23.06.2022
 000000609451
 Date of first issue: 04.01.2016

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P280 Wear protective gloves/ protective clothing/ eye protective // protective clothing/ eye protective // protective // pro

tion/ face protection/ hearing protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical ad-

vice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

nginiy closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)	
Cement, portland, chemicals	65997-15-1	>= 60 -<= 100	
calcium carbonate	471-34-1	>= 10 -< 30	
calcium sulfate	7778-18-9	< 10	
Fumes, silica	69012-64-2	< 10	
calcium oxide	1305-78-8	>= 1 -< 3	
Quartz (SiO2) <5µm	14808-60-7	>= 0.1 -< 1	

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

SikaGrout®-300PT AU



Date of last issue: 16.07.2021 Version Revision Date: SDS Number: 000000609451 Date of first issue: 04.01.2016 23.06.2022 4.0

Show this safety data sheet to the doctor in attendance.

If inhaled Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact Take off contaminated clothing and shoes immediately.

> Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

irritant effects

sensitising effects

Cough

Respiratory disorder Allergic reactions **Excessive lachrymation**

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms. Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. May cause cancer by inhalation.

Treat symptomatically. Notes to physician

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Hazardous combustion prod- :

No hazardous combustion products are known

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SikaGrout®-300PT AU



Date of last issue: 16.07.2021 Version Revision Date: SDS Number: 000000609451 Date of first issue: 04.01.2016 23.06.2022 4.0

SECTION 6. ACCIDENTAL RELEASE MEASURES

tive equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

Environmental precautions Do not flush into surface water or sanitary sewer system.

Methods and materials for

containment and cleaning up

Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Advice on safe handling Do not breathe vapours/dust.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Hygiene measures Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage Store in original container.

> Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

Further information on stor-

Keep in a dry place.

age stability

No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
------------	---------	------------	-----------------	-------

SikaGrout®-300PT AU



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 16.07.2021

 4.0
 23.06.2022
 000000609451
 Date of first issue: 04.01.2016

		(Form of exposure)	ters / Permissible concentration		
Cement, portland, chemicals	65997-15-1	TWA	10 mg/m3	AU OEL	
calcium carbonate	471-34-1	TWA	10 mg/m3 (Calcium car-	AU OEL	
	bonate) Further information: This value is for inhalable dust containing no asbestos and < 1% crystalline silica				
calcium sulfate	7778-18-9	TWA	10 mg/m3	AU OEL	
	Further information: This value is for inhalable dust containing no asbestos and < 1% crystalline silica				
Fumes, silica	69012-64-2	TWA (Res- pirable dust)	2 mg/m3	AU OEL	
	Further information: Containing no asbestos and < 1% crystalline silica				
calcium oxide	1305-78-8	TWA	2 mg/m3	AU OEL	
Quartz (SiO2) <5μm	14808-60-7	TWA (Res- pirable dust)	0.05 mg/m3	AU OEL	
	Further information: Category 1A (Carc. 1A) Known to have carcinogenic potential for humans				

Appropriate engineering

controls

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Personal protective equipment

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

particulate filter P

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Follow AS/NZS 1337.1

Recommended: Butyl rubber, PVC, cotton gloves

Eye protection : Safety glasses

Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working

clothing, long trousers)

Follow AS 2210:3

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Colour : grey

Odour : characteristic

SikaGrout®-300PT AU



Version Date of last issue: 16.07.2021 Revision Date: SDS Number: 000000609451 Date of first issue: 04.01.2016 23.06.2022 4.0

Odour Threshold No data available

Not applicable pН

Melting point/range / Freezing :

Boiling point/boiling range

No data available

Flash point Not applicable

Evaporation rate No data available

Flammability (solid, gas) No data available

Upper explosion limit / Upper

flammability limit

No data available

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure No data available

Relative vapour density No data available

Density 1 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

No data available Auto-ignition temperature

Decomposition temperature No data available

Viscosity

Viscosity, dynamic No data available

Viscosity, kinematic Not applicable

Explosive properties No data available

Oxidizing properties No data available

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control)

Not applicable

SECTION 10. STABILITY AND REACTIVITY

SikaGrout®-300PT AU



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 16.07.2021

 4.0
 23.06.2022
 000000609451
 Date of first issue: 04.01.2016

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

No hazards to be specially mentioned.

Conditions to avoid : No data available

Incompatible materials : see section 7.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

calcium sulfate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer by inhalation.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

SikaGrout®-300PT AU



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 16.07.2021

 4.0
 23.06.2022
 000000609451
 Date of first issue: 04.01.2016

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

: There is no data available for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SikaGrout®-300PT AU



Version Date of last issue: 16.07.2021 Revision Date: SDS Number: 000000609451 Date of first issue: 04.01.2016 23.06.2022 4.0

National Regulations

ADG

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture : No poison schedule number allocated

Standard for the Uniform

Scheduling of Medicines and

Poisons

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements

Not applicable

There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

The components of this product are reported in the following inventories:

AIIC : On the inventory, or in compliance with the inventory, or has

been registered as new substance

AICS : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date 23.06.2022 Date format dd.mm.yyyy

Full text of other abbreviations

AU OEL Australia. Workplace Exposure Standards for Airborne Con-

AU OEL / TWA Exposure standard - time weighted average

Australian Dangerous Goods Code. **ADG**

European Agreement concerning the International Carriage of **ADR**

Dangerous Goods by Road

Chemical Abstracts Service CAS Derived no-effect level **DNEL**

Half maximal effective concentration EC50

Globally Harmonized System **GHS**

International Air Transport Association IATA

International Maritime Code for Dangerous Goods **IMDG**

Median lethal dosis (the amount of a material, given all at LD50

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

SikaGrout®-300PT AU



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 16.07.2021

 4.0
 23.06.2022
 000000609451
 Date of first issue: 04.01.2016

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN