

# SAFETY DATA SHEET

## Sikagard®-680 S Betoncolor



Version  
2.0

Revision Date:  
17.07.2023

SDS Number:  
000000003260

Date of last issue: 24.11.2018  
Date of first issue: 24.11.2018

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikagard®-680 S Betoncolor

#### Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.  
55 Elizabeth Street  
Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45

Emergency telephone number : +61 1800 033 111

Telefax : +61 2 9725 33 30

#### Recommended use of the chemical and restrictions on use

Product use : Intermediate

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Flammable liquids : Category 3

Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

Short-term (acute) aquatic hazard : Category 3

Long-term (chronic) aquatic hazard : Category 2

#### GHS label elements

Hazard pictograms : 

Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H402 Harmful to aquatic life.  
H411 Toxic to aquatic life with long lasting effects.

# SAFETY DATA SHEET

## Sikagard®-680 S Betoncolor



Version  
2.0

Revision Date:  
17.07.2023

SDS Number:  
000000003260

Date of last issue: 24.11.2018  
Date of first issue: 24.11.2018

### Precautionary statements

:

#### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P261 Avoid breathing mist or vapours.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

#### Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.  
P391 Collect spillage.

#### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

#### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards which do not result in classification

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Hydrocarbons, C9, aromatics	64742-95-6	>= 30 -< 60
2-methoxy-1-methylethyl acetate	108-65-6	>= 10 -< 20
xylene	1330-20-7	>= 2.5 -< 10
ethylbenzene	100-41-4	< 10
1,1'-[methylenebis(oxyethane-1,2-diyl oxy)]bisbenzene	13879-32-8	>= 0.25 -< 2.5

# SAFETY DATA SHEET

## Sikagard®-680 S Betoncolor



Version  
2.0

Revision Date:  
17.07.2023

SDS Number:  
000000003260

Date of last issue: 24.11.2018  
Date of first issue: 24.11.2018

n-butyl methacrylate	97-88-1	< 1
methyl methacrylate	80-62-6	< 1

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : irritant effects  
Cough  
Respiratory disorder  
Loss of balance  
Vertigo  
See Section 11 for more detailed information on health effects and symptoms.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.
- Notes to physician : Treat symptomatically.

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : Water  
High volume water jet

# SAFETY DATA SHEET

## Sikagard®-680 S Betoncolor



Version  
2.0

Revision Date:  
17.07.2023

SDS Number:  
000000003260

Date of last issue: 24.11.2018  
Date of first issue: 24.11.2018

- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.  
Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Use water spray to cool unopened containers.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Hazchem Code : •3Y

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.
- Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Use explosion-proof equipment.  
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.

# SAFETY DATA SHEET

## Sikagard®-680 S Betoncolor



Version  
2.0

Revision Date:  
17.07.2023

SDS Number:  
000000003260

Date of last issue: 24.11.2018  
Date of first issue: 24.11.2018

For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Follow standard hygiene measures when handling chemical products

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.  
Keep in a well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Store in accordance with local regulations.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrocarbons, C9, aromatics	64742-95-6	TWA	900 mg/m3	AU OEL
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 274 mg/m3	AU OEL
Further information: Skin absorption				
		STEL	100 ppm 548 mg/m3	AU OEL
xylene	1330-20-7	STEL	150 ppm 655 mg/m3	AU OEL
		TWA	80 ppm 350 mg/m3	AU OEL
ethylbenzene	100-41-4	TWA	100 ppm 434 mg/m3	AU OEL
		STEL	125 ppm 543 mg/m3	AU OEL
methyl methacrylate	80-62-6	TWA	50 ppm 208 mg/m3	AU OEL
Further information: Sensitiser				
		STEL	100 ppm 416 mg/m3	AU OEL

# SAFETY DATA SHEET

## Sikagard®-680 S Betoncolor



Version  
2.0

Revision Date:  
17.07.2023

SDS Number:  
000000003260

Date of last issue: 24.11.2018  
Date of first issue: 24.11.2018

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
xylene	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI

**Appropriate engineering controls** : Use adequate ventilation and/or engineering controls to prevent exposure to vapours.  
Avoid vapor formation.  
Provide appropriate exhaust ventilation at places where vapor is formed.

### Personal protective equipment

**Respiratory protection** : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  
Follow AS/NZS 1337.1  
Recommended: Butyl rubber/nitrile rubber gloves.  
Contaminated gloves should be removed.

**Eye protection** : Safety glasses

**Skin and body protection** : Protective clothing (e.g. safety shoes, long-sleeved working clothing, long trousers)  
Follow AS 2210:3  
Protective clothing needs to be made of cotton.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

# SAFETY DATA SHEET

## Sikagard®-680 S Betoncolor



Version  
2.0

Revision Date:  
17.07.2023

SDS Number:  
000000003260

Date of last issue: 24.11.2018  
Date of first issue: 24.11.2018

---

Appearance	: liquid
Colour	: clear
Odour	: hydrocarbon-like
Odour Threshold	: No data available
pH	: Not applicable
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: ca. 25 °C (77 °F) (Method: closed cup)
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: 7 %(V)
Lower explosion limit / Lower flammability limit	: 0.8 %(V)
Vapour pressure	: 7.9993 hPa
Relative vapour density	: No data available
Density	: ca. 0.9 g/cm <sup>3</sup> (20 °C (68 °F))
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: 333 °C
Decomposition temperature	: No data available
Viscosity	

---

# SAFETY DATA SHEET

## Sikagard®-680 S Betoncolor



Version  
2.0

Revision Date:  
17.07.2023

SDS Number:  
000000003260

Date of last issue: 24.11.2018  
Date of first issue: 24.11.2018

Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 20.5 mm <sup>2</sup> /s ( 40 °C (104 °F))
Explosive properties	: No data available
Oxidizing properties	: No data available
Volatile organic compounds	: Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 56.2% w/w

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: see section 7.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Components:

##### Hydrocarbons, C9, aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

##### 2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

##### xylene:

Acute oral toxicity : LD50 Oral (Rat): 3,523 mg/kg

##### ethylbenzene:

Acute oral toxicity : LD50 Oral (Rat): 3,500 mg/kg



# SAFETY DATA SHEET

## Sikagard®-680 S Betoncolor



Version  
2.0

Revision Date:  
17.07.2023

SDS Number:  
000000003260

Date of last issue: 24.11.2018  
Date of first issue: 24.11.2018

Acute dermal toxicity : LD50 Dermal (Rabbit): 5,510 mg/kg

**1,1'-[methylenebis(oxyethane-1,2-diylloxy)]bisbenzene:**

Acute oral toxicity : LD50 Oral (Rat): > 10,000 mg/kg

**methyl methacrylate:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 29.8 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Components:**

**Hydrocarbons, C9, aromatics:**

Assessment : Repeated exposure may cause skin dryness or cracking.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Respiratory or skin sensitisation**

**Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Chronic toxicity**

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

May cause respiratory irritation.  
May cause drowsiness or dizziness.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

# SAFETY DATA SHEET

## Sikagard®-680 S Betoncolor



Version  
2.0

Revision Date:  
17.07.2023

SDS Number:  
000000003260

Date of last issue: 24.11.2018  
Date of first issue: 24.11.2018

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

##### Components:

##### **Hydrocarbons, C9, aromatics:**

Toxicity to algae/aquatic plants : (Pseudokirchneriella subcapitata (green algae)): 2.6 - 2.9 mg/l  
Exposure time: 72 h

##### **xylene:**

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l  
Exposure time: 56 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia (water flea)): 1.17 mg/l  
Exposure time: 7 d

##### **methyl methacrylate:**

Toxicity to fish : NOEC (Danio rerio (zebra fish)): 9.4 mg/l

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 69 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

NOEC: 37 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 202

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 37 mg/l  
Exposure time: 21 d

#### **Persistence and degradability**

No data available

#### **Bioaccumulative potential**

No data available

#### **Mobility in soil**

No data available

#### **Other adverse effects**

##### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

# SAFETY DATA SHEET

## Sikagard®-680 S Betoncolor



Version  
2.0

Revision Date:  
17.07.2023

SDS Number:  
000000003260

Date of last issue: 24.11.2018  
Date of first issue: 24.11.2018

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

- UN/ID No. : UN 1263  
Proper shipping name : Paint  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

##### IMDG-Code

- UN number : UN 1263  
Proper shipping name : PAINT  
(solvent naphtha)  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : yes

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### National Regulations

##### ADG

- UN number : UN 1263  
Proper shipping name : PAINT  
Class : 3  
Packing group : III  
Labels : 3

# SAFETY DATA SHEET

## Sikagard®-680 S Betoncolor



Version  
2.0

Revision Date:  
17.07.2023

SDS Number:  
000000003260

Date of last issue: 24.11.2018  
Date of first issue: 24.11.2018

Hazchem Code : •3Y

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : Schedule 5  
Scheduling of Medicines and  
Poisons

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors  
Prohibition/Licensing Requirements : There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.

### The components of this product are reported in the following inventories:

AIIC : On the inventory, or in compliance with the inventory

## SECTION 16. OTHER INFORMATION

Revision Date : 17.07.2023

Date format : dd.mm.yyyy

### Full text of other abbreviations

ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.  
AU OEL / TWA : Exposure standard - time weighted average  
AU OEL / STEL : Exposure standard - short term exposure limit  
ADG : Australian Dangerous Goods Code.  
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road  
CAS : Chemical Abstracts Service  
DNEL : Derived no-effect level  
EC50 : Half maximal effective concentration  
GHS : Globally Harmonized System  
IATA : International Air Transport Association  
IMDG : International Maritime Code for Dangerous Goods  
LD50 : Median lethal dose (the amount of a material, given all at

# SAFETY DATA SHEET

## Sikagard®-680 S Betoncolor



Version  
2.0

Revision Date:  
17.07.2023

SDS Number:  
000000003260

Date of last issue: 24.11.2018  
Date of first issue: 24.11.2018

	once, which causes the death of 50% (one half) of a group of test animals)
LC50	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: [aus.sika.com](http://aus.sika.com)

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

AU / EN