

# SAFETY DATA SHEET

## Sikalastic®-701 Part A



Version  
1.0

Revision Date:  
12.04.2023

SDS Number:  
100000017152

Date of last issue: -  
Date of first issue: 12.04.2023

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikalastic®-701 Part A

#### Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.  
55 Elizabeth Street  
Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45

Emergency telephone number : +61 1800 033 111

Telefax : +61 2 9725 33 30

#### Recommended use of the chemical and restrictions on use

Product use : Liquid applied membranes

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Flammable liquids : Category 3

Skin sensitisation : Category 1

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Short-term (acute) aquatic hazard : Category 3

Long-term (chronic) aquatic hazard : Category 3

#### GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.  
H317 May cause an allergic skin reaction.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

# SAFETY DATA SHEET

## Sikalastic®-701 Part A



Version  
1.0

Revision Date:  
12.04.2023

SDS Number:  
100000017152

Date of last issue: -  
Date of first issue: 12.04.2023

Precautionary statements

:

### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing mist or vapours.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

### Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards which do not result in classification

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
---------------	---------	-----------------------

# SAFETY DATA SHEET

## Sikalastic®-701 Part A



Version  
1.0

Revision Date:  
12.04.2023

SDS Number:  
100000017152

Date of last issue: -  
Date of first issue: 12.04.2023

2-methoxy-1-methylethyl acetate	108-65-6	$\geq 20$ -< 30
n-butyl acetate	123-86-4	0 -< 10
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	$\geq 0.1$ -< 3
2-hydroxyethyl methacrylate	868-77-9	0 -< 1
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	82919-37-7	$\geq 0.1$ -< 3

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : sensitising effects  
Allergic reactions  
Loss of balance  
Vertigo  
See Section 11 for more detailed information on health effects and symptoms.  
May cause an allergic skin reaction.  
May cause drowsiness or dizziness.
- Notes to physician : Treat symptomatically.

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

# SAFETY DATA SHEET

## Sikalastic®-701 Part A



Version  
1.0

Revision Date:  
12.04.2023

SDS Number:  
100000017152

Date of last issue: -  
Date of first issue: 12.04.2023

- Unsuitable extinguishing media : Water  
High volume water jet
- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Use water spray to cool unopened containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Hazchem Code : •3Y

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.
- Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

---

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Use explosion-proof equipment.  
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.

# SAFETY DATA SHEET

## Sikalastic®-701 Part A



Version  
1.0

Revision Date:  
12.04.2023

SDS Number:  
100000017152

Date of last issue: -  
Date of first issue: 12.04.2023

For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Follow standard hygiene measures when handling chemical products

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.  
Keep in a well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Store in accordance with local regulations.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 274 mg/m <sup>3</sup>	AU OEL
Further information: Skin absorption				
		STEL	100 ppm 548 mg/m <sup>3</sup>	AU OEL
n-butyl acetate	123-86-4	STEL	200 ppm 950 mg/m <sup>3</sup>	AU OEL
		TWA	150 ppm 713 mg/m <sup>3</sup>	AU OEL

Appropriate engineering controls : Use adequate ventilation and/or engineering controls to prevent exposure to vapours.  
Avoid vapor formation.  
Provide appropriate exhaust ventilation at places where vapor is formed.

#### Personal protective equipment

# SAFETY DATA SHEET

## Sikalastic®-701 Part A



Version  
1.0

Revision Date:  
12.04.2023

SDS Number:  
100000017152

Date of last issue: -  
Date of first issue: 12.04.2023

- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  
Follow AS/NZS 1337.1  
Recommended: Butyl rubber/nitrile rubber gloves.  
Contaminated gloves should be removed.
- Eye protection : Safety glasses
- Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working clothing, long trousers)  
Follow AS 2210:3  
Protective clothing needs to be made of cotton.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : white
- Odour : mild
- Odour Threshold : No data available
- pH : Not applicable
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : > 44 °C (111 °F)  
(Method: closed cup)
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available

# SAFETY DATA SHEET

## Sikalastic®-701 Part A



Version  
1.0

Revision Date:  
12.04.2023

SDS Number:  
100000017152

Date of last issue: -  
Date of first issue: 12.04.2023

Upper explosion limit / Upper flammability limit : 7.5 %(V)

Lower explosion limit / Lower flammability limit : 1.2 %(V)

Vapour pressure : 12.4989 hPa

Relative vapour density : No data available

Density : ca. 1.27 g/cm<sup>3</sup> (20 °C (68 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : 333 °C

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : 250 mPa.s

Viscosity, kinematic : > 20.5 mm<sup>2</sup>/s ( 40 °C (104 °F))

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 32.9% w/w

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reactions : Stable under recommended storage conditions.  
Vapours may form explosive mixture with air.

# SAFETY DATA SHEET

## Sikalastic®-701 Part A



Version  
1.0

Revision Date:  
12.04.2023

SDS Number:  
100000017152

Date of last issue: -  
Date of first issue: 12.04.2023

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : see section 7.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **2-methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

##### **n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 23.4 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

#### Skin corrosion/irritation

Not classified based on available information.

#### Components:

##### **n-butyl acetate:**

Result : Repeated exposure may cause skin dryness or cracking.

#### Serious eye damage/eye irritation

Not classified based on available information.

#### Respiratory or skin sensitisation

##### **Skin sensitisation**

May cause an allergic skin reaction.

##### **Respiratory sensitisation**

Not classified based on available information.

#### Chronic toxicity

##### **Germ cell mutagenicity**

Not classified based on available information.



# SAFETY DATA SHEET

## Sikalastic®-701 Part A



Version  
1.0

Revision Date:  
12.04.2023

SDS Number:  
100000017152

Date of last issue: -  
Date of first issue: 12.04.2023

### **Carcinogenicity**

Not classified based on available information.

### **Reproductive toxicity**

Not classified based on available information.

### **STOT - single exposure**

May cause drowsiness or dizziness.

### **STOT - repeated exposure**

Not classified based on available information.

### **Aspiration toxicity**

Not classified based on available information.

---

## **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

#### **Components:**

##### **n-butyl acetate:**

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 647.7 mg/l  
Exposure time: 72 h

### **Persistence and degradability**

No data available

### **Bioaccumulative potential**

No data available

### **Mobility in soil**

No data available

### **Other adverse effects**

#### **Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

## **SECTION 13. DISPOSAL CONSIDERATIONS**

### **Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

# SAFETY DATA SHEET

## Sikalastic®-701 Part A



Version  
1.0

Revision Date:  
12.04.2023

SDS Number:  
100000017152

Date of last issue: -  
Date of first issue: 12.04.2023

Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

UN/ID No. : UN 1993  
Proper shipping name : Flammable liquid, n.o.s.  
(2-methoxy-1-methylethyl acetate)  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366

##### IMDG-Code

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(2-methoxy-1-methylethyl acetate)  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### National Regulations

##### ADG

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(2-methoxy-1-methylethyl acetate)  
Class : 3  
Packing group : III  
Labels : 3  
Hazchem Code : •3Y

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### SECTION 15. REGULATORY INFORMATION

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : Schedule 5

# SAFETY DATA SHEET

## Sikalastic®-701 Part A



Version  
1.0

Revision Date:  
12.04.2023

SDS Number:  
100000017152

Date of last issue: -  
Date of first issue: 12.04.2023

Scheduling of Medicines and  
Poisons

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors  
Prohibition/Licensing Requirements : There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.

### The components of this product are reported in the following inventories:

AIIC : On the inventory, or in compliance with the inventory

## SECTION 16. OTHER INFORMATION

Revision Date : 12.04.2023

Date format : dd.mm.yyyy

### Full text of other abbreviations

AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.  
AU OEL / TWA : Exposure standard - time weighted average  
AU OEL / STEL : Exposure standard - short term exposure limit  
ADG : Australian Dangerous Goods Code.  
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road  
CAS : Chemical Abstracts Service  
DNEL : Derived no-effect level  
EC50 : Half maximal effective concentration  
GHS : Globally Harmonized System  
IATA : International Air Transport Association  
IMDG : International Maritime Code for Dangerous Goods  
LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)  
LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)  
MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978  
OEL : Occupational Exposure Limit  
PBT : Persistent, bioaccumulative and toxic  
PNEC : Predicted no effect concentration  
REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemi-

# SAFETY DATA SHEET

## Sikalastic®-701 Part A



Version  
1.0

Revision Date:  
12.04.2023

SDS Number:  
100000017152

Date of last issue: -  
Date of first issue: 12.04.2023

---

SVHC	:	cals (REACH), establishing a European Chemicals Agency
vPvB	:	Substances of Very High Concern
	:	Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: [aus.sika.com](http://aus.sika.com)

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

AU / EN