Sikaflex[®]-255 FC



Version	Revision Date:	SDS Number:	Date of last issue: 08.04.2022
1.1	21.01.2025	000000606814	Date of first issue: 08.04.2022

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name:Sikaflex®-255 FCManufacturer or supplier's detailsCompany:Sika Australia Pty. Ltd.
55 Elizabeth Street
Wetherill Park, NSW 2164Telephone:+61 2 9725 11 45Emergency telephone number:+61 1800 033 111Telefax:+61 2 9725 33 30

Recommended use of the chemical and restrictions on use

Product use	:	Adhesive
-------------	---	----------

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification	
Flammable liquids	

Flammable liquids	:	Category 4
Specific target organ toxicity - repeated exposure (Inhala- tion)	:	Category 2 (Central nervous system)
Short-term (acute) aquatic hazard	:	Category 3
Long-term (chronic) aquatic hazard	:	Category 3
GHS label elements Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	H227 Combustible liquid. H373 May cause damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames

Sikaflex[®]-255 FC



Version 1.1	Revision Date: 21.01.2025	SDS Number: 000000606814	Date of last issue: 08.04.2022 Date of first issue: 08.04.2022
		and other ignition sources. P260 Do not breathe mist of P273 Avoid release to the P280 Wear protective glov tion/ face protection/ hearing	or vapours. environment. es/ protective clothing/ eye protec-
		Response:	- 4 4
		P314 Get medical advice/ P370 + P378 In case of fire alcohol-resistant foam to e	e: Use dry sand, dry chemical or
		Storage:	
		P403 Store in a well-ventila	ated place.
		Disposal:	
		P501 Dispose of contents/ disposal plant.	container to an approved waste
Othor	bazarda which do not	regult in clossification	

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	64742-82-1	>= 1 -< 2.5
xylene	1330-20-7	>= 0.25 -< 2.5
4,4'-methylenediphenyl diisocyanate	101-68-8	0 -< 1
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	>= 0.025 -< 0.25
dibutyltin dichloride	683-18-1	>= 0.0025 -< 0.025

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	: Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
	2/11

Sikaflex[®]-255 FC



Version 1.1	Revision Date: 21.01.2025		SDS Number: 000000606814	Date of last issue: 08.04.2022 Date of first issue: 08.04.2022
If swallowed		:	Do not give milk or alcoholic	drink afterwards plenty of water. beverages. th to an unconscious person.
Most important symptoms and effects, both acute and delayed		:	and symptoms.	or hazards. ailed information on health effects ns through prolonged or repeated
Notes	s to physician	: Treat symptomatically.		

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Carbon dioxide (CO2)
Unsuitable extinguishing media	:	Water
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
Specific extinguishing meth- ods	:	Standard procedure for chemical fires.
	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer- gency procedures	Use personal protective equipment. Deny access to unprotected persons.
Environmental precautions :	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for : containment and cleaning up	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Advice on safe handling	:	Avoid exceeding the given occupational exposure limits (see section 8).

Sikaflex[®]-255 FC



Version 1.1	Revision Date: 21.01.2025	SDS Number: 000000606814	Date of last issue: 08.04.2022 Date of first issue: 08.04.2022
		For personal protec Smoking, eating an plication area.	on skin, or on clothing. tion see section 8. d drinking should be prohibited in the ap- giene measures when handling chemical
Hygiene measures Conditions for safe storage		practice. When using do not When using do not Wash hands before Store in original cor Keep in a well-venti Observe label preca	smoke. breaks and at the end of workday. itainer. lated place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis	
Hydrocarbons, C9-C12, n- alkanes, isoalkanes, cyclics, aromatics (2-25%)	64742-82-1	TWA	900 mg/m3	AU OEL	
xylene	1330-20-7	STEL	150 ppm 655 mg/m3	AU OEL	
		TWA	80 ppm 350 mg/m3	AU OEL	
4,4'-methylenediphenyl diiso- cyanate	101-68-8	TWA	0.02 mg/m3 (NCO)	AU OEL	
	Further inform cinogen, Sens		2 (Carc. 2) Suspected	d human car-	
		STEL	0.07 mg/m3 (NCO)	AU OEL	
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9	TWA	0.02 mg/m3 (NCO)	AU OEL	
	Further information: Sensitiser				
		STEL	0.07 mg/m3 (NCO)	AU OEL	

Biological occupational exposure limits

Components	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
xylene	1330-20-7	Methylhip- puric acids	Urine	End of shift (As soon as possible after ex- posure	1.5 g/g creat- inine	ACGIH BEI

Sikaflex[®]-255 FC



Vers 1.1	ion Revision Date: 21.01.2025		SDS Number: 00000060681		of last issue: 08.04.2022 of first issue: 08.04.2022
				ceases)	
	Appropriate engineering controls	:	Use adequate vent vent exposure to va	ilation and/or enginee	ring controls to pre-
	Personal protective equip	ment			
	Respiratory protection	:	Respirator selectio exposure levels, th	ate ventilation wear rean n must be based on kn e hazards of the produ e selected respirator.	nown or anticipated
	Hand protection	:	approved standard chemical products essary. Follow AS/NZS 133 Recommended: Bu	, impervious gloves co should be worn at all if a risk assessment in 37.1 ityl rubber/nitrile rubbe es should be removed	times when handling idicates this is nec- er gloves.
	Eye protection	:	Safety glasses		
	Skin and body protection	:	clothing, long trous Follow AS 2210:3	(e.g. safety shoes, lor ers) needs to be made of o	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	paste
Colour	:	black
Odour	:	characteristic
Odour Threshold	:	No data available
рН	:	Not applicable
Melting point/ range / Freez-	:	No data available
ing point Boiling point/boiling range	:	No data available
Flash point	:	ca. 80 °C (176 °F) (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower	:	No data available

Sikaflex[®]-255 FC



Version 1.1	Revision Date: 21.01.2025		SDS Number: 000000606814	Date of last issue: 08.04.2022 Date of first issue: 08.04.2022
flam	mability limit			
Vap	our pressure	:	0.01 hPa	
Rela	ative vapour density	:	No data available	
Den	sity	:	ca. 1.22 g/cm3 (23 °C (73 °F))	
	ıbility(ies) Vater solubility	:	insoluble	
S	Solubility in other solvents	:	No data available	
	ition coefficient: n- nol/water	:	No data available	
	p-ignition temperature	:	No data available	
Dec	omposition temperature	:	No data available	
	osity /iscosity, dynamic	:	No data available	
٨	/iscosity, kinematic	:	ca. > 20.5 mm2/s (40 °C (104 °F	-))
Exp	losive properties	:	No data available	
Oxic	lizing properties	:	No data available	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reac- tions	:	No hazards to be specially mentioned.
Conditions to avoid	:	No data available
Incompatible materials	:	see section 7.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Sikaflex[®]-255 FC



rsion	Revision Date: 21.01.2025	SDS Number: 000000606814	Date of last issue: 08.04.2022 Date of first issue: 08.04.2022
Comp	onents:		
xylene			
Acute	oral toxicity	: LD50 Oral (Rat): 3,523 mg/	kg
	ethylenediphenyl dii		
Acute	oral toxicity	: LD50 Oral (Rat): > 5,000 m Method: OECD Test Guidel	
Acute	inhalation toxicity	: LC50: 1.5 mg/l	
		Exposure time: 4 h	
		Test atmosphere: dust/mist Method: Expert judgement	
	yanatomethyl-3,5,5-1 oral toxicity	rimethylcyclohexyl isocyanate: : LD50 Oral (Rat): 4,814 mg/	
	inhalation toxicity	: LC50 (Rat): 0.031 mg/l	5
Acute		Exposure time: 4 h	
		Test atmosphere: dust/mist	
Acute	dermal toxicity	: LD50 Dermal (Rat): > 7,000) mg/kg
dibuty	/Itin dichloride:		
Acute	oral toxicity	: LD50 Oral (Rat): 219 mg/kg	3
	corrosion/irritation assified based on avai	lable information.	
Comp	onents:		
-	carbons, C9-C12, n-	alkanes, isoalkanes, cyclics, arc : Repeated exposure may ca	omatics (2-25%): ause skin dryness or cracking.
Serio	us eye damage/eye iı	ritation	
	assified based on avai		
Respi	ratory or skin sensit	sation	
Skin s	ensitisation		
Not cla	assified based on avai	lable information.	
Respi	ratory sensitisation		
-	assified based on avai	lable information.	
Chron	ic toxicity		
	cell mutagenicity		
	assified based on avai	lable information.	
	nogenicity		
	assified based on avai		

Sikaflex[®]-255 FC



Version	Revision Date:	SDS Number:	Date of last issue: 08.04.2022
1.1	21.01.2025	00000606814	Date of first issue: 08.04.2022

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

May cause damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

xylene: Toxicity to fish (Chronic tox- : icity)	NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l Exposure time: 56 d
Toxicity to daphnia and other : aquatic invertebrates (Chron- ic toxicity)	NOEC (Daphnia (water flea)): 1.17 mg/l Exposure time: 7 d
dibutyltin dichloride: Toxicity to daphnia and other : aquatic invertebrates	EC50 (Daphnia (water flea)): 1.4 mg/l Exposure time: 48 h
M-Factor (Acute aquatic tox- : icity)	10
M-Factor (Chronic aquatic : toxicity)	10
Persistence and degradability No data available	
Bioaccumulative potential No data available	
Mobility in soil	
No data available Other adverse effects	
<u>Product:</u> Additional ecological infor- : mation	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life with long lasting effects.

Sikaflex[®]-255 FC



1.1 21.01.2025 000000606814 Date of first issue: 08.04.202	Version	Revision Date:	SDS Number:	Date of last issue: 08.04.2022
	1.1	21.01.2025	00000606814	Date of first issue: 08.04.2022

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods Waste from residues	:	Send to a licensed waste management company.
		The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemi- cal or used container.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product.
		Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR UN/ID No. Proper shipping name Class Subsidiary risk Packing group Labels Packing instruction (cargo aircraft) Packing instruction (passen- ger aircraft)	Not applicable Not applicable Not applicable Not applicable Not applicable Not applicable Not applicable
IMDG-Code UN number Proper shipping name Class Subsidiary risk Packing group Labels EmS Code Marine pollutant	Not applicable Not applicable Not applicable Not applicable Not applicable Not applicable Not applicable Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG		
UN number	:	Not applicable
Proper shipping name	:	Not applicable
Class	:	Not applicable
Subsidiary risk	:	Not applicable

Sikaflex[®]-255 FC



Version 1.1	Revision Date: 21.01.2025	SDS Number: 000000606814		Date of last issue: 08.04.2022 Date of first issue: 08.04.2022		
Labe	ting group els chem Code	 Not applicable Not applicable Not applicable 				
-	Special precautions for user Not applicable					
SECTION	15. REGULATORY INF	ORMATION				
Thera	-	ental regulations/legisl : No poison schedule		specific for the substance or mixture per allocated		
Schee	International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors Prohibition/Licensing Requirements		:	Not applicable		

The components of this product are reported in the following inventories:AICS: On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date Date format	-	21.01.2025 dd.mm.yyyy			
Full text of other abbreviations					
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)			
AU OEL	:	Australia. Workplace Exposure Standards for Airborne Con- taminants.			
AU OEL / TWA	:	Exposure standard - time weighted average			
AU OEL / STEL	:	Exposure standard - short term exposure limit			
ADG	:	Australian Dangerous Goods Code.			
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road			
CAS	:	Chemical Abstracts Service			
DNEL	:	Derived no-effect level			
EC50	:	Half maximal effective concentration			
GHS	:	Globally Harmonized System			
ΙΑΤΑ	:	International Air Transport Association			
IMDG	:	International Maritime Code for Dangerous Goods			
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)			
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation			

Sikaflex®-255 FC



Version 1.1	Revision Date: 21.01.2025		SDS Number: 000000606814	Date of last issue: 08.04.2022 Date of first issue: 08.04.2022
MARPO	L	:	period) International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978	
OEL PBT PNEC		:	Occupational Exposure Limit Persistent, bioaccumulative and toxic Predicted no effect concentration	
REACH		:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency	
SVHC vPvB		:	Substances of Very High Conce Very persistent and very bioaccu	rn

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

AU / EN