Sika Thinner 15



Version Revision Date: SDS Number: Date of last issue: 11.08.2018 000000606181 Date of first issue: 11.08.2018 13.02.2022 2.0

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sika Thinner 15

Product code : 000000606181

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street

Wetherill Park. NSW 2164

Telephone : +61 2 9725 11 45 : +61 2 9725 33 30 Telefax : +61 1800 033 111 Emergency telephone num-

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 4

Skin corrosion/irritation Category 2

Serious eye damage/eye irri- : Category 1

tation

single exposure

Specific target organ toxicity - : Category 3 (Respiratory system)

Specific target organ toxicity - : Category 2

repeated exposure

(Inhalation)

: Category 1 Aspiration hazard

Short-term (acute) aquatic

hazard

Category 2

Long-term (chronic) aquatic

hazard

: Category 3

GHS label elements

Hazard pictograms









Signal word Danger

Sika Thinner 15



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 11.08.2018

 2.0
 13.02.2022
 000000606181
 Date of first issue: 11.08.2018

Hazard statements : H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or re-

peated exposure if inhaled. H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting equipment

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P260 Do not breathe mist or vapours.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/

doctor if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/ doctor.

P314 Get medical advice/ attention if you feel unwell.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Sika Thinner 15



Version Revision Date: Date of last issue: 11.08.2018 SDS Number: 000000606181 Date of first issue: 11.08.2018 13.02.2022 2.0

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
xylene	1330-20-7	>= 60 -<= 100
ethylbenzene	100-41-4	>= 10 -< 30
2-methylpropan-1-ol	78-83-1	>= 10 -< 20

SECTION 4. FIRST AID MEASURES

General advice Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled Move to fresh air.

Consult a physician after significant exposure.

Take off contaminated clothing and shoes immediately. In case of skin contact

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.

Most important symptoms

and effects, both acute and

delayed

Risk of serious damage to the lungs (by aspiration).

irritant effects

Aspiration may cause pulmonary oedema and pneumonitis.

Cough

Respiratory disorder **Excessive lachrymation**

Sika Thinner 15



Date of last issue: 11.08.2018 Version Revision Date: SDS Number: Date of first issue: 11.08.2018 13.02.2022 000000606181 2.0

> Headache Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye damage.

Harmful if inhaled.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated

exposure if inhaled.

Notes to physician Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

Water

Hazardous combustion prod- :

No hazardous combustion products are known

Specific extinguishing meth-

Use water spray to cool unopened containers.

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Hazchem Code •3YE

SECTION 6. ACCIDENTAL RELEASE MEASURES

tive equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment.

Remove all sources of ignition. Deny access to unprotected persons.

Environmental precautions Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Sika Thinner 15



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 11.08.2018

 2.0
 13.02.2022
 000000606181
 Date of first issue: 11.08.2018

Advice on protection against :

fire and explosion

Use explosion-proof equipment.

Keep away from heat/ sparks/ open flames/ hot surfaces. No

smoking.

Take precautionary measures against electrostatic discharg-

es.

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

products

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
xylene	1330-20-7 ST		150 ppm 655 mg/m3	AU OEL
		TWA	80 ppm 350 mg/m3	AU OEL
ethylbenzene	100-41-4	TWA	100 ppm 434 mg/m3	AU OEL
		STEL	125 ppm 543 mg/m3	AU OEL
2-methylpropan-1-ol	78-83-1	TWA	50 ppm 152 mg/m3	AU OEL

Sika Thinner 15



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 11.08.2018

 2.0
 13.02.2022
 000000606181
 Date of first issue: 11.08.2018

Biological occupational exposure limits

Components	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
xylene	1330-20-7	Methylhip- puric acids	Urine	End of shift (As soon as possible after ex- posure ceases)	1.5 g/g creat- inine	ACGIH BEI
ethylbenzene	100-41-4	Sum of mandelic acid and phenyl gly- oxylic acid	Urine	End of shift (As soon as possible after ex- posure ceases)	0.15 g/g cre- atinine	ACGIH BEI

Appropriate engineering

controls

Use adequate ventilation and/or engineering controls to pre-

vent exposure to vapours.

Avoid vapor formation.

Provide appropriate exhaust ventilation at places where va-

por is formed.

Personal protective equipment

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

organic vapor filter (Type A)

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Follow AS/NZS 1337.1

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Eye protection : Safety goggles

Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working

clothing, long trousers) Follow AS 2210:3

Protective clothing needs to be made of cotton.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : clear

Sika Thinner 15



Version Revision Date: Date of last issue: 11.08.2018 SDS Number: 000000606181 Date of first issue: 11.08.2018 13.02.2022 2.0

Odour characteristic

Odour Threshold No data available

Not applicable

Melting point/range / Freezing :

No data available

Boiling point/boiling range 130 °C (266 °F)

Flash point 24 °C (75 °F)

(Method: closed cup)

Evaporation rate No data available

Flammability (solid, gas) No data available

Upper explosion limit / Upper

flammability limit

Upper flammability limit

9 %(V)

Lower explosion limit / Lower

flammability limit

: Lower flammability limit

1.6 %(V)

Vapour pressure 12 hPa

Relative vapour density No data available

0.85 g/cm3 (20 °C (68 °F)) Density

Solubility(ies)

Water solubility No data available

Solubility in other solvents :

Partition coefficient: n-

octanol/water

No data available

No data available

415 °C Auto-ignition temperature

Decomposition temperature No data available

Viscosity

No data available Viscosity, dynamic

> 7 mm2/s (40 °C (104 °F)) Viscosity, kinematic

Explosive properties No data available

Oxidizing properties No data available

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 100% w/w

Sika Thinner 15



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 11.08.2018

 2.0
 13.02.2022
 000000606181
 Date of first issue: 11.08.2018

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions. Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : see section 7.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if inhaled.

Components:

xylene:

Acute oral toxicity : LD50 Oral (Rat): 3,523 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 1,700 mg/kg

ethylbenzene:

Acute oral toxicity : LD50 Oral (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 5,510 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Sika Thinner 15



Version Date of last issue: 11.08.2018 Revision Date: SDS Number: Date of first issue: 11.08.2018 13.02.2022 000000606181 2.0

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

xylene:

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 2.2

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l

Exposure time: 56 d

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia (water flea)): 1.17 mg/l

Exposure time: 7 d

ethylbenzene:

M-Factor (Acute aquatic tox- : 1

icity)

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues The product should not be allowed to enter drains, water

courses or the soil.

Sika Thinner 15



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 11.08.2018

 2.0
 13.02.2022
 000000606181
 Date of first issue: 11.08.2018

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1993

Proper shipping name : Flammable liquid, n.o.s.

Class : 3 Packing group : II

Labels : Flammable Liquids

Packing instruction (cargo : 364

aircraft)

Packing instruction (passen- : 353

ger aircraft)

IMDG-Code

UN number : UN 1993

Proper shipping name : FLAMMABLE LIQUID, N.O.S.

 Class
 : 3

 Packing group
 : II

 Labels
 : 3

 EmS Code
 : F-E, S-E

 Marine pollutant
 : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number : UN 1993

Proper shipping name : FLAMMABLE LIQUID, N.O.S.

Class : 3
Packing group : II
Labels : 3
Hazchem Code : •3YE

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet.

Sika Thinner 15



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 11.08.2018

 2.0
 13.02.2022
 000000606181
 Date of first issue: 11.08.2018

Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : Schedule 6

Scheduling of Medicines and

Poisons

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements

Not applicable

There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions

The components of this product are reported in the following inventories:

AIIC : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date : 13.02.2022 Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

AU OEL : Australia. Workplace Exposure Standards for Airborne Con-

taminants.

AU OEL / TWA : Exposure standard - time weighted average AU OEL / STEL : Exposure standard - short term exposure limit

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

Sika Thinner 15



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 11.08.2018

 2.0
 13.02.2022
 000000606181
 Date of first issue: 11.08.2018

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN