

PRODUCT DATA SHEET

Sikagard®-220 Invisible Sealer

A general purpose penetrating sealer for porous surfaces

DESCRIPTION

- Sikagard®-220 Invisible Sealer is a general purpose, solvent free, penetrating sealer designed to prevent water, moisture and staining to porous surfaces.
- Sikagard®-220 Invisible Sealer is milky white in appearance but dries invisible.
- Sikagard®-220 Invisible Sealer prevents mould and Efflorescence.

USES

Sikagard®-220 Invisible Sealer is suitable for the following surfaces with porosity greater than 5% including

- Concrete
- Pavers
- Porous Tiles
- Natural Stone, including Marble, Limestone, Blue-stone, Granite and other porous stones.
- Terracotta
- Slate
- Cement based renders and masonry
- Cement-based tile grout
- Cement boards and sheets

FEATURES

- Seals and protects surfaces from water & moisture
- Prevents stains
- Easy to use
- Fast drying
- Prevents Efflorescence
- Prevents Mould Growth
- Invisible when dry for natural appearance
- Creates water beading effect to prevent moisture and stain by increasing penetration time.
- Low VOC

PRODUCT INFORMATION

Packaging	500ml Spray Bottle 5Ltr Jerry Can
Appearance and colour	Milky white liquid that dries clear.
Shelf life	12 months from date of manufacture.
Storage conditions	Store in dry cool conditions out of direct sunlight. Prevent from freezing.

APPLICATION INFORMATION

Consumption

Consumption shall depend on the porosity of the material being treated. Consumption as a guide only and porosity of materials being treated is beyond the control of the manufacturer.

Porosity level	Approximate coverage per Ltr
High porosity	2-4m ² per Ltr
Medium porosity	4-6m ² per Ltr
Low porosity	6-10m ² per Ltr

Applied product ready for use

Application	Wait Time
1st Coat	1-2 hours
2nd Coat	3-4 hours
3rd or Additional Coats	3-4 hours
Foot traffic	3 hours
Final Cure - Moisture/Rain protection	24 hours

Wait times are measured at 23°C and 50% relative humidity. Allow longer in cool or cold temperatures.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS OF USE

- Test product in an inconspicuous area first.
- Do not dilute, apply neat to surfaces.
- Not suitable for dense surfaces with porosity less than 5%.
- Protect from rain and moisture for 24 hours.

IMPORTANT CONSIDERATIONS

Keep Sikagard®-220 Invisible Sealer away from naked flames and ignition sources. Refer to the safety data sheet for additional information.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

APPLICATION INSTRUCTIONS

EQUIPMENT

Sikagard®-220 Invisible Sealer can be applied to surfaces with the following applicators.

- Paint brush
- Lambswool applicator
- Medium nap paint roller
- Low pressure sprayer
- 500ml Spray bottle

SUBSTRATE PREPARATION

- Surfaces must be clean and dry prior to application.
- Remove mould or green growths where applicable.
- Areas that have been deep cleaned with water and rinsed with pressure washing shall be allowed to dry for 24 hours prior to application.

MIXING

- Lightly shake the container prior to application.

APPLICATION METHOD / TOOLS

- Ensure surfaces being treated are clean and dry.
- Apply to the Sikagard®-220 Invisible Sealer to the surface to saturation level.
- Repeat process with applicable wait times between coats
- Allow to dry and protect from rain or water ingress for 24 hours.

CLEANING OF EQUIPMENT

- Tools and equipment can be cleaned with water prior to drying.

MAINTENANCE INSTRUCTIONS

CLEANING

- Avoid using harsh acidic chemical in cleaning regimes.
- For best results use a pH neutral cleaner such as Davco Tile & Grout Cleaner.

MAINTENANCE

- As the surface wears monitor the surface porosity for previously treated areas. As the surface begins to accept more penetration of water or staining this is a sign to clean and reapply the Sikagard®-220 Invisible Sealer.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Australia Pty Limited

ABN 12 001 342 329

aus.sika.com

Tel: 1300 22 33 48

Product Data Sheet

Sikagard®-220 Invisible Sealer

October 2026, Version 01.01

021890100000266458

Sikagard-220InvisibleSealer-en-AU-(10-2026)-1-1.pdf

