

SAFETY DATA SHEET

SikaBond® SprayFix



Version
7.0

Revision Date:
31.03.2025

SDS Number:
000000620255

Date of last issue: 25.03.2025
Date of first issue: 09.05.2018

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SikaBond® SprayFix

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.
55 Elizabeth Street
Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45

Emergency telephone number : +61 1800 033 111

Telefax : +61 2 9725 33 30

Recommended use of the chemical and restrictions on use

Product use : Sealant/adhesive

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Aerosols : Category 1
Skin corrosion/irritation : Category 2
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)
Short-term (acute) aquatic hazard : Category 2
Long-term (chronic) aquatic hazard : Category 2

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

SikaBond® SprayFix



Version
7.0

Revision Date:
31.03.2025

SDS Number:
000000620255

Date of last issue: 25.03.2025
Date of first issue: 09.05.2018

Precautionary statements

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing mist.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	>= 20 -< 25
petroleum gases, liquefied	68476-85-7	>= 10 -< 30
cyclohexane	110-82-7	>= 10 -< 20
dimethyl ether	115-10-6	>= 10 -< 30
ethanol	64-17-5	>= 10 -< 30
acetone	67-64-1	< 10

SAFETY DATA SHEET

SikaBond® SprayFix



Version
7.0

Revision Date:
31.03.2025

SDS Number:
000000620255

Date of last issue: 25.03.2025
Date of first issue: 09.05.2018

SECTION 4. FIRST AID MEASURES

- | | | |
|---|---|---|
| General advice | : | Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance. |
| If inhaled | : | Move to fresh air. |
| In case of skin contact | : | Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician. |
| In case of eye contact | : | Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : | Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention. |
| Most important symptoms and effects, both acute and delayed | : | irritant effects
Dermatitis
Loss of balance
Vertigo
See Section 11 for more detailed information on health effects and symptoms.
Causes skin irritation.
May cause drowsiness or dizziness. |
| Notes to physician | : | Treat symptomatically. |

SECTION 5. FIREFIGHTING MEASURES

- | | | |
|---------------------------------------|---|--|
| Suitable extinguishing media | : | Water spray jet
Dry powder
Foam
Carbon dioxide (CO ₂) |
| Unsuitable extinguishing media | : | High volume water jet |
| Specific hazards during fire-fighting | : | Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : | No hazardous combustion products are known |
| Specific extinguishing methods | : | Use water spray to cool unopened containers.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must |

SAFETY DATA SHEET

SikaBond® SprayFix



Version
7.0

Revision Date:
31.03.2025

SDS Number:
000000620255

Date of last issue: 25.03.2025
Date of first issue: 09.05.2018

be disposed of in accordance with local regulations.

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.
for firefighters

Hazchem Code : 2YE

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Use explosion-proof equipment.
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Do not spray on a naked flame or any incandescent material.
Take precautionary measures against electrostatic discharges.

Advice on safe handling : Do not breathe vapours or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Follow standard hygiene measures when handling chemical products

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
Store in original container.
Keep in a well-ventilated place.

SAFETY DATA SHEET

SikaBond® SprayFix



Version
7.0

Revision Date:
31.03.2025

SDS Number:
000000620255

Date of last issue: 25.03.2025
Date of first issue: 09.05.2018

Observe label precautions.
Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	TWA	900 mg/m ³	AU OEL
petroleum gases, liquefied	68476-85-7	TWA	1,000 ppm 1,800 mg/m ³	AU OEL
Further information: Category 1B (Carc. 1B) Presumed to have carcinogenic potential for humans				
cyclohexane	110-82-7	TWA	100 ppm 350 mg/m ³	AU OEL
		STEL	300 ppm 1,050 mg/m ³	AU OEL
dimethyl ether	115-10-6	STEL	500 ppm 950 mg/m ³	AU OEL
		TWA	400 ppm 760 mg/m ³	AU OEL
ethanol	64-17-5	TWA	1,000 ppm 1,880 mg/m ³	AU OEL
acetone	67-64-1	TWA	500 ppm 1,185 mg/m ³	AU OEL
		STEL	1,000 ppm 2,375 mg/m ³	AU OEL

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
cyclohexane	110-82-7	1,2-Cyclohexanediol	Urine	End of shift at end of workweek	50 mg/g creatinine	ACGIH BEI
acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI

Appropriate engineering controls : Use adequate ventilation and/or engineering controls to prevent exposure to vapours.

Personal protective equipment

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated

SAFETY DATA SHEET

SikaBond® SprayFix



Version
7.0

Revision Date:
31.03.2025

SDS Number:
000000620255

Date of last issue: 25.03.2025
Date of first issue: 09.05.2018

exposure levels, the hazards of the product and the safe working limits of the selected respirator.

- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Follow AS/NZS 1337.1
- Eye protection : Safety glasses
- Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working clothing, long trousers)
Follow AS 2210:3
Protective clothing needs to be made of cotton.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Aerosol containing a liquefied gas
- Colour : No data available
- Odour : solvent-like
- Odour Threshold : No data available
- pH : No data available
- Melting point/ range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : -41 °C (-42 °F)
(Method: closed cup)
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit / Upper flammability limit : 7.4 %(V)
- Lower explosion limit / Lower flammability limit : 1.1 %(V)
- Vapour pressure : 5100 hPa
- Relative vapour density : No data available
- Density : ca. 0.709 g/cm³ (ca. 20 °C (68 °F))
- Solubility(ies)

SAFETY DATA SHEET

SikaBond® SprayFix



Version 7.0	Revision Date: 31.03.2025	SDS Number: 000000620255	Date of last issue: 25.03.2025 Date of first issue: 09.05.2018
----------------	------------------------------	-----------------------------	---

Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 7 mm ² /s (40 °C (104 °F))
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds	:	Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 72% w/w

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	see section 7.
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

acetone:

Acute oral toxicity	:	LD50 Oral (Rat): 5,800 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 76 mg/l Exposure time: 4 h

SAFETY DATA SHEET

SikaBond® SprayFix



Version
7.0

Revision Date:
31.03.2025

SDS Number:
000000620255

Date of last issue: 25.03.2025
Date of first issue: 09.05.2018

Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): 20,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Chronic toxicity

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

acetone:

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 530 mg/l
Exposure time: 96 h

Persistence and degradability

No data available

SAFETY DATA SHEET

SikaBond® SprayFix



Version
7.0

Revision Date:
31.03.2025

SDS Number:
000000620255

Date of last issue: 25.03.2025
Date of first issue: 09.05.2018

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Send to a licensed waste management company.

The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.

Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

SAFETY DATA SHEET

SikaBond® SprayFix



Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2025
7.0	31.03.2025	000000620255	Date of first issue: 09.05.2018

Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1
Hazchem Code	: 2YE
Environmentally hazardous	: no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Therapeutic Goods (Poisons Standard) Instrument	: No poison schedule number allocated (Please use the original publication to check for specific uses, specific conditions or threshold limits that might apply for this chemical)
International Chemical Weapons Convention (CWC)	: Not applicable
Schedules of Toxic Chemicals and Precursors	
Prohibition/Licensing Requirements	: There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.

The components of this product are reported in the following inventories:

AIIC	: Listed introduction
AICS	: On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date	: 31.03.2025
Date of last issue	: 25.03.2025
Date format	: dd.mm.yyyy

Full text of other abbreviations

ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
AU OEL	: Australia. Workplace Exposure Standards for Airborne Con-

SAFETY DATA SHEET

SikaBond® SprayFix



Version
7.0

Revision Date:
31.03.2025

SDS Number:
000000620255

Date of last issue: 25.03.2025
Date of first issue: 09.05.2018

taminants.

AU OEL / TWA	: Exposure standard - time weighted average
AU OEL / STEL	: Exposure standard - short term exposure limit
ADG	: Australian Dangerous Goods Code.
ADR	: European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	: Chemical Abstracts Service
DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Globally Harmonized System
IATA	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

AU / EN