

PRODUCT DATA SHEET

Sika® Super Filler

A MULTI PURPOSE CRACK AND REPAIR FILLER FOR USE INTERNALLY & EXTERNALLY.

DESCRIPTION

Sika® Super Filler is a water based acrylic putty with reinforcement fibres designed for use by contractors and D.I.Y.

Sika® Super Filler can be used for both internal and external applications on porous substrates.

USES

Sika® Super Filler is suitable for;
for bridging cracks and small repairs on porous surfaces.

for use both indoors and outdoors, for filling on concrete, mortar, plaster, and paint.

CHARACTERISTICS / ADVANTAGES

- Pre-mixed, no mixing required - ready to use
- No wastage
- Easy to apply
- No odour
- Suitable for sanding after 24 hours
- Reinforced for additional strength and reduced shrinkage

PRODUCT INFORMATION

Composition	Acrylic dispersion and fibreglass
Packaging	1 kg Tub
Shelf life	12 Months from date of manufacture
Storage conditions	Store in dry cool conditions in original packaging. Protect from frost and direct sunlight.
Appearance and colour	White paste
Density	1.64g/cm ³
Tensile adhesion strength	1.8 N/mm ² after 7 days, +23°C, 50% RH

APPLICATION INFORMATION

Mixing ratio	Sika® Super Filler is supplied ready to use - no mixing required.
Consumption	Dependant on the surface profile a 1mm layer of Sika® Super Filler can cover 1m ² (as a guide).
Layer thickness	maximum 4mm thickness
Ambient air temperature	+5°C Min / +35°C Max

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER INFORMATION

- Do not use to fill plastic or metals.
- Do not apply when rain is imminent (external use).
- Do not apply in temperatures (ambient and surface) below 5°C.
- If using externally over-painting is essential.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

Surfaces must be clean, dry and dust free prior to application.
Contaminates such as oil, grease, old paint that is flaky or bubbling must be removed prior to application.

APPLICATION

Sika® Super Filler can be applied with a spatula or scaper in thickness of 1-4mm. When filling holes or larger cracks, it must be applied in multiple layers, allowing each layer to dry prior to next application.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Australia Pty Limited

ABN 12 001 342 329

aus.sika.com

Tel: 1300 22 33 48