Sikafloor® PurCem® Pigment Paste



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.01.2022

 3.0
 29.08.2025
 000000611986
 Date of first issue: 06.03.2018

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikafloor® PurCem® Pigment Paste

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street

Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45

Emergency telephone number: +61 1800 033 111

Telefax : +61 2 9725 33 30

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Long-term (chronic) aquatic

hazard

Category 3

GHS label elements

Hazard pictograms : None Signal word : None

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention:

P273 Avoid release to the environment.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
oxydipropyl dibenzoate	27138-31-4	>= 10 -< 25
2,2'-(ethylenedioxy)diethanol	112-27-6	0 -< 10
White mineral oil (petroleum), light	92062-35-6	0 -< 10

Sikafloor® PurCem® Pigment Paste



Version Revision Date: SDS Number: Date of last issue: 26.01.2022 000000611986 Date of first issue: 06.03.2018 29.08.2025 3.0

Hydrocarbons, C9, aromatics 64742-95-6 >= 2.5 -< 10

SECTION 4. FIRST AID MEASURES

General advice No hazards which require special first aid measures.

If inhaled Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact Take off contaminated clothing and shoes immediately.

> Wash off with soap and plenty of water. If symptoms persist, call a physician.

Flush eyes with water as a precaution. In case of eye contact

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms

and effects, both acute and

delayed

No known significant effects or hazards.

See Section 11 for more detailed information on health effects

and symptoms.

Notes to physician Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

ucts

Hazardous combustion prod- : No hazardous combustion products are known

Specific extinguishing meth-

Standard procedure for chemical fires.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

tive equipment and emer-

gency procedures

Personal precautions, protec- : For personal protection see section 8.

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Sikafloor® PurCem® Pigment Paste



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.01.2022

 3.0
 29.08.2025
 000000611986
 Date of first issue: 06.03.2018

Methods and materials for containment and cleaning up

Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Do not get in eyes, on skin, or on clothing.

For personal protection see section 8.

Follow standard hygiene measures when handling chemical

products

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday. Keep container tightly closed in a dry and well-ventilated

Conditions for safe storage : Ke

place.

Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2,2'-(ethylenedioxy)diethanol	112-27-6	TWA (Inhal- able fraction and vapor)	10 mg/m3	ACGIH

Appropriate engineering

controls

Use adequate ventilation and/or engineering controls to pre-

vent exposure to vapours.

Personal protective equipment

Respiratory protection : No special measures required.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Follow AS/NZS 1337.1

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Eye protection : Safety glasses

Sikafloor® PurCem® Pigment Paste



Date of last issue: 26.01.2022 Version Revision Date: SDS Number: 000000611986 Date of first issue: 06.03.2018 29.08.2025 3.0

Skin and body protection Protective clothing (e.g. safety shoes, long-sleeved working

clothing, long trousers)

Follow AS 2210:3

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance paste

Colour various

Odour characteristic

Odour Threshold No data available

Not applicable pΗ

Melting point/ range / Freez-

ing point

No data available

Boiling point/boiling range No data available

> 93.3 °C (> 199.9 °F) Flash point

(Method: closed cup)

Evaporation rate No data available

Flammability (solid, gas) No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

0.01 hPa Vapour pressure

Relative vapour density No data available

Density 1.45 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility No data available

Solubility in other solvents No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature No data available

Decomposition temperature No data available

Viscosity

Viscosity, dynamic No data available

Sikafloor® PurCem® Pigment Paste



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.01.2022

 3.0
 29.08.2025
 000000611986
 Date of first issue: 06.03.2018

Viscosity, kinematic : $> 7 \text{ mm2/s} (40 ^{\circ}\text{C} (104 ^{\circ}\text{F}))$

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and

livestock rearing emissions (integrated pollution prevention

and control)

Volatile organic compounds (VOC) content: 3.1% w/w

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

No hazards to be specially mentioned.

Conditions to avoid : No data available

Incompatible materials : see section 7.

Hazardous decomposition

products

No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

oxydipropyl dibenzoate:

Acute oral toxicity : LD50 Oral (Rat): 3,914 mg/kg

Hydrocarbons, C9, aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

Skin corrosion/irritation

Not classified due to lack of data.

Components:

Hydrocarbons, C9, aromatics:

Assessment : Repeated exposure may cause skin dryness or cracking.

Sikafloor® PurCem® Pigment Paste



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.01.2022

 3.0
 29.08.2025
 000000611986
 Date of first issue: 06.03.2018

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Chronic toxicity

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

oxydipropyl dibenzoate:

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 19.3 mg/l

mg/l

aquatic invertebrates (Chron- Exposure time: 48 h

ic toxicity)

Hydrocarbons, C9, aromatics:

Toxicity to algae/aquatic : (Pseudokirchneriella subcapitata (green algae)): 2.6 - 2.9

plants

Exposure time: 72 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Sikafloor® PurCem® Pigment Paste



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.01.2022

 3.0
 29.08.2025
 000000611986
 Date of first issue: 06.03.2018

Other adverse effects

Product:

Additional ecological infor-

mation

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Send to a licensed waste management company.

The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo : Not applicable

aircraft)

Packing instruction (passen- : No

Not applicable

ger aircraft)

IMDG-Code

Not regulated as a dangerous good

UN number Not applicable Proper shipping name Not applicable Class Not applicable Subsidiary risk Not applicable Not applicable Packing group Labels Not applicable Not applicable EmS Code Marine pollutant Not applicable

Sikafloor® PurCem® Pigment Paste



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.01.2022

 3.0
 29.08.2025
 000000611986
 Date of first issue: 06.03.2018

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

Not regulated as a dangerous good

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Hazchem Code : Not applicable

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Therapeutic Goods (Poisons : Standard) Instrument

No poison schedule number allocated (Please use the original publication to check for specific uses, specific conditions or

threshold limits that might apply for this chemical)

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements

: Not applicable

 There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions.

The components of this product are reported in the following inventories:

AIIC : Listed introduction

AICS : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date : 29.08.2025 Date of last issue : 26.01.2022 Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIH / TWA : 8-hour, time-weighted average ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Sikafloor® PurCem® Pigment Paste



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.01.2022

 3.0
 29.08.2025
 000000611986
 Date of first issue: 06.03.2018

Dangerous Goods by Road
CAS : Chemical Abstracts Service

DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN