

PRODUCT DATA SHEET

SikaRoof® VersiJack® Turning Tool

TURNING TOOL FOR HEIGHT-ADJUSTABLE PEDESTAL SYSTEM

DESCRIPTION

SikaRoof® VersiJack® Turning Tool is an attachment that, when used with a power tool, attaches to the top of adjustable pedestals to easily and quickly adjust the height of the pedestal.

SikaRoof® VersiJack® Turning Tool is used in conjunction with SikaRoof® VersiJack® pedestals, and helps to screw or unscrew the pedestals to adjust their heights at a faster pace for quicker installation times.

USES

Turning tools are used with adjustable pedestals for raised flooring on podiums, balconies, roof terraces and areas with hardscape finishes.

FEATURES

- Faster height adjustment of pedestals
- Resistant to biological attack by moulds and algae
- Chemically resistant to acids, alkalis, oils and soil chemicals

PRODUCT INFORMATION

Packaging

- SikaRoof® VersiJack® C Turning Tool
- Refer to pricelist

Appearance and colour

Power tool attachment



Shelf life	No expiration date if the product is stored in accordance with the storage conditions as stated in this Product Data Sheet
Storage conditions	Product must be stored in their original packing, laid in a horizontal position, and under cool and dry conditions. The product must be protected from direct sunlight, rain, snow and ice, and any other elements
Dimensions	Ø 136 x 90 mm

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

- SikaRoof® VersiJack® Turning Tool is not resistant to permanent weathering and UV exposure. For more information, please contact Sika Sales Personnel.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Australia Pty Limited
 ABN 12 001 342 329
 aus.sika.com
 Tel: 1300 22 33 48

Product Data Sheet
 SikaRoof® VersiJack® Turning Tool
 May 2026, Version 01.01
 020945051990243570

SikaRoofVersiJackTurningTool-en-AU-(05-2026)-1-1.pdf

