Sikadur 31 Part B- Interflow



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.08.2018

 2.0
 06.07.2022
 000000613252
 Date of first issue: 18.08.2018

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikadur 31 Part B- Interflow

Product code : 000000613252

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street

Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45 Telefax : +61 2 9725 33 30 Emergency telephone num- : +61 1800 033 111

ber

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion/irritation : Sub-category 1B

Serious eye damage/eye irri-

tation

: Category 1

Skin sensitisation : Category 1

Long-term (chronic) aquatic

hazard

Category 3

GHS label elements

Hazard pictograms :

L.



Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P260 Do not breathe dust.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection/ hearing protection.

Response:

Sikadur 31 Part B- Interflow



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.08.2018

 2.0
 06.07.2022
 000000613252
 Date of first issue: 18.08.2018

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT

induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediate-

ly all contaminated clothing. Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Immediately call a

POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/ doctor.

P333 + P313 If skin irritation or rash occurs: Get medical ad-

vice/ attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Quartz (SiO2)	14808-60-7	>= 30 -< 60
Sikafloor®-94 (B)	Not Assigned	>= 10 -< 25
calcium carbonate	471-34-1	>= 10 -< 30

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

Sikadur 31 Part B- Interflow



Date of last issue: 18.08.2018 Version Revision Date: SDS Number: 000000613252 Date of first issue: 18.08.2018 06.07.2022 2.0

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Health injuries may be delayed.

corrosive effects sensitising effects Allergic reactions **Dermatitis**

See Section 11 for more detailed information on health effects

and symptoms.

May cause an allergic skin reaction. Causes serious eye damage.

Causes severe burns.

Notes to physician Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Hazardous combustion prod- :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

Standard procedure for chemical fires.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Hazchem Code 2X

SECTION 6. ACCIDENTAL RELEASE MEASURES

tive equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment. Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for Pick up and arrange disposal without creating dust.

Sikadur 31 Part B- Interflow



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.08.2018

 2.0
 06.07.2022
 000000613252
 Date of first issue: 18.08.2018

containment and cleaning up Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.

Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parame- ters / Permissible	Basis	
		exposure)	concentration		
Quartz (SiO2)	14808-60-7	TWA (Res-	0.05 mg/m3	AU OEL	
		pirable dust)			
	Further information: Category 1A (Carc. 1A) Known to have car-				
	cinogenic potential for humans				
calcium carbonate	471-34-1	TWA	10 mg/m3	AU OEL	
			(Calcium car-		
			bonate)		
	Further information: This value is for inhalable dust containing no				
	asbestos and < 1% crystalline silica				

Appropriate engineering

controls

Provide appropriate exhaust ventilation at places where dust

is formed.

Sikadur 31 Part B- Interflow



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.08.2018

 2.0
 06.07.2022
 000000613252
 Date of first issue: 18.08.2018

Personal protective equipment

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Follow AS/NZS 1337.1

Eye protection : Safety glasses

Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working

clothing, long trousers) Follow AS 2210:3 Rubber aprons

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : grey

Odour : characteristic

Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

Flash point : $> 93.3 \,^{\circ}\text{C} \, (> 199.9 \,^{\circ}\text{F})$

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Sikadur 31 Part B- Interflow



Revision Date: Date of last issue: 18.08.2018 Version SDS Number: Date of first issue: 18.08.2018 06.07.2022 000000613252 2.0

: 1.9 g/cm3 (20 °C (68 °F)) Density

Solubility(ies)

No data available Water solubility

Solubility in other solvents No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature No data available

Decomposition temperature No data available

Viscosity

No data available Viscosity, dynamic

Viscosity, kinematic Not applicable

Explosive properties No data available

Oxidizing properties No data available

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 8.04% w/w

SECTION 10. STABILITY AND REACTIVITY

Reactivity No dangerous reaction known under conditions of normal use.

Chemical stability The product is chemically stable.

Possibility of hazardous reac- : Stable under recommended storage conditions.

Conditions to avoid No data available

Incompatible materials see section 7.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

Sikafloor®-94 (B):

Acute oral toxicity : Acute toxicity estimate: 1,618 mg/kg

Method: Calculation method

Acute inhalation toxicity Acute toxicity estimate: > 5 mg/l

Exposure time: 4 h

Sikadur 31 Part B- Interflow



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.08.2018

 2.0
 06.07.2022
 000000613252
 Date of first issue: 18.08.2018

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Sikadur 31 Part B- Interflow



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.08.2018

 2.0
 06.07.2022
 000000613252
 Date of first issue: 18.08.2018

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

Components:

Sikafloor®-94 (B):

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1759

Proper shipping name : Corrosive solid, n.o.s.

Class : 8 Packing group : III

Labels : Corrosive Packing instruction (cargo : 864

aircraft)

Packing instruction (passen- :

860

ger aircraft)

IMDG-Code

UN number : UN 1759

Proper shipping name : CORROSIVE SOLID, N.O.S.

Class : 8
Packing group : III
Labels : 8

8 / 10

Sikadur 31 Part B- Interflow



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.08.2018

 2.0
 06.07.2022
 000000613252
 Date of first issue: 18.08.2018

EmS Code : F-A, S-B Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number : UN 1759

Proper shipping name : CORROSIVE SOLID, N.O.S.

Class : 8
Packing group : III
Labels : 8
Hazchem Code : 2X

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : No poison schedule number allocated

Scheduling of Medicines and

Poisons

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements

: Not applicable

: There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions.

The components of this product are reported in the following inventories:

AIIC : All components are listed on the inventory, regulatory obliga-

tions/restrictions apply

SECTION 16. OTHER INFORMATION

Revision Date : 06.07.2022 Date format : dd.mm.yyyy

Full text of other abbreviations

AU OEL : Australia. Workplace Exposure Standards for Airborne Con-

taminants.

AU OEL / TWA : Exposure standard - time weighted average

ADG : Australian Dangerous Goods Code.

Sikadur 31 Part B- Interflow



Version 2.0		Revision Date: 06.07.2022		SDS Number: 000000613252	Date of last issue: 18.08.2018 Date of first issue: 18.08.2018
AD	R		:	European Agreement concerning the International Carriage of Dangerous Goods by Road	
CA	S		:	Chemical Abstracts Service	
D١	IEL		:	Derived no-effect level	
EC	50		:	Half maximal effective concentration	on
GH	lS		:	Globally Harmonized System	
IA	ГА		:	International Air Transport Associa	
	DG		:	International Maritime Code for Da	
LD	50		:	Median lethal dosis (the amount of once, which causes the death of 50 test animals)	
LC	50		:	Median lethal concentration (conce air that kills 50% of the test animals period)	
MA	ARPOL		:	International Convention for the Pr Ships, 1973 as modified by the Pro	
OE	EL		:	Occupational Exposure Limit	
PB	T		:	Persistent, bioaccumulative and to	xic
PN	IEC		:	Predicted no effect concentration	
RE	ACH		:	Regulation (EC) No 1907/2006 of t and of the Council of 18 December istration, Evaluation, Authorisation cals (REACH), establishing a Euro	2006 concerning the Reg- and Restriction of Chemi-
SV	'HC		:	Substances of Very High Concern	
vP	vB		:	Very persistent and very bioaccum	ulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN