Sikalastic®-488 SL



Revision Date: SDS Number: Date of last issue: 12.05.2023 Version 17.05.2023 000000612798 Date of first issue: 12.05.2023 2.0

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikalastic®-488 SL

Manufacturer or supplier's details

Sika Australia Pty. Ltd. Company

55 Elizabeth Street

Wetherill Park, NSW 2164

: +61 2 9725 11 45 Telephone

Emergency telephone number: +61 1800 033 111

: +61 2 9725 33 30 Telefax

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Category 4 Flammable liquids

Acute toxicity (Inhalation) Category 4

Reproductive toxicity : Category 2

single exposure

Specific target organ toxicity - : Category 3 (Respiratory system, Central nervous system)

Aspiration hazard Category 1

Long-term (chronic) aquatic

hazard

Category 3

GHS label elements

Hazard pictograms





Signal word Danger

H227 Combustible liquid. Hazard statements

H304 May be fatal if swallowed and enters airways.

H332 Harmful if inhaled.

H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child. H412 Harmful to aquatic life with long lasting effects.

Sikalastic®-488 SL



SDS Number: Date of last issue: 12.05.2023 Version **Revision Date:** 17.05.2023 000000612798 Date of first issue: 12.05.2023 2.0

Precautionary statements Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing mist or vapours.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/ doctor.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture Mixture

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|---|------------|-----------------------|
| Hydrocarbons, C9, aromatics | 64742-95-6 | >= 20 -< 25 |
| 1-isopropyl-2,2-dimethyltrimethylene diisobu- | 6846-50-0 | >= 3 -< 10 |
| tyrate | | |
| m-tolylidene diisocyanate | 26471-62-5 | >= 0.25 -< 1 |

SECTION 4. FIRST AID MEASURES

Sikalastic®-488 SL



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12.05.2023

 2.0
 17.05.2023
 000000612798
 Date of first issue: 12.05.2023

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Risk of serious damage to the lungs (by aspiration).

irritant effects

Aspiration may cause pulmonary oedema and pneumonitis.

Cough

Respiratory disorder

Headache Loss of balance

Vertigo

See Section 11 for more detailed information on health effects

and symptoms.

May be fatal if swallowed and enters airways.

Harmful if inhaled.

May cause respiratory irritation.

May cause drowsiness or dizziness.

Suspected of damaging fertility or the unborn child.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Carbon dioxide (CO2)

Unsuitable extinguishing

media

Water

Sikalastic®-488 SL



Revision Date: Date of last issue: 12.05.2023 Version SDS Number: 17.05.2023 000000612798 Date of first issue: 12.05.2023 2.0

ucts

Hazardous combustion prod- : No hazardous combustion products are known

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Deny access to unprotected persons.

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical

products

Hygiene measures Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage Store in original container.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

Sikalastic®-488 SL



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12.05.2023

 2.0
 17.05.2023
 000000612798
 Date of first issue: 12.05.2023

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of | Control parame- ters / Permissible | Basis | | |
|-----------------------------|--|------------------------|---------------------------------------|--------|--|--|
| | | exposure) | concentration | | | |
| II local con OO con of co | 0.4740.05.0 | | | ALLOFI | | |
| Hydrocarbons, C9, aromatics | 64742-95-6 | TWA | 900 mg/m3 | AU OEL | | |
| m-tolylidene diisocyanate | 26471-62-5 | TWA | 0.02 mg/m3 (NCO) | AU OEL | | |
| | | | | | | |
| | Further information: Category 2 (Carc. 2) Suspected human car- | | | | | |
| | cinogen, Sensitiser | | | | | |
| | | STEL | 0.07 mg/m3 | AU OEL | | |
| | | | (NCO) | | | |

Biological occupational exposure limits

| Components | CAS-No. | Control | Biological | Sampling | Permissible | Basis |
|------------------------|-----------|------------|------------|----------|---------------|-------|
| | | parameters | specimen | time | concentration | |
| m-tolylidene diisocya- | 26471-62- | toluene | Urine | End of | 5 μg/g creat- | ACGIH |
| nate | 5 | diamine | | shift | inine | BEI |

Appropriate engineering

controls

: Use adequate ventilation and/or engineering controls to pre-

vent exposure to vapours.

Personal protective equipment

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Follow AS/NZS 1337.1

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Eye protection : Safety glasses

Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working

clothing, long trousers) Follow AS 2210:3

Protective clothing needs to be made of cotton.

Sikalastic®-488 SL



Version 2.0

Revision Date: 17.05.2023

SDS Number: 000000612798

Date of last issue: 12.05.2023 Date of first issue: 12.05.2023

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : various

Odour : characteristic

Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

Flash point : 62 °C (144 °F)

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : 4.9996 hPa

Relative vapour density : No data available

Density : 1.32 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Sikalastic®-488 SL



Version **Revision Date:** SDS Number: Date of last issue: 12.05.2023 17.05.2023 000000612798 Date of first issue: 12.05.2023 2.0

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic No data available

Viscosity, kinematic > 7 mm2/s (40 °C (104 °F))

Explosive properties No data available

Oxidizing properties No data available

: Directive 2010/75/EU of 24 November 2010 on industrial Volatile organic compounds

> emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 20.8% w/w

SECTION 10. STABILITY AND REACTIVITY

Reactivity No dangerous reaction known under conditions of normal use.

Chemical stability The product is chemically stable.

tions

Possibility of hazardous reac- : No hazards to be specially mentioned.

Conditions to avoid No data available

Incompatible materials see section 7.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if inhaled.

Components:

Hydrocarbons, C9, aromatics:

Acute oral toxicity LD50 Oral (Rat): > 2,000 mg/kg

Acute dermal toxicity LD50 Dermal (Rabbit): > 2,000 mg/kg

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Acute oral toxicity : LD50 Oral (Rat): > 3,200 mg/kg

Acute dermal toxicity LD50 Dermal (Rat): > 5,000 mg/kg

m-tolylidene diisocyanate:

Sikalastic®-488 SL



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12.05.2023

 2.0
 17.05.2023
 000000612798
 Date of first issue: 12.05.2023

Acute inhalation toxicity : LC50 (Rat): 0.107 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Skin corrosion/irritation

Not classified based on available information.

Components:

Hydrocarbons, C9, aromatics:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT - single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Hydrocarbons, C9, aromatics:

Toxicity to algae/aquatic : (Pseud

plants

(Pseudokirchneriella subcapitata (green algae)): 2.6 - 2.9

mg/l

Exposure time: 72 h

Sikalastic®-488 SL



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12.05.2023

 2.0
 17.05.2023
 000000612798
 Date of first issue: 12.05.2023

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

: Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Send to a licensed waste management company.

The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo : Not applicable

aircraft)

Packing instruction (passen- : Not applicable

Sikalastic®-488 SL



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12.05.2023

 2.0
 17.05.2023
 000000612798
 Date of first issue: 12.05.2023

ger aircraft)

IMDG-Code

UN number Not applicable Not applicable Proper shipping name Not applicable Class Not applicable Subsidiary risk Not applicable Packing group Not applicable Labels EmS Code Not applicable Not applicable Marine pollutant

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Hazchem Code : Not applicable

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform

Scheduling of Medicines and

Poisons

: No poison schedule number allocated

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements

Not applicable

There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions.

The components of this product are reported in the following inventories:

AIIC : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date : 17.05,2023

Sikalastic®-488 SL



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12.05.2023

 2.0
 17.05.2023
 000000612798
 Date of first issue: 12.05.2023

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

AU OEL : Australia. Workplace Exposure Standards for Airborne Con-

taminants.

AU OEL / TWA : Exposure standard - time weighted average AU OEL / STEL : Exposure standard - short term exposure limit

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN