

PRODUCT DATA SHEET

Sika MaxTack®

Sika MaxTack is a one part high strength, copolymer dispersion adhesive.

DESCRIPTION

Sika MaxTack® is a 1-component, solvent-free high tack adhesive with high initial grab for bonding of building materials indoors and in sheltered outdoor areas.

USES

Sika MaxTack® is designed for the indoor and sheltered outdoor bonding of building materials such as skirting boards, wood frames, panels, terracotta tiles, anodised aluminum, hard PVC profiles, polystyrene mouldings and panels, polystyrene ceiling tiles and wood mouldings.

Sika MaxTack® adheres well to various porous materials such as concrete, mortar, fiber cement, wood and the painted substrates of decorative pieces.

CHARACTERISTICS / ADVANTAGES

- High initial tack
- Powerful grab properties (green strength)
- Fixing without tapes, nails or screws
- Good adhesion on many substrates
- Good workability
- Water-based
- Over-paintable with water based paints
- For interior use on wall and ceiling
- For sheltered outdoor use on wall (canopy, balcony)

PRODUCT INFORMATION

Composition	1-Component water-based dispersion	
Packaging	400 g cartridge, 12 cartridges per box 100 g foil pack, 24 foil packs per box	
Shelf life	Sika MaxTack® has a shelf life of 18 months from the date of production, if it is stored properly in undamaged, original, sealed packaging, and if the storage conditions are met.	
Storage conditions	Sika MaxTack® shall be stored in dry conditions, protected from direct sunlight and at temperatures between +5 °C and +25 °C.	
Colour	Off-white	
Density	1.40 kg/l approx.	(ISO 1183-1)

TECHNICAL INFORMATION

Shore A hardness	85 approx. (after 28 days)	(ISO 868)
Shear strength	3.0 N/mm ² approx., 1mm adhesive thickness	(EN 1465)

Service temperature -15 °C to +60 °C

APPLICATION INFORMATION

Sagging	Very low	(ISO 7930)
Ambient air temperature	+5 °C to +35 °C, min. 3 °C above dew point temperature	
Substrate temperature	+5 °C to +35 °C	
Curing rate	6 mm/24 hours approx. (23 °C / 50% r.h.)	(CQP 049-2)
Skimming time	30 minutes approx. (23 °C / 50% r.h.)	(CQP 019-1)

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER INFORMATION

- Safety Data Sheet
- Pre-treatment Chart Sealing and Bonding

IMPORTANT CONSIDERATIONS

- For good workability, the adhesive temperature shall be +20 °C.
- For proper curing of the adhesive, sufficient ambient humidity / moisture is necessary.
- Application during high temperature changes is not recommended (movements during the curing).
- Before bonding, check adhesion and resistance of paints and coatings by carrying out a trail.
- Trials shall be carried out to test for overpaint ability and paint compatibility. When overcoating Sika MaxTack®, compatibility of coatings must be tested individually.
- For good bonding, one of the two substrates must be porous.
- Do not use Sika MaxTack® on bituminous substrates, natural rubber, EPDM rubber or on any building materials which might bleed oils, plasticizers or solvents that could attack the sealant.
- Do not use outside on easily corroding substrates such as blank steel or iron.
- Do not use on polyethylene (PE), polypropylene (PP), polytetrafluoroethylene (PTFE / Teflon), and certain plasticized synthetic materials (pre-trials shall be carried out or contact our Technical Service Department).
- Do not use Sika MaxTack® as glass sealer, in floor joints, in sanitary joints and structural bonding.
- Do not use Sika MaxTack® for joints under water pressure or for permanent water immersion.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

For the application of Sika MaxTack® all standard construction guidelines apply.

SUBSTRATE PREPARATION

The substrate must be clean, dry, sound and homogeneous, free from oils, grease, dust and loose or friable particles. Paint, cement laitance and other poorly adhering contaminants must be removed. Sika MaxTack® adheres without primers and/or activators.

Non-porous substrates

Aluminium, anodised aluminium, stainless steel, PVC, galvanised steel, powder coated metals or glazed tiles have to be cleaned and pre-treated using Sika® Aktivator-205, wiped on with a clean towel. Before sealing, allow a flash-off time of > 15 minutes (< 6 hours). Other metals, such as copper, brass and titanium-zinc, also have to be cleaned and pre-treated using Sika® Aktivator-205, wiped on with a clean towel. After the necessary flash-off time, use a brush to apply Sika® Primer-3 N and allow a further flash-off time of > 30 minutes (< 8 hours) before sealing the joints.

Porous substrates

Wood has to be sanded, concrete and mortar have to be scrubbed and sanded to remove laitance.

Clean with an industrial vacuum.

For more detailed advice and instructions please contact our Technical Service Department.

APPLICATION METHOD / TOOLS

After the necessary substrate preparation, apply Sika MaxTack® in round shapes with a 5 mm diameter, in intervals of a few centimetres each. If necessary, use a notched trowel to distribute Sika MaxTack® evenly. Press or tap bonded parts together firmly to ensure good adhesion before a skin occurs. An incorrectly positioned element can easily be unfastened and repositioned.

tioned during the first few minutes after application. If necessary, use adhesive tapes, wedges, or props to hold the assembled elements together during the initial curing hours.

The recommended adhesive layer thickness (depending on surface evenness) is < 3 mm. For immediate fixing, the thickness of the bonding adhesive layer must be ≤ 1 mm.

Fresh, uncured adhesive remaining on the surface must be removed immediately.

Final strength will be obtained after complete curing of Sika MaxTack®.

CLEANING OF EQUIPMENT

Clean all tools and application equipment immediately after use with water. Once cured, residual material can only be removed mechanically.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Australia Pty Limited

ABN 12 001 342 329

aus.sika.com

Tel: 1300 22 33 48

Product Data Sheet

Sika MaxTack®

April 2023, Version 01.02

02051303000000012

SikaMaxTack-en-AU-(04-2023)-1-2.pdf