

# SAFETY DATA SHEET

## Sika® Primer-207



Version 1.0      Revision Date: 05.04.2022      SDS Number: 100000005704      Date of last issue: -  
Date of first issue: 05.04.2022

---

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sika® Primer-207

Product code : 100000005704

#### Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.  
55 Elizabeth Street  
Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45

Telefax : +61 2 9725 33 30

Emergency telephone number : +61 1800 033 111

#### Recommended use of the chemical and restrictions on use

Product use : Pretreatment agent, Product is not intended for consumer use

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Flammable liquids : Category 2

Serious eye damage/eye irritation : Category 2A

Skin sensitisation : Category 1

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

#### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.

# SAFETY DATA SHEET

## Sika® Primer-207



Version  
1.0

Revision Date:  
05.04.2022

SDS Number:  
100000005704

Date of last issue: -  
Date of first issue: 05.04.2022

P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P261 Avoid breathing mist or vapours.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

### Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards which do not result in classification

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
ethyl acetate	141-78-6	>= 30 -< 60
butanone	78-93-3	>= 30 -< 60
aromatic polyisocyanate	53317-61-6	>= 1 -< 10
tris(p-isocyanatophenyl) thiophosphate	4151-51-3	0 -< 10

# SAFETY DATA SHEET

## Sika® Primer-207



Version 1.0      Revision Date: 05.04.2022      SDS Number: 100000005704      Date of last issue: -  
Date of first issue: 05.04.2022

Tris(3-(trimethoxysilyl)propyl)isocyanurate	26115-70-8	0 -< 10
4,4'-methylenediphenyl diisocyanate	101-68-8	0 -< 1

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : irritant effects  
sensitising effects  
Allergic reactions  
Excessive lachrymation  
Loss of balance  
Vertigo  
See Section 11 for more detailed information on health effects and symptoms.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.
- Notes to physician : Treat symptomatically.

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : Water  
High volume water jet
- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.

# SAFETY DATA SHEET

## Sika® Primer-207



Version 1.0	Revision Date: 05.04.2022	SDS Number: 100000005704	Date of last issue: - Date of first issue: 05.04.2022
----------------	------------------------------	-----------------------------	--

---

- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Use water spray to cool unopened containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Hazchem Code : •3YE

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.
- Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

---

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Use explosion-proof equipment.  
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Follow standard hygiene measures when handling chemical

# SAFETY DATA SHEET

## Sika® Primer-207



Version  
1.0

Revision Date:  
05.04.2022

SDS Number:  
100000005704

Date of last issue: -  
Date of first issue: 05.04.2022

products

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.  
Store in cool place.  
Keep in a well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Store in accordance with local regulations.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethyl acetate	141-78-6	STEL	400 ppm 1,440 mg/m <sup>3</sup>	AU OEL
		TWA	200 ppm 720 mg/m <sup>3</sup>	AU OEL
butanone	78-93-3	STEL	300 ppm 890 mg/m <sup>3</sup>	AU OEL
		TWA	150 ppm 445 mg/m <sup>3</sup>	AU OEL
tris(p-isocyanatophenyl) thiophosphate	4151-51-3	TWA	0.02 mg/m <sup>3</sup> (NCO)	AU OEL
		Further information: Sensitiser		
		STEL	0.07 mg/m <sup>3</sup> (NCO)	AU OEL
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0.02 mg/m <sup>3</sup> (NCO)	AU OEL
		Further information: Category 2 (Carc. 2) Suspected human carcinogen, Sensitiser		
		STEL	0.07 mg/m <sup>3</sup> (NCO)	AU OEL

#### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
methanol	67-56-1	TWA	200 ppm 262 mg/m <sup>3</sup>	AU OEL
		Further information: Skin absorption		
		STEL	250 ppm	AU OEL

# SAFETY DATA SHEET

## Sika® Primer-207



Version  
1.0

Revision Date:  
05.04.2022

SDS Number:  
100000005704

Date of last issue: -  
Date of first issue: 05.04.2022

328 mg/m3

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
butanone	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI

**Appropriate engineering controls** : Use adequate ventilation and/or engineering controls to prevent exposure to vapours.  
Avoid vapor formation.  
Provide appropriate exhaust ventilation at places where vapor is formed.

### Personal protective equipment

**Respiratory protection** : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  
Follow AS/NZS 1337.1  
Recommended: Butyl rubber/nitrile rubber gloves.  
Contaminated gloves should be removed.

**Eye protection** : Safety glasses

**Skin and body protection** : Protective clothing (e.g. safety shoes, long-sleeved working clothing, long trousers)  
Follow AS 2210:3  
Protective clothing needs to be made of cotton.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** : liquid

**Colour** : black

**Odour** : solvent-like

**Odour Threshold** : No data available

**pH** : Not applicable substance/mixture is non-soluble (in water)

# SAFETY DATA SHEET

## Sika® Primer-207



Version 1.0      Revision Date: 05.04.2022      SDS Number: 100000005704      Date of last issue: -  
Date of first issue: 05.04.2022

---

Melting point/range / Freezing point : No data available  
Boiling point/boiling range : > 70 °C (158 °F)  
Flash point : -4 °C (25 °F)  
(Method: closed cup)  
Evaporation rate : No data available  
Flammability (solid, gas) : No data available  
Upper explosion limit / Upper flammability limit : 11.5 %(V)  
Lower explosion limit / Lower flammability limit : 1.8 %(V)  
Vapour pressure : 99.9915 hPa  
Relative vapour density : No data available  
Density : ca. 0.97 g/cm<sup>3</sup> (20 °C (68 °F))  
Solubility(ies)  
    Water solubility : insoluble  
    Solubility in other solvents : No data available  
Partition coefficient: n-octanol/water : No data available  
Auto-ignition temperature : 427 °C  
Decomposition temperature : No data available  
Viscosity  
    Viscosity, dynamic : ca. 15 mPa.s (20 °C (68 °F))  
    Viscosity, kinematic : < 20.5 mm<sup>2</sup>/s (40 °C (104 °F))  
Explosive properties : No data available  
Oxidizing properties : No data available  
Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 68.05% w/w

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.  
Chemical stability : The product is chemically stable.

# SAFETY DATA SHEET

## Sika® Primer-207



Version 1.0      Revision Date: 05.04.2022      SDS Number: 100000005704      Date of last issue: -  
Date of first issue: 05.04.2022

---

Possibility of hazardous reactions : Stable under recommended storage conditions.  
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.  
Avoid moisture.

Incompatible materials : Strong acids and oxidizing agents

Hazardous decomposition products : methanol

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **ethyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): ca. 1,600 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

##### **butanone:**

Acute oral toxicity : LD50 Oral (Rat): 3,300 mg/kg

Acute inhalation toxicity : LC50 (Rat): 36 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

##### **aromatic polyisocyanate:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

##### **tris(p-isocyanatophenyl) thiophosphate:**

Acute oral toxicity : LD50 Oral (Rat): > 675 mg/kg  
Remarks: see user defined free text

Acute inhalation toxicity : LC50 (Rat): 5.721 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

##### **Tris(3-(trimethoxysilyl)propyl)isocyanurate:**

Acute oral toxicity : LD50 Oral (Rat): 1,713 mg/kg

##### **4,4'-methylenediphenyl diisocyanate:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg



# SAFETY DATA SHEET

## Sika® Primer-207



Version  
1.0

Revision Date:  
05.04.2022

SDS Number:  
100000005704

Date of last issue: -  
Date of first issue: 05.04.2022

---

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1.5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgement

### **Skin corrosion/irritation**

Not classified based on available information.

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

May cause an allergic skin reaction.

#### **Respiratory sensitisation**

Not classified based on available information.

### **Chronic toxicity**

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT - single exposure**

May cause drowsiness or dizziness.

#### **STOT - repeated exposure**

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

### **Further information**

#### **Product:**

Remarks : Toxicology data for the components  
Information given is based on data on the components and  
the toxicology of similar products.  
Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

## Sika® Primer-207



Version  
1.0

Revision Date:  
05.04.2022

SDS Number:  
100000005704

Date of last issue: -  
Date of first issue: 05.04.2022

---

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

No data available

#### Persistence and degradability

No data available

#### Bioaccumulative potential

No data available

#### Mobility in soil

No data available

#### Other adverse effects

#### Product:

Additional ecological information : There is no data available for this product.

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

UN/ID No. : UN 1866  
Proper shipping name : Resin solution  
Class : 3  
Packing group : II  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353

##### IMDG-Code

# SAFETY DATA SHEET

## Sika® Primer-207



Version 1.0      Revision Date: 05.04.2022      SDS Number: 100000005704      Date of last issue: -  
Date of first issue: 05.04.2022

---

UN number : UN 1866  
Proper shipping name : RESIN SOLUTION  
Class : 3  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

#### ADG

UN number : UN 1866  
Proper shipping name : RESIN SOLUTION  
Class : 3  
Packing group : II  
Labels : 3  
Hazchem Code : •3YE

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet.

Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## SECTION 15. REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : Schedule 5  
Scheduling of Medicines and  
Poisons

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors  
Prohibition/Licensing Requirements : There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.

### The components of this product are reported in the following inventories:

AllC : All components are listed on the inventory, regulatory obligations/restrictions apply

---

## SECTION 16. OTHER INFORMATION

Revision Date : 05.04.2022  
Date format : dd.mm.yyyy

---

# SAFETY DATA SHEET

## Sika® Primer-207



Version 1.0      Revision Date: 05.04.2022      SDS Number: 100000005704      Date of last issue: -  
Date of first issue: 05.04.2022

---

### Full text of other abbreviations

ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
AU OEL	:	Australia. Workplace Exposure Standards for Airborne Contaminants.
AU OEL / TWA	:	Exposure standard - time weighted average
AU OEL / STEL	:	Exposure standard - short term exposure limit
ADG	:	Australian Dangerous Goods Code.
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: [aus.sika.com](http://aus.sika.com)

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

AU / EN