Sika[®] Aktivator-100



Version 2.0	Revision Date: 31.10.2024		SDS Number: 000000033123	Date of last issue: 05.04.2022 Date of first issue: 05.04.2022
SECTION	1. PRODUCT AND COM	МРА	NY IDENTIFICATION	
Produ	uct name	:	Sika [®] Aktivator-100	
Manu	ufacturer or supplier's o	deta	ils	
Com	pany	:	Sika Australia Pty. Ltd. 55 Elizabeth Street Wetherill Park, NSW 2164	
Telep	bhone	:	+61 2 9725 11 45	
Emer	rgency telephone numbe	r:	+61 1800 033 111	
Telef	ax	:	+61 2 9725 33 30	
Reco	ommended use of the cl	hem	ical and restrictions on use	9
Produ	uct use	:	Pretreatment agent	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification		
Flammable liquids	:	Category 2
Skin corrosion/irritation	:	Category 2
Serious eye damage/eye irri- tation	:	Category 1
Skin sensitisation	:	Category 1
Specific target organ toxicity - single exposure	:	Category 3 (Central nervous system)
Aspiration hazard	:	Category 1
Long-term (chronic) aquatic hazard	:	Category 2
GHS label elements		
Hazard pictograms	:	
Signal word	:	Danger

Sika[®] Aktivator-100



Version 2.0	Revision Date: 31.10.2024	SDS Number: 000000033123	Date of last issue: 05.04.2022 Date of first issue: 05.04.2022
Hazaı	rd statements	 H225 Highly flammable lique H304 May be fatal if swallow H315 Causes skin irritation. H317 May cause an allergide H318 Causes serious eye of H336 May cause drowsines H411 Toxic to aquatic life w 	wed and enters airways. c skin reaction. damage. ss or dizziness.
Preca	autionary statements	 and other ignition sources. P233 Keep container tightly P240 Ground and bond cor P241 Use explosion-proof ement. P242 Use non-sparking too P243 Take action to preven P261 Avoid breathing mister P264 Wash skin thoroughly P271 Use only outdoors or P272 Contaminated work content 	 v closed. ntainer and receiving equipment. electrical/ ventilating/ lighting equipols. nt static discharges. or vapours. v after handling. in a well-ventilated area. lothing should not be allowed out of
		P273 Avoid release to the e P280 Wear protective glove tion/ face protection/ hearin Response:	es/ protective clothing/ eye protec-
		 P301 + P310 IF SWALLOW CENTER/ doctor. P303 + P361 + P353 IF ON Iy all contaminated clothing P304 + P340 + P312 IF INH and keep comfortable for bit doctor if you feel unwell. P305 + P351 + P338 + P31 water for several minutes. F and easy to do. Continue rit CENTER/ doctor. P331 Do NOT induce vomit P333 + P313 If skin irritation vice/ attention. P362 + P364 Take off conta reuse. P370 + P378 In case of fire alcohol-resistant foam to ex P391 Collect spillage. 	HALED: Remove person to fresh air reathing. Call a POISON CENTER/ 10 IF IN EYES: Rinse cautiously with Remove contact lenses, if present nsing. Immediately call a POISON ting. n or rash occurs: Get medical ad- aminated clothing and wash it before e: Use dry sand, dry chemical or
		tightly closed.	II-ventilated place. Keep container II-ventilated place. Keep cool.

Sika[®] Aktivator-100



Version	Revision Date:	SDS Number:	Date of last issue: 05.04.2022
2.0	31.10.2024	00000033123	Date of first issue: 05.04.2022

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Hydrocarbons, C7, n-alkanes, isoalkanes, cy-	64742-49-0	>= 60 -<= 100
clics		
ethanol	64-17-5	< 10
N-(3-(trimethoxysilyl)propyl)ethylenediamine	1760-24-3	>= 1 -< 3
tris(dodecylbenzenesulphonato-O)(propan-2-	61417-55-8	>= 1 -< 3
olato)titanium		

SECTION 4. FIRST AID MEASURES

General advice :	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled :	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact :	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact :	Small amounts splashed into eyes can cause irreversible tis- sue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed :	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.

Sika[®] Aktivator-100



Version 2.0	Revision Date: 31.10.2024	SDS Number: 000000033123	Date of last issue: 05.04.2022 Date of first issue: 05.04.2022
		Take victim immediately to	hospital.
	mportant symptoms ffects, both acute and ed	Allergic reactions Excessive lachrymation Dermatitis Loss of balance Vertigo	nonary oedema and pneumonitis. etailed information on health effects and enters airways. reaction. ge.
Notes	to physician	: Treat symptomatically.	

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	Water High volume water jet
Specific hazards during fire- fighting	:	Do not use a solid water stream as it may scatter and spread fire. Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
Specific extinguishing meth- ods	:	Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.

Sika[®] Aktivator-100



2.0	Revision Date: 31.10.2024		SDS Number: 000000033123	Date of last issue: 05.04.2022 Date of first issue: 05.04.2022
Hazchen	n Code	:	•3YE	
SECTION 6.	ACCIDENTAL RELE	ASI	E MEASURES	
tive equi	l precautions, protec- pment and emer- ocedures	:	Use personal protective equ Remove all sources of ignition Deny access to unprotected	on.
Environn	nental precautions	:	Prevent product from enterin If the product contaminates respective authorities.	ng drains. rivers and lakes or drains inform
	and materials for nent and cleaning up	:	sorbent material, (e.g. sand,	ollect with non-combustible ab- , earth, diatomaceous earth, ver- ner for disposal according to local ection 13).
SECTION 7.	HANDLING AND ST	DR/	AGE	
	n protection against explosion	:	smoking.	ient. ss/ open flames/ hot surfaces. No es against electrostatic discharg-
Advice o	n safe handling	:	section 8). Do not get in eyes, on skin, For personal protection see Persons with a history of ski ma, allergies, chronic or rec not be employed in any prod used. Smoking, eating and drinkin plication area. Take precautionary measure Open drum carefully as cont Take necessary action to av (which might cause ignition of	occupational exposure limits (see or on clothing. section 8. in sensitisation problems or asth- urrent respiratory disease should cess in which this mixture is being g should be prohibited in the ap- es against static discharge. tent may be under pressure. void static electricity discharge

Sika[®] Aktivator-100



Version 2.0	Revision Date: 31.10.2024	SDS Number: 000000033123	Date of last issue: 05.04.2022 Date of first issue: 05.04.2022
		When using do not smoke. Wash hands before breaks	and at the end of workday.
Condi	tions for safe storage	: Store in original container. Store in cool place. Keep in a well-ventilated pla Containers which are opene kept upright to prevent leaks Observe label precautions. Store in accordance with loo	ed must be carefully resealed and age.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	TWA	900 mg/m3	AU OEL
ethanol	64-17-5	TWA	1,000 ppm 1,880 mg/m3	AU OEL

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis	
methanol	67-56-1	TWA	200 ppm 262 mg/m3	AU OEL	
	Further informa	ation: Skin abso	rption		
		STEL	250 ppm 328 mg/m3	AU OEL	
Appropriate engineering controls: Use adequate ventilation and/or engineering controls to pre- vent exposure to vapours. Avoid vapor formation. Provide appropriate exhaust ventilation at places where va- por is formed.					
Personal protective equipmen	t				
Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. organic vapor filter (Type A)					
Hand protection :	approved star	ndard should be	s gloves complying w worn at all times whe sessment indicates th	en handling	
	6 /	12			

Sika[®] Aktivator-100



Version 2.0	Revision Date: 31.10.2024		SDS Number: 000000033123	Date of last issue: 05.04.2022 Date of first issue: 05.04.2022
			Follow AS/NZS 1337.1 Recommended: Butyl rubber/ Contaminated gloves should l	
Eye protection		:	Safety glasses	
Skin and body protection		:	 Protective clothing (e.g. safety shoes, long-sleeved working clothing, long trousers) Follow AS 2210:3 Protective clothing needs to be made of cotton. 	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	colourless
Odour	:	hydrocarbon-like
Odour Threshold	:	No data available
рН	:	Not applicable substance/mixture is non-soluble (in water)
Melting point/ range / Freez- ing point	:	No data available
Boiling point/boiling range	:	ca. 78 °C (172 °F)
Flash point	:	ca4 °C (25 °F) (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	7 %(V)
Lower explosion limit / Lower flammability limit	:	0.6 %(V)
Vapour pressure	:	75.9935 hPa
Relative vapour density	:	No data available

Sika[®] Aktivator-100



Vers 2.0	ion Revision Date: 31.10.2024		SDS Number: 000000033123	Date of last issue: 05.04.2022 Date of first issue: 05.04.2022
	Density	:	ca. 0.727 g/cm3 (20 °C (68 °F))	
	Solubility(ies) Water solubility	:	insoluble	
	Solubility in other solvents	:	No data available	
	Partition coefficient: n- octanol/water	:	No data available	
	Auto-ignition temperature	:	200 °C	
	Decomposition temperature	:	No data available	
	Viscosity Viscosity, dynamic	:	No data available	
	Viscosity, kinematic	:	< 20.5 mm2/s (40 °C (104 °F))	
	Explosive properties	:	No data available	
	Oxidizing properties	:	No data available	
	Volatile organic compounds	:	Directive 2010/75/EU of 24 Nove emissions (integrated pollution pr Volatile organic compounds (VOC	evention and control)

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal us	
Chemical stability	:	The product is chemically stable.	
Possibility of hazardous reac- tions	:	Stable under recommended storage conditions. Vapours may form explosive mixture with air.	
Conditions to avoid	:	Heat, flames and sparks.	
Incompatible materials	:	see section 7.	
Hazardous decomposition products	:	methanol	

Sika[®] Aktivator-100

Revision Date:

31.10.2024

Version

2.0



Date of last issue: 05.04.2022

Date of first issue: 05.04.2022

SECTION 11. TOXICOLOGICAL INFORMATION
Acute toxicity
Not classified due to lack of data.
<u>Components:</u> N-(3-(trimethoxysilyl)propyl)ethylenediamine: Acute oral toxicity : LD50 Oral (Rat): 2,995 mg/kg
Skin corrosion/irritation
Causes skin irritation.
Serious eye damage/eye irritation
Causes serious eye damage.
Respiratory or skin sensitisation
Skin sensitisation
May cause an allergic skin reaction.
Respiratory sensitisation Not classified due to lack of data.
Chronic toxicity
Germ cell mutagenicity
Not classified due to lack of data.
Carcinogenicity
Not classified due to lack of data.
Reproductive toxicity
Not classified due to lack of data.
STOT - single exposure
May cause drowsiness or dizziness.
STOT - repeated exposure
Not classified due to lack of data.
Aspiration toxicity
May be fatal if swallowed and enters airways.
SECTION 12. ECOLOGICAL INFORMATION
Ecotoxicity
No data available
Persistence and degradability
No data available

SDS Number:

00000033123

Sika[®] Aktivator-100



Version 2.0	Revision Date: 31.10.2024		SDS Number: 000000033123	Date of last issue: 05.04.2022 Date of first issue: 05.04.2022
	ccumulative potential			
Mobi	lity in soil			
No da	No data available			
Othe	r adverse effects			
Prod	uct:			
Addit matio	ional ecological infor- n		An environmental hazard canr unprofessional handling or dis Toxic to aquatic life with long l	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods Waste from residues :	Send to a licensed waste management company.		
	The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemi- cal or used container.		
Contaminated packaging :	Empty remaining contents. Dispose of as unused product.		
	Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.		

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR		
UN/ID No.	:	UN 1866
Proper shipping name	:	Resin solution
Class	:	3
Packing group	:	II
Labels	:	Flammable Liquids
Packing instruction (cargo	:	364
aircraft)		
Packing instruction (passen-	:	353
ger aircraft)		
Environmentally hazardous	:	yes
IMDG-Code		
UN number		UN 1866
	•	

Sika[®] Aktivator-100



Version 2.0	Revision Date: 31.10.2024	SDS Number: 000000033123	Date of last issue: 05.04.2022 Date of first issue: 05.04.2022
Proper shipping name Class Packing group Labels EmS Code Marine pollutant		 RESIN SOLUTION (n-heptane) 3 II 3 F-E, <u>S-E</u> yes 	
Transport in bulk according Not applicable for product as s		ng to Annex II of MARPOL 73/78 s supplied.	and the IBC Code
National Regulations			
ADG			

UN number	:	UN 1866
Proper shipping name	:	RESIN SOLUTION
Class	:	3
Packing group	:	II
Labels	:	3
Hazchem Code	:	•3YE
Environmentally hazardous	:	yes
•		•

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

			n specific for the substance or mixture
Therapeutic Goods (Poisons : Standard) Instrument	: No poison schedule number allocated (Please use the original publication to check for specific uses, specific conditions or threshold limits that might apply for this chemical)		
International Chemical Weapons	· · ·	:	Not applicable
Schedules of Toxic Chemicals and Precursors Prohibition/Licensing Requirements		:	There is no applicable prohibition, authorisation and restricted use requirements, including for carcino- gens referred to in Schedule 10 of the model WHS Act and Regula- tions.
The components of this produc	t are reported in the	e foll	lowing inventories:

AIIC : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date

: 31.10.2024

Sika[®] Aktivator-100



Versic 2.0	on	Revision Date: 31.10.2024		SDS Number: 000000033123	Date of last issue: 05.04.2022 Date of first issue: 05.04.2022			
l	Date form	nat	:	dd.mm.yyyy				
I	Full text	of other abbreviatio	ns					
,	AU OEL		:	Australia. Workplace Exposure Standards for Airborne Con- taminants.				
	AU OEL / TWA AU OEL / STEL ADG ADR		::	Exposure standard - time weighted average Exposure standard - short term exposure limit Australian Dangerous Goods Code. European Agreement concerning the International Carriage of				
I	CAS DNEL EC50		Dangerous Goods by Road Chemical Abstracts Service Derived no-effect level Half maximal effective concentration		on			
l	GHS IATA IMDG		 Globally Harmonized System International Air Transport Association International Maritime Code for Dangerous Goods 		angerous Goods			
	LD50		: Median lethal dosis (the amount of a material, given all a once, which causes the death of 50% (one half) of a groutest animals)		i0% (one half) of a group of			
	LC50		 Median lethal concentration (concentrations of the chair that kills 50% of the test animals during the observer period) 		Is during the observation			
ſ	MARPOL		:	International Convention for the P Ships, 1973 as modified by the Pr				
l	OEL PBT PNEC REACH		:	Occupational Exposure Limit Persistent, bioaccumulative and to Predicted no effect concentration Regulation (EC) No 1907/2006 of and of the Council of 18 December istration, Evaluation, Authorisation	oxic the European Parliament er 2006 concerning the Reg- a and Restriction of Chemi-			
	SVHC vPvB		:	cals (REACH), establishing a Euro Substances of Very High Concern Very persistent and very bioaccur				

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

AU / EN