# Sikaflex®-298 FC



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.08.2018

 2.0
 31.08.2023
 000000106742
 Date of first issue: 08.08.2018

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : Sikaflex®-298 FC

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street

Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45

Emergency telephone number : +61 1800 033 111

Telefax : +61 2 9725 33 30

Recommended use of the chemical and restrictions on use

Product use : Sealant/adhesive

#### **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Flammable liquids : Category 4

Specific target organ toxicity - :

repeated exposure (Inhala-

tion)

Category 2 (Central nervous system)

Short-term (acute) aquatic

hazard

Category 3

**GHS** label elements

Hazard pictograms



Signal word : Warning

Hazard statements : H227 Combustible liquid.

H373 May cause damage to organs (Central nervous system)

through prolonged or repeated exposure if inhaled.

H402 Harmful to aquatic life.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

## Sikaflex®-298 FC



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.08.2018

 2.0
 31.08.2023
 000000106742
 Date of first issue: 08.08.2018

P260 Do not breathe mist or vapours. P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection/ hearing protection.

Response:

P314 Get medical advice/ attention if you feel unwell. P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P403 Store in a well-ventilated place.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

#### Other hazards which do not result in classification

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Hydrocarbons, C9-C12, n-alkanes, isoalkanes,	64742-82-1	>= 1 -< 2.5
cyclics, aromatics (2-25%)		
xylene	1330-20-7	>= 0.25 -< 2.5
Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-	77703-56-1	>= 0.25 -< 2.5
butyl-		
4,4'-methylenediphenyl diisocyanate	101-68-8	0 -< 1

### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

## Sikaflex®-298 FC



Version Revision Date: SDS Number: Date of last issue: 08.08.2018 31.08.2023 000000106742 Date of first issue: 08.08.2018 2.0

If eye irritation persists, consult a specialist.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

No known significant effects or hazards.

See Section 11 for more detailed information on health effects

and symptoms.

May cause damage to organs through prolonged or repeated

exposure if inhaled.

Notes to physician Treat symptomatically.

### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Carbon dioxide (CO2)

Unsuitable extinguishing

media

Water

Hazardous combustion prod- :

No hazardous combustion products are known

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment.

Deny access to unprotected persons.

**Environmental precautions** Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

# Sikaflex®-298 FC



Version **Revision Date:** SDS Number: Date of last issue: 08.08.2018 000000106742 31.08.2023 Date of first issue: 08.08.2018 2.0

#### **SECTION 7. HANDLING AND STORAGE**

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Hygiene measures Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage Store in original container.

Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	64742-82-1	TWA	900 mg/m3	AU OEL
xylene	1330-20-7	STEL	150 ppm 655 mg/m3	AU OEL
		TWA	80 ppm 350 mg/m3	AU OEL
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0.02 mg/m3 (NCO)	AU OEL
	Further information: Category 2 (Carc. 2) Suspected human carcinogen, Sensitiser			
		STEL	0.07 mg/m3 (NCO)	AU OEL

#### **Biological occupational exposure limits**

Components	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
xylene	1330-20-7	Methylhip-	Urine	End of	1.5 g/g creat-	ACGIH

## Sikaflex®-298 FC



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.08.2018

 2.0
 31.08.2023
 000000106742
 Date of first issue: 08.08.2018

puric acids	shift (As	inine	BEI
	soon as		
	possible		
	after ex-		
	posure		
	ceases)		

Appropriate engineering

controls

Use adequate ventilation and/or engineering controls to pre-

vent exposure to vapours.

Personal protective equipment

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Follow AS/NZS 1337.1

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Eye protection : Safety glasses

Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working

clothing, long trousers)

Follow AS 2210:3

Protective clothing needs to be made of cotton.

# **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : paste

Colour : various

Odour : slight

Odour Threshold : No data available

pH : Not applicable substance/mixture is non-soluble (in water)

Melting point/range / Freezing :

point

No data available

# Sikaflex®-298 FC



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.08.2018

 2.0
 31.08.2023
 000000106742
 Date of first issue: 08.08.2018

Boiling point/boiling range : No data available

Flash point : ca. 65 °C (149 °F)

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : 0.01 hPa

Relative vapour density : No data available

Density : ca. 1.18 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic :  $> 20.5 \text{ mm2/s} (40 ^{\circ}\text{C} (104 ^{\circ}\text{F}))$ 

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 4.3% w/w

### **SECTION 10. STABILITY AND REACTIVITY**

## Sikaflex®-298 FC



Version **Revision Date:** SDS Number: Date of last issue: 08.08.2018 2.0 31.08.2023 000000106742 Date of first issue: 08.08.2018

Reactivity No dangerous reaction known under conditions of normal use.

Chemical stability The product is chemically stable.

Possibility of hazardous reac- : No hazards to be specially mentioned.

Conditions to avoid No data available

Incompatible materials see section 7.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Acute toxicity**

Not classified due to lack of data.

#### Components:

xylene:

Acute oral toxicity LD50 Oral (Rat): 3,523 mg/kg

4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

: LC50: 1.5 mg/l Acute inhalation toxicity

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

#### Skin corrosion/irritation

Not classified due to lack of data.

#### **Components:**

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Result Repeated exposure may cause skin dryness or cracking.

### Serious eye damage/eye irritation

Not classified due to lack of data.

#### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified due to lack of data.

### Respiratory sensitisation

Not classified due to lack of data.

# Sikaflex®-298 FC



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.08.2018

 2.0
 31.08.2023
 000000106742
 Date of first issue: 08.08.2018

### **Chronic toxicity**

#### Germ cell mutagenicity

Not classified due to lack of data.

### Carcinogenicity

Not classified due to lack of data.

#### Reproductive toxicity

Not classified due to lack of data.

### STOT - single exposure

Not classified due to lack of data.

### STOT - repeated exposure

May cause damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

#### **Aspiration toxicity**

Not classified due to lack of data.

#### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

### **Components:**

xylene:

Toxicity to fish (Chronic tox-

icitv)

NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l

Exposure time: 56 d

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia (water flea)): 1.17 mg/l

Exposure time: 7 d

### Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Raphidocelis subcapitata (freshwater green alga)): >

100 mg/l

Exposure time: 72 h

# Persistence and degradability

No data available

#### **Bioaccumulative potential**

No data available

# Sikaflex®-298 FC



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.08.2018

 2.0
 31.08.2023
 000000106742
 Date of first issue: 08.08.2018

Mobility in soil

No data available

Other adverse effects

**Product:** 

Additional ecological infor-

mation

: There is no data available for this product.

**SECTION 13. DISPOSAL CONSIDERATIONS** 

**Disposal methods** 

Waste from residues : Send to a licensed waste management company.

The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION** 

**International Regulations** 

IATA-DGR

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo : Not applicable

aircraft)

Packing instruction (passen-

ger aircraft)

Not applicable

IMDG-Code

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable

9/11

## Sikaflex®-298 FC



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.08.2018

 2.0
 31.08.2023
 000000106742
 Date of first issue: 08.08.2018

Labels : Not applicable
EmS Code : Not applicable
Marine pollutant : Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

**National Regulations** 

**ADG** 

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Hazchem Code : Not applicable

Special precautions for user

Not applicable

**SECTION 15. REGULATORY INFORMATION** 

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform

Scheduling of Medicines and

Poisons

: No poison schedule number allocated

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements

: Not applicable

 There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions.

The components of this product are reported in the following inventories:

AIIC : On the inventory, or in compliance with the inventory

**SECTION 16. OTHER INFORMATION** 

Revision Date : 31.08.2023

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

AU OEL : Australia. Workplace Exposure Standards for Airborne Con-

taminants.

# Sikaflex®-298 FC



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.08.2018

 2.0
 31.08.2023
 000000106742
 Date of first issue: 08.08.2018

AU OEL / TWA : Exposure standard - time weighted average AU OEL / STEL : Exposure standard - short term exposure limit

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN