Sikaflex®-292i



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.09.2021

 2.0
 21.01.2025
 000000607756
 Date of first issue: 18.09.2021

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikaflex®-292i

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45

Emergency telephone number: +61 1800 033 111

Telefax : +61 2 9725 33 30

Recommended use of the chemical and restrictions on use

Product use : Sealant/adhesive

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin sensitisation : Category 1

GHS label elements

Hazard pictograms :

Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

Precautionary statements : P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

Prevention:

P261 Avoid breathing mist or vapours.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water. P333 + P313 If skin irritation or rash occurs: Get medical ad-

vice/ attention.

P362 + P364 Take off contaminated clothing and wash it before

Sikaflex®-292i



Version Revision Date: Date of last issue: 18.09.2021 SDS Number: 000000607756 Date of first issue: 18.09.2021 21.01.2025 2.0

reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-	77703-56-1	>= 2.5 -< 10
butyl-		
Hexamethylene-1,6-diisocyanate homopolymer	28182-81-2	0 -< 1
Hardener LH (1,6-Hexanedialdimine)	613222-52-9	0 -< 1
Hardener LI (Isophoronedialdimine)	932742-30-8	>= 0.25 -< 1
Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane	252047-49-7	>= 0.1 -< 0.25
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	>= 0.1 -< 0.25

SECTION 4. FIRST AID MEASURES

Move out of dangerous area. General advice

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

Remove contact lenses. In case of eye contact

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

sensitising effects Allergic reactions

See Section 11 for more detailed information on health effects

Sikaflex®-292i



Date of last issue: 18.09.2021 Version Revision Date: SDS Number: 21.01.2025 000000607756 Date of first issue: 18.09.2021 2.0

and symptoms.

May cause an allergic skin reaction.

Notes to physician Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Hazardous combustion prod: :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

Standard procedure for chemical fires.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

tive equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment.

Deny access to unprotected persons.

Environmental precautions Do not flush into surface water or sanitary sewer system.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Handle in accordance with good industrial hygiene and safety Hygiene measures

Sikaflex®-292i



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.09.2021

 2.0
 21.01.2025
 000000607756
 Date of first issue: 18.09.2021

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis		
		(Form of	ters / Permissible			
		exposure)	concentration			
Hexamethylene-1,6- diisocyanate homopolymer	28182-81-2	TWA	0.02 mg/m3 (NCO)	AU OEL		
	Further inform	Further information: Sensitiser				
		STEL	0.07 mg/m3 (NCO)	AU OEL		

Appropriate engineering

controls

Use adequate ventilation and/or engineering controls to pre-

vent exposure to vapours.

Personal protective equipment

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Follow AS/NZS 1337.1

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Eye protection : Safety glasses

Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working

clothing, long trousers)

Follow AS 2210:3

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : various

Odour : odourless

Sikaflex®-292i



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.09.2021

 2.0
 21.01.2025
 000000607756
 Date of first issue: 18.09.2021

Odour Threshold : No data available

pH : Not applicable substance/mixture is non-soluble (in water)

Melting point/ range / Freez-

ing point

Boiling point/boiling range

No data availableNo data available

Flash point : $> 101 \,^{\circ}\text{C} (214 \,^{\circ}\text{F})$

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : 0.01 hPa

Relative vapour density : No data available

Density : ca. 1.3 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : Not applicable

Viscosity, kinematic : Not applicable

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control)

Not applicable

SECTION 10. STABILITY AND REACTIVITY

Sikaflex®-292i



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.09.2021

 2.0
 21.01.2025
 000000607756
 Date of first issue: 18.09.2021

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

No hazards to be specially mentioned.

Conditions to avoid : No data available

Incompatible materials : see section 7.

Hazardous decomposition

products

No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

Hexamethylene-1,6-diisocyanate homopolymer:

Acute oral toxicity : LD50 Oral (Rat): > 2,500 mg/kg

Acute inhalation toxicity : LC50: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Acute dermal toxicity : LD50 Dermal (Rat): > 2,000 mg/kg

Hardener LI (Isophoronedialdimine):

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Sikaflex®-292i



Date of last issue: 18.09.2021 Version Revision Date: SDS Number: 000000607756 Date of first issue: 18.09.2021 2.0 21.01.2025

Chronic toxicity

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Urea, N, N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Toxicity to fish LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Raphidocelis subcapitata (freshwater green alga)): >

100 ma/l

Exposure time: 72 h

Hardener LI (Isophoronedialdimine):

Toxicity to fish LC50 (Fish): 87.2 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

EC50 (Desmodesmus subspicatus (green algae)): 180.4 mg/l

plants Exposure time: 72 h

Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethox-

ysilane:

Toxicity to fish LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Sikaflex®-292i



Version Date of last issue: 18.09.2021 Revision Date: SDS Number: 21.01.2025 000000607756 Date of first issue: 18.09.2021 2.0

aquatic invertebrates Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l Exposure time: 72 h

Method: OECD Test Guideline 201

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

There is no data available for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues Send to a licensed waste management company.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : Not applicable : Not applicable Proper shipping name : Not applicable Class : Not applicable Subsidiary risk : Not applicable Packing group Not applicable Labels Not applicable Packing instruction (cargo

aircraft)

Packing instruction (passen-

: Not applicable

ger aircraft)

IMDG-Code

Sikaflex®-292i



Date of last issue: 18.09.2021 Version Revision Date: SDS Number: 21.01.2025 000000607756 Date of first issue: 18.09.2021 2.0

Not applicable **UN** number Not applicable Proper shipping name Not applicable Class Not applicable Subsidiary risk Not applicable Packing group Not applicable Labels Not applicable **EmS Code** Not applicable Marine pollutant

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number Not applicable Proper shipping name Not applicable Class Not applicable Subsidiary risk Not applicable Packing group Not applicable Labels Not applicable Not applicable Hazchem Code

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard) Instrument

Therapeutic Goods (Poisons : No poison schedule number allocated (Please use the original publication to check for specific uses, specific conditions or

threshold limits that might apply for this chemical)

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements

Not applicable

There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions.

The components of this product are reported in the following inventories:

AIIC : Low volume exemption

SECTION 16. OTHER INFORMATION

Revision Date 21.01.2025 Date format dd.mm.yyyy

Full text of other abbreviations

Sikaflex®-292i



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.09.2021

 2.0
 21.01.2025
 000000607756
 Date of first issue: 18.09.2021

AU OEL : Australia. Workplace Exposure Standards for Airborne Con-

taminants.

AU OEL / TWA : Exposure standard - time weighted average AU OEL / STEL : Exposure standard - short term exposure limit

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service DNEL : Derived no-effect level

EC50 : Half maximal effective concentration GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN