Sikaflex 211



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 16.11.2019

 2.0
 19.04.2022
 000000606764
 Date of first issue: 23.06.2016

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikaflex 211

Product code : 000000606764

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street

Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45 Telefax : +61 2 9725 33 30 Emergency telephone num- : +61 1800 033 111

ber

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 4

GHS label elements

Hazard pictograms : None Signal word : Warning

Hazard statements : H227 Combustible liquid.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection/ hearing protection.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P403 Store in a well-ventilated place.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Sikaflex 211



Date of last issue: 16.11.2019 Version Revision Date: SDS Number: 19.04.2022 000000606764 Date of first issue: 23.06.2016 2.0

Components

Chemical name	CAS-No.	Concentration (% w/w)
Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-	77703-56-1	>= 2.5 -< 10
butyl-		
xylene	1330-20-7	>= 0.25 -< 2.5
4,4'-methylenediphenyl diisocyanate	101-68-8	0 -< 1

SECTION 4. FIRST AID MEASURES

General advice : No hazards which require special first aid measures.

If inhaled Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

Flush eyes with water as a precaution. In case of eye contact

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms

and effects, both acute and

delayed

No known significant effects or hazards.

See Section 11 for more detailed information on health effects

and symptoms.

Notes to physician Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media Carbon dioxide (CO2)

Unsuitable extinguishing

media

Water

Hazardous combustion prod- :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

Standard procedure for chemical fires.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Sikaflex 211



Version Date of last issue: 16.11.2019 Revision Date: SDS Number: 19.04.2022 000000606764 Date of first issue: 23.06.2016 2.0

tive equipment and emer-

gency procedures

Personal precautions, protec- : For personal protection see section 8.

Environmental precautions No special environmental precautions required.

Methods and materials for

containment and cleaning up

Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Advice on safe handling Do not get in eyes, on skin, or on clothing.

For personal protection see section 8.

Follow standard hygiene measures when handling chemical

products

Handle in accordance with good industrial hygiene and safety Hygiene measures

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage Store in original container.

> Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis	
		(Form of	ters / Permissible		
		exposure)	concentration		
xylene	1330-20-7	STEL	150 ppm	AU OEL	
			655 mg/m3		
		TWA	80 ppm	AU OEL	
			350 mg/m3		
4,4'-methylenediphenyl diiso-	101-68-8	TWA	0.02 mg/m3	AU OEL	
cyanate			(NCO)		
	Further information: Category 2 (Carc. 2) Suspected human car-				
	cinogen, Sensitiser				
		STEL	0.07 mg/m3	AU OEL	
			(NCO)		

Biological occupational exposure limits

Components	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	

Sikaflex 211



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 16.11.2019

 2.0
 19.04.2022
 000000606764
 Date of first issue: 23.06.2016

posure ceases)	xylene	1330-20-7	Methylhip- puric acids	Urine	l •	1.5 g/g creat- inine	ACGIH BEI
----------------	--------	-----------	---------------------------	-------	-----	-------------------------	--------------

Appropriate engineering controls

Use adequate ventilation and/or engineering controls to pre-

vent exposure to vapours.

Personal protective equipment

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Follow AS/NZS 1337.1

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Eye protection : Safety glasses

Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working

clothing, long trousers)

Follow AS 2210:3

Protective clothing needs to be made of cotton.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : various

Odour : characteristic

Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

Flash point : ca. 70 °C (158 °F)

(Method: closed cup)

Evaporation rate : No data available

Sikaflex 211



Version Revision Date: Date of last issue: 16.11.2019 SDS Number: 000000606764 Date of first issue: 23.06.2016 19.04.2022 2.0

Flammability (solid, gas) No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : 0.01 hPa

Relative vapour density No data available

Density ca. 1.33 g/cm3 (23 °C (73 °F))

Solubility(ies)

: No data available Water solubility

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature No data available

Decomposition temperature No data available

Viscosity

: not determined Viscosity, dynamic

> 20.5 mm2/s (40 °C (104 °F)) Viscosity, kinematic

Explosive properties No data available

No data available Oxidizing properties

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

> emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 3.04% w/w

SECTION 10. STABILITY AND REACTIVITY

: No dangerous reaction known under conditions of normal use. Reactivity

Chemical stability The product is chemically stable.

tions

Possibility of hazardous reac- : No hazards to be specially mentioned.

Conditions to avoid : No data available

Incompatible materials : see section 7.

Sikaflex 211



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 16.11.2019

 2.0
 19.04.2022
 000000606764
 Date of first issue: 23.06.2016

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

xylene:

Acute oral toxicity : LD50 Oral (Rat): 3,523 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 1,700 mg/kg

4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Sikaflex 211



Version Date of last issue: 16.11.2019 Revision Date: SDS Number: 000000606764 19.04.2022 Date of first issue: 23.06.2016 2.0

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: EC50 (Raphidocelis subcapitata (freshwater green alga)): >

100 mg/l

Exposure time: 72 h

xylene:

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 2.2

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l

Exposure time: 56 d

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia (water flea)): 1.17 mg/l

Exposure time: 7 d

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil No data available

Other adverse effects

Product:

Additional ecological infor-

There is no data available for this product.

mation

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging Empty remaining contents.

Sikaflex 211



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 16.11.2019

 2.0
 19.04.2022
 000000606764
 Date of first issue: 23.06.2016

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : No poison schedule number allocated

Scheduling of Medicines and

Poisons

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements

Not applicable

There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions.

The components of this product are reported in the following inventories:

AICS : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date : 19.04.2022 Date format : dd.mm.yyyy

Sikaflex 211



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 16.11.2019

 2.0
 19.04.2022
 000000606764
 Date of first issue: 23.06.2016

Full text of other abbreviations

ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

AU OEL : Australia. Workplace Exposure Standards for Airborne Con-

taminants.

AU OEL / TWA : Exposure standard - time weighted average AU OEL / STEL : Exposure standard - short term exposure limit

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN