



BUILDING TRUST



PRODUCT DATA SHEET

Davco Rejuvenation Grout

DESCRIPTION

Davco Rejuvenation Grout is a premixed, ready to use grout designed to be applied straight over existing grout.

Davco Rejuvenation Grout suitable for grout joints 1-5mm wide and a maximum 5mm depth.

Davco Rejuvenation Grout is fast and easy to use and is stain, mould and bacteria resistant.

CHARACTERISTICS / ADVANTAGES

- Ready to use
- Suitable for use in pools
- Easy and fast application
- Stain, mould and bacteria resistant
- No need to rake out full depth of existing grout - only needs 1mm depth

USES

- Suitable for glossy and smooth tiles only. Grout joints with at least 1mm of depth from the existing grout surface to the top of the tile.
- Note: Do not use on flush joints or highly textured and / or porous / unglazed tiles.
- Areas Suitable for interior and exterior applications. Commercial and domestic walls and floors including pools and submerged areas.

PRODUCT INFORMATION

Packaging	1.7kg pails	
Shelf life	12 Months from date of manufacture if unopened	
Storage conditions	Store in dry cool conditions, off ground out of direct sunlight	
Appearance / Colour	Coloured paste	
Volatile organic compound (VOC) content	Low VOC - 2g/L (SCAQMD method 304-91)	
Consumption	1.7kg pail of Davco Rejuvenation Grout covers approximately 20m ² (based on 200 x 200mm tiles with a 4mm wide by 1mm deep grout joint)	
Applied Product Ready for Use	Application	Wait time
	Dry Areas	12 hours
	Wet Areas	2 days
	Submerged Areas	7 days

All measurements are taken at 22°C and 50% relative humidity. Specifications vary according to site conditions and should be taken as a guide only.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

- Test the grout in an inconspicuous area first
- Do not apply in temperatures above 35°C or below 5°C
- In cool and / or humid conditions, allow longer setting times
- Davco Rejuvenation Grout is not recommended for use on highly textured or porous tiles due to its high bond strength
- Existing grout must be at least 1mm below the surface of the tile, allowing sufficient depth for the Rejuvenation Grout to bond to the grout joint
- Alternatively rake out sufficient grout to allow 1mm depth
- Do not allow the Rejuvenation Grout to skin / dry out in the tub. Always replace the plastic film after use
- Do not use acidic cleaners on Rejuvenation Grout
- When used in pools the pH of the water must remain between 6 and 8
- For other uses not mentioned in these instructions, please contact Sika Australia

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

APPLICATION INSTRUCTIONS

EQUIPMENT

- Protective personal equipment
- Grout float or squeegee
- Grouting sponge
- Bucket and clean water

SUBSTRATE PREPARATION

- All surfaces must be installed according to manufacturer's instructions and relevant Australian Standard(s) and be structurally sound, dry, clean and free from movement, oil, grease, wax, sealers, curing compounds, release agents and any other loose or contaminating material
- The tile and grout surface must be thoroughly cleaned with either a mild soap and water mixture or sugar soap mixture. If required, a bristle brush can be used to clean the existing grout joints

Sika Australia Pty Limited

ABN 12 001 342 329

aus.sika.com

Tel: 1300 22 33 48



Product Data Sheet

Davco Rejuvenation Grout

August 2022, Version 01.01

02172010000000107

- Rinse surface with clean water to ensure there is no residue on the surface and allow the surface to completely dry prior to application of Rejuvenation Grout

MIXING

Stir thoroughly before use

APPLICATION

1. Apply to the grout joint and using the float or squeegee, spread diagonally across the joint. Ensure you are filling the joint evenly. Only cover 1m² at a time as Rejuvenation Grout will be difficult to clean off once it dries.
2. After approximately 5-10 minutes, clean off excess grout and evenly shape the grout joints by laying a damp sponge on the tile surface and lightly wiping in a circular motion.
3. Finish the application with a single diagonal wipe to the tile surface with a well wrung sponge. Avoid applying excessive force or repeatedly wiping as this may remove the grout from the joint. If the water in the bucket becomes dirty, replace with clean water.

CLEANING OF TOOLS

Tools and equipment can be cleaned with water prior to the grout drying.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

DavcoRejuvenationGrout-en-AUDAVCO-(08-2022)-1-1.pdf