Sika® Concrete Primer (A)



Version SDS Number: Date of last issue: 26.07.2020 Revision Date: 000000604217 Date of first issue: 04.11.2016 21.06.2022 3.0

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sika® Concrete Primer (A)

Product code : 000000604217

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street

Wetherill Park. NSW 2164

Telephone : +61 2 9725 11 45 +61 2 9725 33 30 Telefax : +61 1800 033 111 Emergency telephone num-

Recommended use of the chemical and restrictions on use

Product use : Primer, For professional users only.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Skin corrosion/irritation Category 2

Serious eye damage/eye irri-

tation

: Category 2A

Respiratory sensitisation : Category 1

Skin sensitisation Category 1

Carcinogenicity Category 2

single exposure

Specific target organ toxicity - : Category 3 (Central nervous system)

GHS label elements

Hazard pictograms







Signal word

H226 Flammable liquid and vapour. Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

Sika® Concrete Primer (A)



Version Revision Date: SDS Number: Date of last issue: 26.07.2020 21.06.2022 000000604217 Date of first issue: 04.11.2016 3.0

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

Precautionary statements **Prevention:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting equip-

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing mist or vapours.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection/ hearing protection.

P284 Wear respiratory protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.

P362 + P364 Take off contaminated clothing and wash it before

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Sika® Concrete Primer (A)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.07.2020

 3.0
 21.06.2022
 000000604217
 Date of first issue: 04.11.2016

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
2-methoxy-1-methylethyl acetate	108-65-6	>= 20 -< 30
4,4'-methylenediphenyl diisocyanate	101-68-8	>= 1 -< 10
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	>= 1 -< 10
propyl acetate	109-60-4	< 10
Diphenylmethanediisocyanate, isomeres and	9016-87-9	>= 1 -< 10
homologues		
2,2'-methylenediphenyl diisocyanate	2536-05-2	< 1

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

: irritant effects sensitising effects

Asthmatic appearance
Allergic reactions
Excessive lachrymation

Dermatitis

Sika® Concrete Primer (A)



Date of last issue: 26.07.2020 Version Revision Date: SDS Number: Date of first issue: 04.11.2016 21.06.2022 000000604217 3.0

Loss of balance

Vertigo

See Section 11 for more detailed information on health effects

and symptoms. Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

May cause drowsiness or dizziness. Suspected of causing cancer.

Treat symptomatically. Notes to physician

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

Water

High volume water jet

Specific hazards during fire-

fighting

Do not use a solid water stream as it may scatter and spread

fire.

Hazardous combustion prod- :

No hazardous combustion products are known

Specific extinguishing meth-

Use water spray to cool unopened containers.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Hazchem Code •3Y

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Remove all sources of ignition. Deny access to unprotected persons.

Environmental precautions Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

Sika® Concrete Primer (A)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.07.2020

 3.0
 21.06.2022
 000000604217
 Date of first issue: 04.11.2016

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Use explosion-proof equipment.

Keep away from heat/ sparks/ open flames/ hot surfaces. No

smoking.

Take precautionary measures against electrostatic discharg-

es.

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

products

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis	
2-methoxy-1-methylethyl ace-	108-65-6	TWA	50 ppm	AU OEL	
tate			274 mg/m3		
Further information: Skin absorption					

Sika® Concrete Primer (A)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.07.2020

 3.0
 21.06.2022
 000000604217
 Date of first issue: 04.11.2016

		STEL	100 ppm 548 mg/m3	AU OEL		
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0.02 mg/m3 (NCO)	AU OEL		
	Further information: Category 2 (Carc. 2) Suspected human carcinogen, Sensitiser					
		STEL	0.07 mg/m3 (NCO)	AU OEL		
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	TWA	0.02 mg/m3 (NCO)	AU OEL		
	Further information: Sensitiser					
		STEL	0.07 mg/m3 (NCO)	AU OEL		
		TWA	0.02 mg/m3 (NCO)	AU OEL		
	Further information: Category 2 (Carc. 2) Suspected human carcinogen, Sensitiser					
		STEL	0.07 mg/m3 (NCO)	AU OEL		
propyl acetate	109-60-4	TWA	200 ppm 835 mg/m3	AU OEL		
		STEL	250 ppm 1,040 mg/m3	AU OEL		
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	TWA	0.02 mg/m3 (NCO)	AU OEL		
	Further information: Sensitiser					
		STEL	0.07 mg/m3 (NCO)	AU OEL		
		TWA	0.02 mg/m3 (NCO)	AU OEL		
	Further information: Category 2 (Carc. 2) Suspected human carcinogen, Sensitiser					
		STEL	0.07 mg/m3 (NCO)	AU OEL		
2,2'-methylenediphenyl diisocyanate	2536-05-2	TWA	0.02 mg/m3 (NCO)	AU OEL		
-	Further information: Sensitiser					
		STEL	0.07 mg/m3 (NCO)	AU OEL		
		TWA	0.02 mg/m3 (NCO)	AU OEL		
	Further information: Category 2 (Carc. 2) Suspected human carcinogen, Sensitiser					
		STEL	0.07 mg/m3 (NCO)	AU OEL		

Appropriate engineering controls

Use adequate ventilation and/or engineering controls to prevent exposure to vapours.

veni exposure to vapour

Avoid vapor formation.

Provide appropriate exhaust ventilation at places where va-

por is formed.

Sika® Concrete Primer (A)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.07.2020

 3.0
 21.06.2022
 000000604217
 Date of first issue: 04.11.2016

Personal protective equipment

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

organic vapor filter (Type A)

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary

Follow AS/NZS 1337.1

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Eye protection : Safety glasses

Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working

clothing, long trousers) Follow AS 2210:3

Protective clothing needs to be made of cotton.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : light yellow

Odour : characteristic

Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing :

Boiling point/boiling range

point

Flash point

No data available

No data available

40 °C (104 °F) (Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

10.8 %(V)

Lower explosion limit / Lower

flammability limit

1.5 %(V)

Vapour pressure : 33 hPa

Sika® Concrete Primer (A)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.07.2020

 3.0
 21.06.2022
 000000604217
 Date of first issue: 04.11.2016

Relative vapour density : No data available

Density : ca. 1.1 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

Auto-ignition temperature

: 333 °C

No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : $> 7 \text{ mm2/s} (40 ^{\circ}\text{C} (104 ^{\circ}\text{F}))$

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 33.86% w/w

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions. Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : see section 7.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Sika® Concrete Primer (A)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.07.2020

 3.0
 21.06.2022
 000000604217
 Date of first issue: 04.11.2016

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity : LD50 Oral (Rat): > 10,000 mg/kg

Acute inhalation toxicity : LC50: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9,400 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Sika® Concrete Primer (A)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.07.2020

 3.0
 21.06.2022
 000000604217
 Date of first issue: 04.11.2016

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l

Exposure time: 96 h

Toxicity to algae/aquatic

plants

: EC50 (Desmodesmus subspicatus (green algae)): > 1,640

mg/l

Exposure time: 72 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

: There is no data available for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

SECTION 14. TRANSPORT INFORMATION

International Regulations

Sika® Concrete Primer (A)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.07.2020

 3.0
 21.06.2022
 000000604217
 Date of first issue: 04.11.2016

IATA-DGR

UN/ID No. : UN 1263

Proper shipping name : Paint related material

Class : 3 Packing group : III

Labels : Flammable Liquids

Packing instruction (cargo : 366

aircraft)

Packing instruction (passen- : 355

ger aircraft)

IMDG-Code

UN number : UN 1263

Proper shipping name : PAINT RELATED MATERIAL

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number : UN 1263

Proper shipping name : PAINT RELATED MATERIAL

Class : 3
Packing group : III
Labels : 3
Hazchem Code : •3Y

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : No poison schedule number allocated

Scheduling of Medicines and

Poisons

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements

Not applicable

There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

Sika® Concrete Primer (A)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.07.2020

 3.0
 21.06.2022
 000000604217
 Date of first issue: 04.11.2016

tions.

The components of this product are reported in the following inventories:

AICS : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date : 21.06.2022 Date format : dd.mm.yyyy

Full text of other abbreviations

AU OEL : Australia. Workplace Exposure Standards for Airborne Con-

taminants.

AU OEL / TWA : Exposure standard - time weighted average AU OEL / STEL : Exposure standard - short term exposure limit

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road Chemical Abstracts Service

CAS : Chemical Abstracts Servi
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Sika® Concrete Primer (A)



Version 3.0

Revision Date: 21.06.2022

SDS Number: 000000604217

Date of last issue: 26.07.2020 Date of first issue: 04.11.2016

Changes as compared to previous version!

AU / EN