# Sikadur 52(AU) Part B



Version 4.0

Revision Date: 15.06.2023

SDS Number: 100000008657

Date of last issue: 22.07.2021 Date of first issue: 14.11.2019

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : Sikadur 52(AU) Part B

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45

Emergency telephone number : +61 1800 033 111

Telefax : +61 2 9725 33 30

### **SECTION 2. HAZARDS IDENTIFICATION**

#### **GHS Classification**

Acute toxicity (Oral) : Category 4

Skin corrosion/irritation : Sub-category 1B

Serious eye damage/eye irri-

tation

Category 1

Skin sensitisation : Category 1

Long-term (chronic) aquatic

hazard

Category 2

### **GHS** label elements

Hazard pictograms







Signal word : Danger

Hazard statements : H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:** 

P261 Avoid breathing mist or vapours. P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

# Sikadur 52(AU) Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.07.2021

 4.0
 15.06.2023
 100000008657
 Date of first issue: 14.11.2019

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

#### Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

#### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

#### Other hazards which do not result in classification

None known.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
benzyl alcohol	100-51-6	>= 30 -< 60
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	>= 10 -< 30
3,6-diazaoctanethylenediamin	112-24-3	>= 10 -< 25
bis(isopropyl)naphthalene	38640-62-9	>= 10 -< 25
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	>= 5 -< 10
Adduct IA (epoxy amine adduct)	68609-08-5	>= 2.5 -< 10
bis[(dimethylamino)methyl]phenol	71074-89-0	>= 1 -< 3
2-(2-aminoethylamino)ethanol	111-41-1	< 0.3
2-piperazin-1-ylethylamine	140-31-8	< 1
3,6,9-triazaundecamethylenediamine	112-57-2	< 1

# Sikadur 52(AU) Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.07.2021

 4.0
 15.06.2023
 100000008657
 Date of first issue: 14.11.2019

**SECTION 4. FIRST AID MEASURES** 

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Health injuries may be delayed.

corrosive effects sensitising effects

Gastrointestinal discomfort

Allergic reactions

**Dermatitis** 

See Section 11 for more detailed information on health effects

and symptoms. Harmful if swallowed.

May cause an allergic skin reaction. Causes serious eye damage.

Causes severe burns.

Notes to physician : Treat symptomatically.

### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

# Sikadur 52(AU) Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.07.2021

 4.0
 15.06.2023
 100000008657
 Date of first issue: 14.11.2019

Hazardous combustion prod- :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

ods

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Hazchem Code : 2X

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

# Sikadur 52(AU) Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.07.2021

 4.0
 15.06.2023
 100000008657
 Date of first issue: 14.11.2019

Conditions for safe storage : Store in original container.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Appropriate engineering

controls

: Use adequate ventilation and/or engineering controls to pre-

vent exposure to vapours.

Personal protective equipment

Respiratory protection : No special measures required.

Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Follow AS/NZS 1337.1

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Eye protection : Safety glasses

Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working

clothing, long trousers) Follow AS 2210:3 Rubber aprons

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : yellow

Odour : amine-like

Odour Threshold : No data available

pH : > 11 (20 °C (68 °F))

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

# Sikadur 52(AU) Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.07.2021

 4.0
 15.06.2023
 100000008657
 Date of first issue: 14.11.2019

Flash point :  $> 140 \, ^{\circ}\text{C} \, (> 284 \, ^{\circ}\text{F})$ 

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : 0.07 hPa

Relative vapour density : No data available

Density : ca. 1.01 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : ca. 45 mPa.s (20 °C (68 °F))

Viscosity, kinematic : > 20.5 mm2/s ( 40 °C (104 °F))

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 37.1% w/w

**SECTION 10. STABILITY AND REACTIVITY** 

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions.

# Sikadur 52(AU) Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.07.2021

 4.0
 15.06.2023
 100000008657
 Date of first issue: 14.11.2019

Conditions to avoid : No data available

Incompatible materials : see section 7.

No decomposition if stored and applied as directed.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

**Acute toxicity** 

Harmful if swallowed.

Components: benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity : LD50 Oral (Rat): 1,030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 10 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 - 5,000 mg/kg

3,6-diazaoctanethylenediamin:

Acute oral toxicity : LD50 Oral (Rat): 1,716 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 1,465 mg/kg

bis(isopropyl)naphthalene:

Acute oral toxicity : LD50 Oral (Rat): > 3,900 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.64 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): > 4,500 mg/kg

2,4,6-tris(dimethylaminomethyl)phenol:

Acute oral toxicity : LD50 Oral (Rat): 2,169 mg/kg

Adduct IA (epoxy amine adduct):

Acute oral toxicity : LD50 Oral (Rat, female): 300 - 2,000 mg/kg

Method: OECD Test Guideline 423

2-piperazin-1-ylethylamine:

# Sikadur 52(AU) Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.07.2021

 4.0
 15.06.2023
 100000008657
 Date of first issue: 14.11.2019

Acute oral toxicity : LD50 Oral (Rat): 2,097 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): ca. 866 mg/kg

3,6,9-triazaundecamethylenediamine:

Acute oral toxicity : LD50 Oral (Rat): 1,716.2 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): 1,260 mg/kg

Skin corrosion/irritation

Causes severe burns.

**Components:** 

**2,4,6-tris(dimethylaminomethyl)phenol:**Species : Rabbit

Assessment : Corrosive

Method : OECD Test Guideline 404

Serious eye damage/eye irritation

Causes serious eye damage.

**Components:** 

**2,4,6-tris(dimethylaminomethyl)phenol:**Species : Rabbit

Assessment : Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

**Chronic toxicity** 

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

# Sikadur 52(AU) Part B



Date of last issue: 22.07.2021 Version Revision Date: SDS Number: 100000008657 Date of first issue: 14.11.2019 4.0 15.06.2023

### **Aspiration toxicity**

Not classified based on available information.

#### **SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity** 

Components:

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to algae/aquatic

ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100

plants

Exposure time: 72 h

NOEC (Desmodesmus subspicatus (green algae)): 1.5 mg/l

Exposure time: 72 h

3,6-diazaoctanethylenediamin:

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 10 - 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 10 -

100 mg/l

Exposure time: 72 h

2,4,6-tris(dimethylaminomethyl)phenol:

Toxicity to algae/aquatic EC50 (Scenedesmus capricornutum (fresh water algae)): > 10

plants - 100 mg/l

Exposure time: 72 h

Adduct IA (epoxy amine adduct):

Toxicity to algae/aquatic

: EC50 (Pseudokirchneriella subcapitata (algae)): 3.13 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic tox-

icity)

plants

LC50 (Danio rerio (zebra fish)): 1.62 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates (Chron-Exposure time: 48 h

EC50 (Daphnia magna (Water flea)): 1.75 mg/l

ic toxicity)

2-piperazin-1-ylethylamine:

Toxicity to fish LC50 (Fish): > 100 mg/l

Exposure time: 96 h

# Sikadur 52(AU) Part B



Date of last issue: 22.07.2021 Version Revision Date: SDS Number: 100000008657 Date of first issue: 14.11.2019 4.0 15.06.2023

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

**Product:** 

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues Send to a licensed waste management company.

The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

### **SECTION 14. TRANSPORT INFORMATION**

## **International Regulations**

**IATA-DGR** 

UN/ID No. UN 1760

Proper shipping name Corrosive liquid, n.o.s.

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, Amines,

polyethylenepoly-, triethylenetetramine fraction)

Class Ш Packing group

Labels Corrosive Packing instruction (cargo 856

aircraft)

Packing instruction (passen-

ger aircraft)

852

**IMDG-Code** 

**UN** number UN 1760

10 / 12

# Sikadur 52(AU) Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.07.2021

 4.0
 15.06.2023
 100000008657
 Date of first issue: 14.11.2019

Proper shipping name : CORROSIVE LIQUID, N.O.S.

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, Amines, pol-

yethylenepoly-, triethylenetetramine fraction)

Class : 8
Packing group : III
Labels : 8
EmS Code : F-A

EmS Code : F-A, S-B Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## **National Regulations**

**ADG** 

UN number : UN 1760

Proper shipping name : CORROSIVE LIQUID, N.O.S.

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, Amines,

polyethylenepoly-, triethylenetetramine fraction)

Class : 8
Packing group : III
Labels : 8
Hazchem Code : 2X

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15. REGULATORY INFORMATION**

### Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : Schedule 5

Scheduling of Medicines and

**Poisons** 

Standard for the Uniform : Schedule 5

Scheduling of Medicines and

Poisons

International Chemical Weapons Convention (CWC) : Not

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements

Not applicable

There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions.

### The components of this product are reported in the following inventories:

AICS : On the inventory, or in compliance with the inventory

# Sikadur 52(AU) Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.07.2021

 4.0
 15.06.2023
 100000008657
 Date of first issue: 14.11.2019

#### **SECTION 16. OTHER INFORMATION**

Revision Date : 15.06.2023 Date format : dd.mm.yyyy

Full text of other abbreviations

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN