

PRODUCT DATA SHEET

SikaRoof® VersiFrame Edge Support Spacer Tab

SPACER TAB FOR EDGE SUPPORT ON HEIGHT-ADJUSTABLE PEDESTAL SYSTEM

DESCRIPTION

SikaRoof® VersiFrame Edge Support Spacer Tab is a spacer tab used on top of edge supports to create precise and uniform gaps for the alignment of pavers in raised flooring systems. Spacer tabs are manufactured from recycled polypropylene (PP), and it rotates 360° to be able to support narrow or non-right angled pavers to be installed along perimeter wall, bridge over obstructions on the roof, and support odd-shaped pavers to achieve unique patterns and layouts of raised flooring.

SikaRoof® VersiFrame Edge Support Spacer Tab is used in conjunction with SikaRoof® VersiFrame Edge Support and is placed in three possible rails to maximise variation in spacer tab placement to support as many unique paver designs as possible.

USES

Spacer tabs are used with edge supports for raised flooring on podiums, balconies, roof terraces and areas with hardscape finishes.

FEATURES

- Increased paver design capabilities
- Promotes surface drainage
- Eliminates efflorescence
- Resistant to biological attack by moulds and algae
- Chemically resistant to acids, alkalis, oils and soil chemicals
- Operates within a wide service temperature range

PRODUCT INFORMATION

Packaging

- SikaRoof® VersiFrame Edge Support Spacer Tab 3.0
 - SikaRoof® VersiFrame Edge Support Spacer Tab 4.0
 - SikaRoof® VersiFrame Edge Support Spacer Tab Multiple
- Refer to pricelist

Appearance and colour

Black circular set of 5 spacer tabs



Shelf life	No expiration date if the product is stored in accordance to the storage conditions as stated in this Product Data Sheet.								
Storage conditions	Products must be stored in their original packing, in their original box, and under cool and dry conditions. The product must be protected from direct sunlight, rain, snow and ice, and any other elements.								
Dimensions	Ø 62 x 14 mm								
Thickness	Spacer Tab Thickness SikaRoof® VersiFrame Edge Support Spacer Tab <table><tr><td>3.0</td><td>4.0</td><td>Multiple</td></tr><tr><td>3 mm</td><td>4 mm</td><td>Varied</td></tr></table>			3.0	4.0	Multiple	3 mm	4 mm	Varied
3.0	4.0	Multiple							
3 mm	4 mm	Varied							

TECHNICAL INFORMATION

Service temperature	- 30 °C to 80 °C
---------------------	------------------

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

- SikaRoof® VersiFrame Edge Support Spacer Tab is not resistant to permanent weathering and UV exposure.
- For more information, please contact Sika Sales Personnel.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).



LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Australia Pty Limited

ABN 12 001 342 329

aus.sika.com

Tel: 1300 22 33 48

Product Data Sheet

SikaRoof® VersiFrame Edge Support Spacer Tab

August 2026, Version 01.01

020945051990244013

SikaRoofVersiFrameEdgeSupportSpacerTab-en-AU-(08-2026)-1-1.pdf

