# SikaForce®-800 (B)



Version Date of last issue: 01.07.2022 Revision Date: SDS Number: 100000005942 Date of first issue: 28.05.2015 07.06.2023 4.0

### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : SikaForce®-800 (B)

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45

Emergency telephone number: +61 1800 033 111

: +61 2 9725 33 30 Telefax

Recommended use of the chemical and restrictions on use

Product use : Sealant/adhesive

## **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Acute toxicity (Inhalation) : Category 4

Skin corrosion/irritation Category 2

Serious eye damage/eye irri-

tation

: Category 2A

Respiratory sensitisation : Category 1

Skin sensitisation Category 1

Carcinogenicity Category 2

Specific target organ toxicity - :

single exposure

Category 3 (Respiratory system)

Specific target organ toxicity - : Category 2

repeated exposure

(Inhalation)

**GHS** label elements

Hazard pictograms



Signal word

# SikaForce®-800 (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.07.2022

 4.0
 07.06.2023
 100000005942
 Date of first issue: 28.05.2015

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or re-

peated exposure if inhaled.

#### Precautionary statements

### Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe mist or vapours.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

P284 Wear respiratory protection.

#### Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.

P362 + P364 Take off contaminated clothing and wash it before reuse.

#### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

#### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

# SikaForce®-800 (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.07.2022

 4.0
 07.06.2023
 100000005942
 Date of first issue: 28.05.2015

#### Other hazards which do not result in classification

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Diphenylmethanediisocyanate, isomeres and	9016-87-9	>= 60 -<= 100
homologues		

### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

irritant effects sensitising effects Asthmatic appearance

Couah

Respiratory disorder Allergic reactions Excessive lachrymation

Headache Dermatitis

See Section 11 for more detailed information on health effects

and symptoms. Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficul-

# SikaForce®-800 (B)



Date of last issue: 01.07.2022 Version Revision Date: SDS Number: 10000005942 Date of first issue: 28.05.2015 07.06.2023 4.0

ties if inhaled.

May cause respiratory irritation. Suspected of causing cancer.

May cause damage to organs through prolonged or repeated

exposure if inhaled.

Notes to physician Treat symptomatically.

## **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Hazardous combustion prod- :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

Standard procedure for chemical fires.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

tive equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment.

Deny access to unprotected persons.

**Environmental precautions** : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

## **SECTION 7. HANDLING AND STORAGE**

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

# SikaForce®-800 (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.07.2022

 4.0
 07.06.2023
 100000005942
 Date of first issue: 28.05.2015

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical

products

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis	
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	TWA	0.02 mg/m3 (NCO)	AU OEL	
	Further information: Sensitiser				
		STEL	0.07 mg/m3 (NCO)	AU OEL	
		TWA	0.02 mg/m3 (NCO)	AU OEL	
	Further information: Category 2 (Carc. 2) Suspected human carcinogen, Sensitiser				
		STEL	0.07 mg/m3 (NCO)	AU OEL	

Appropriate engineering

controls

Use adequate ventilation and/or engineering controls to pre-

vent exposure to vapours.

Personal protective equipment

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Follow AS/NZS 1337.1

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

# SikaForce®-800 (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.07.2022

 4.0
 07.06.2023
 100000005942
 Date of first issue: 28.05.2015

Eye protection : Safety glasses

Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working

clothing, long trousers) Follow AS 2210:3

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES** 

Appearance : paste

Colour : grey

Odour : slight

Odour Threshold : No data available

pH : substance/mixture reacts with water

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

Flash point :  $> 100 \,^{\circ}\text{C} \, (212 \,^{\circ}\text{F})$ 

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : 0.01 hPa

Relative vapour density : No data available

Density : ca. 1.23 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

# SikaForce®-800 (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.07.2022

 4.0
 07.06.2023
 100000005942
 Date of first issue: 28.05.2015

Viscosity

Viscosity, dynamic : ca. 35,000 mPa.s (20 °C (68 °F))

Viscosity, kinematic :  $> 20.5 \text{ mm2/s} (40 ^{\circ}\text{C} (104 ^{\circ}\text{F}))$ 

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control)

Not applicable

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

No hazards to be specially mentioned.

Conditions to avoid : No data available

Incompatible materials : see section 7.

## **SECTION 11. TOXICOLOGICAL INFORMATION**

## **Acute toxicity**

Harmful if inhaled.

## Components:

# Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity : LD50 Oral (Rat): > 10,000 mg/kg

Acute inhalation toxicity : LC50: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9,400 mg/kg

### Skin corrosion/irritation

Causes skin irritation.

## Serious eye damage/eye irritation

Causes serious eye irritation.

# SikaForce®-800 (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.07.2022

 4.0
 07.06.2023
 100000005942
 Date of first issue: 28.05.2015

## Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

## Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

## **Chronic toxicity**

## Germ cell mutagenicity

Not classified based on available information.

## Carcinogenicity

Suspected of causing cancer.

### Reproductive toxicity

Not classified based on available information.

### STOT - single exposure

May cause respiratory irritation.

## STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

## **Aspiration toxicity**

Not classified based on available information.

## **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

### **Components:**

## Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l

Exposure time: 96 h

Toxicity to algae/aquatic

: EC50 (Desmodesmus subspicatus (green algae)): > 1,640

plants

mg/l

Exposure time: 72 h

## Persistence and degradability

No data available

# **Bioaccumulative potential**

No data available

### Mobility in soil

No data available

## Other adverse effects

## **Product:**

# SikaForce®-800 (B)



Date of last issue: 01.07.2022 Version Revision Date: SDS Number: 07.06.2023 10000005942 Date of first issue: 28.05.2015 4.0

Additional ecological infor-

mation

There is no data available for this product.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

### **Disposal methods**

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

### **SECTION 14. TRANSPORT INFORMATION**

### **International Regulations**

#### **IATA-DGR**

UN/ID No. Not applicable Not applicable Proper shipping name Not applicable Class Not applicable Subsidiary risk Not applicable Packing group Not applicable Labels Packing instruction (cargo Not applicable

aircraft)

Packing instruction (passen-

ger aircraft)

Not applicable

## **IMDG-Code**

**UN** number Not applicable Proper shipping name Not applicable Class Not applicable Subsidiary risk Not applicable Packing group Not applicable Labels Not applicable EmS Code Not applicable Marine pollutant Not applicable

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

# **National Regulations**

### **ADG**

**UN** number Not applicable Proper shipping name Not applicable Class Not applicable Subsidiary risk Not applicable Packing group Not applicable Labels Not applicable

# SikaForce®-800 (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.07.2022

 4.0
 07.06.2023
 100000005942
 Date of first issue: 28.05.2015

Hazchem Code : Not applicable

Special precautions for user

Not applicable

### **SECTION 15. REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : No poison schedule number allocated

Scheduling of Medicines and

**Poisons** 

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements

Not applicable

There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions

The components of this product are reported in the following inventories:

AICS : On the inventory, or in compliance with the inventory

### **SECTION 16. OTHER INFORMATION**

Revision Date : 07.06.2023 Date format : dd.mm.yyyy

Full text of other abbreviations

AU OEL : Australia. Workplace Exposure Standards for Airborne Con-

taminants.

AU OEL / TWA : Exposure standard - time weighted average AU OEL / STEL : Exposure standard - short term exposure limit

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System
IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

# SikaForce®-800 (B)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.07.2022

 4.0
 07.06.2023
 100000005942
 Date of first issue: 28.05.2015

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN