# Sikadur®-32 LP Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.10.2021

 2.0
 01.12.2025
 100000007159
 Date of first issue: 04.10.2021

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : Sikadur®-32 LP Part B

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street

Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45

Emergency telephone number: +61 1800 033 111

Telefax : +61 2 9725 33 30

Recommended use of the chemical and restrictions on use

Product use : Adhesive, Product is not intended for consumer use

#### **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Skin corrosion/irritation : Sub-category 1B

Serious eye damage/eye irri-

tation

Category 1

Skin sensitisation : Category 1

Short-term (acute) aquatic

hazard

Category 2

Long-term (chronic) aquatic

hazard

Category 2

**GHS** label elements

Hazard pictograms :





Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P261 Avoid breathing mist or vapours.

# Sikadur®-32 LP Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.10.2021

 2.0
 01.12.2025
 100000007159
 Date of first issue: 04.10.2021

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection/ hearing protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT

induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediate-

ly all contaminated clothing. Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Immediately call a

POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/ doctor.

P333 + P313 If skin irritation or rash occurs: Get medical ad-

vice/ attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

P391 Collect spillage.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

### Other hazards which do not result in classification

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)	
Quartz (SiO2)	14808-60-7	>= 10 -< 30	
(1-methylethyl)-1,1'-biphenyl	25640-78-2	>= 10 -< 25	
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	>= 5 -< 10	
3,6-diazaoctanethylenediamin	112-24-3	>= 5 -< 10	
benzyl alcohol	100-51-6	>= 1 -< 10	
Adduct IA (epoxy amine adduct)	68609-08-5	>= 2.5 -< 10	

### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

# Sikadur®-32 LP Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.10.2021

 2.0
 01.12.2025
 100000007159
 Date of first issue: 04.10.2021

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Health injuries may be delayed.

corrosive effects sensitising effects Allergic reactions

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

May cause an allergic skin reaction. Causes serious eye damage.

Causes severe burns.

Notes to physician : Treat symptomatically.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod: :

icts

No hazardous combustion products are known

Specific extinguishing meth-

ods

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

# Sikadur®-32 LP Part B



Version **Revision Date:** SDS Number: Date of last issue: 04.10.2021 100000007159 Date of first issue: 04.10.2021 01.12.2025 2.0

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Hazchem Code 2X

**SECTION 6. ACCIDENTAL RELEASE MEASURES** 

tive equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment. Deny access to unprotected persons.

**Environmental precautions** Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

**SECTION 7. HANDLING AND STORAGE** 

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Handle in accordance with good industrial hygiene and safety Hygiene measures

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Store in original container. Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Store in accordance with local regulations.

# Sikadur®-32 LP Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.10.2021

 2.0
 01.12.2025
 100000007159
 Date of first issue: 04.10.2021

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis	
-		(Form of	ters / Permissible		
		exposure)	concentration		
Quartz (SiO2)	14808-60-7	TWA (Res-	0.05 mg/m3	AU OEL	
		pirable dust)			
	Further information: Category 1A (Carc. 1A) Known to have carcinogenic potential for humans				

Appropriate engineering

controls

Use adequate ventilation and/or engineering controls to pre-

vent exposure to vapours.

Personal protective equipment

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Follow AS/NZS 1337.1

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Eye protection : Safety glasses

Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working

clothing, long trousers) Follow AS 2210:3

Rubber aprons

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : paste

Colour : brown

Odour : amine-like

Odour Threshold : No data available

pH : ca. 11

Concentration: 500 g/l 50 %

Melting point/ range / Freez-

ing point

No data available

Boiling point/boiling range : No data available

# Sikadur®-32 LP Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.10.2021

 2.0
 01.12.2025
 100000007159
 Date of first issue: 04.10.2021

Flash point :  $> 101 \, ^{\circ}\text{C} (214 \, ^{\circ}\text{F})$ 

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : 0.07 hPa

Relative vapour density : No data available

Density : ca. 1.4 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : Not applicable

No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic :  $> 20.5 \text{ mm2/s} (40 ^{\circ}\text{C} (104 ^{\circ}\text{F}))$ 

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and

livestock rearing emissions (integrated pollution prevention

and control)

Volatile organic compounds (VOC) content: 5.1% w/w

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

# Sikadur®-32 LP Part B



Date of last issue: 04.10.2021 Version **Revision Date:** SDS Number: 100000007159 Date of first issue: 04.10.2021 2.0 01.12.2025

tions

Possibility of hazardous reac- : Stable under recommended storage conditions.

Conditions to avoid No data available

see section 7. Incompatible materials

Hazardous decomposition

products

: No hazardous decomposition products are known.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Acute toxicity**

Not classified due to lack of data.

### **Components:**

(1-methylethyl)-1,1'-biphenyl:

Acute oral toxicity LD50 Oral (Rat): 4,650 mg/kg

Method: OECD Test Guideline 401

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity : LD50 Oral (Rat): 1,030 mg/kg

: LC50 (Rat): > 5 mg/l Acute inhalation toxicity

Exposure time: 4 h

Test atmosphere: dust/mist

LD50 (Rabbit): > 2,000 - 5,000 mg/kg Acute dermal toxicity

3,6-diazaoctanethylenediamin:

Acute oral toxicity LD50 Oral (Rat): 1,716 mg/kg

Acute dermal toxicity LD50 Dermal (Rabbit): 1,465 mg/kg

benzyl alcohol:

Acute oral toxicity LD50 Oral (Rat): 1,200 mg/kg

LC50 (Rat): > 4.178 mg/l Acute inhalation toxicity

Exposure time: 4 h

Test atmosphere: dust/mist

Adduct IA (epoxy amine adduct):

LD50 Oral (Rat, female): 300 - 2,000 mg/kg Acute oral toxicity

Method: OECD Test Guideline 423

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

# Sikadur®-32 LP Part B



Version **Revision Date:** SDS Number: Date of last issue: 04.10.2021 100000007159 Date of first issue: 04.10.2021 2.0 01.12.2025

#### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

### Respiratory sensitisation

Not classified due to lack of data.

#### **Chronic toxicity**

### Germ cell mutagenicity

Not classified due to lack of data.

### Carcinogenicity

Not classified due to lack of data.

### Reproductive toxicity

Not classified due to lack of data.

#### STOT - single exposure

Not classified due to lack of data.

### STOT - repeated exposure

Not classified due to lack of data.

#### **Aspiration toxicity**

Not classified due to lack of data.

#### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

#### Components:

### (1-methylethyl)-1,1'-biphenyl:

Toxicity to daphnia and other : LC50 (Daphnia magna (Water flea)): 0.167 mg/l

aquatic invertebrates Exposure time: 48 h

#### 3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to algae/aquatic plants

ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100

mg/l

Exposure time: 72 h

NOEC (Desmodesmus subspicatus (green algae)): 1.5 mg/l

Exposure time: 72 h

#### 3,6-diazaoctanethylenediamin:

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 10 - 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic EC50 (Pseudokirchneriella subcapitata (green algae)): 10 -

# Sikadur®-32 LP Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.10.2021

 2.0
 01.12.2025
 100000007159
 Date of first issue: 04.10.2021

plants 100 mg/l

Exposure time: 72 h

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Adduct IA (epoxy amine adduct):

Toxicity to algae/aquatic

plants

: EC50 (Pseudokirchneriella subcapitata (algae)): 3.13 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic tox-

icity)

LC50 (Danio rerio (zebra fish)): 1.62 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

EC50 (Daphnia magna (Water flea)): 1.75 mg/l

Exposure time: 48 h

Persistence and degradability

No data available

**Bioaccumulative potential** 

No data available

Mobility in soil

No data available

Other adverse effects

**Product:** 

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Send to a licensed waste management company.

The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

# Sikadur®-32 LP Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.10.2021

 2.0
 01.12.2025
 100000007159
 Date of first issue: 04.10.2021

#### **SECTION 14. TRANSPORT INFORMATION**

#### International Regulations

**IATA-DGR** 

UN/ID No. : UN 1759

Proper shipping name : Corrosive solid, n.o.s.

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, (1-

methylethyl)-1,1'-biphenyl)

Class : 8 Packing group : III

Labels : Corrosive

Packing instruction (cargo

aircraft)

Packing instruction (passen: 860

ger aircraft)

Environmentally hazardous : yes

**IMDG-Code** 

UN number : UN 1759

Proper shipping name : CORROSIVE SOLID, N.O.S.

864

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, (1-

methylethyl)-1,1'-biphenyl)

Class : 8
Packing group : III
Labels : 8
EmS Code : F-A, S-B
Marine pollutant : yes
Remarks : Alkalis

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### **National Regulations**

**ADG** 

UN number : UN 1759

Proper shipping name : CORROSIVE SOLID, N.O.S.

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, (1-

methylethyl)-1,1'-biphenyl)

Class : 8
Packing group : III
Labels : 8
Hazchem Code : 2X
Environmentally hazardous : yes

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

# Sikadur®-32 LP Part B



**Revision Date:** Date of last issue: 04.10.2021 Version SDS Number: 100000007159 Date of first issue: 04.10.2021 01.12.2025 2.0

#### **SECTION 15. REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard) Instrument

Therapeutic Goods (Poisons : Schedule 5 (Please use the original publication to check for specific uses, specific conditions or threshold limits that might

apply for this chemical)

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements

Not applicable

There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions.

The components of this product are reported in the following inventories:

AIIC : On the inventory, or in compliance with the inventory

#### **SECTION 16. OTHER INFORMATION**

**Revision Date** 01.12.2025 Date of last issue 04.10.2021 Date format dd.mm.yyyy

Full text of other abbreviations

**AU OEL** Australia. Workplace Exposure Standards for Airborne Con-

taminants.

AU OEL / TWA Exposure standard - time weighted average

**ADG** Australian Dangerous Goods Code.

**ADR** European Agreement concerning the International Carriage of

> Dangerous Goods by Road Chemical Abstracts Service

CAS **DNEL** Derived no-effect level

EC50 Half maximal effective concentration

**GHS** Globally Harmonized System

International Air Transport Association IATA

International Maritime Code for Dangerous Goods **IMDG** 

Median lethal dosis (the amount of a material, given all at LD50

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

International Convention for the Prevention of Pollution from **MARPOL** 

Ships, 1973 as modified by the Protocol of 1978

Occupational Exposure Limit **OEL** 

Persistent, bioaccumulative and toxic **PBT PNEC** Predicted no effect concentration

**REACH** Regulation (EC) No 1907/2006 of the European Parliament

# Sikadur®-32 LP Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.10.2021

 2.0
 01.12.2025
 100000007159
 Date of first issue: 04.10.2021

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN