

# SAFETY DATA SHEET

## SikaBond®-58 Wood Floor



Version  
3.0

Revision Date:  
29.04.2022

SDS Number:  
100000010262

Date of last issue: 10.01.2018  
Date of first issue: 21.12.2017

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SikaBond®-58 Wood Floor

Product code : 100000010262

#### Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.  
55 Elizabeth Street  
Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45

Telefax : +61 2 9725 33 30

Emergency telephone number : +61 1800 033 111

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Skin sensitisation : Category 1

#### GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention:**  
P261 Avoid breathing mist or vapours.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves.

**Response:**  
P302 + P352 IF ON SKIN: Wash with plenty of water.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

#### Other hazards which do not result in classification

None known.

# SAFETY DATA SHEET

## SikaBond®-58 Wood Floor



Version  
3.0

Revision Date:  
29.04.2022

SDS Number:  
100000010262

Date of last issue: 10.01.2018  
Date of first issue: 21.12.2017

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
4,4'-methylenediphenyl diisocyanate	101-68-8	0 -< 1
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	0 -< 1
Hardener LI (Isophoronedialdimine)	932742-30-8	>= 0.25 -< 1
Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane	Not Assigned	>= 0.1 -< 0.25

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : sensitising effects  
Allergic reactions  
See Section 11 for more detailed information on health effects and symptoms.  
May cause an allergic skin reaction.
- Notes to physician : Treat symptomatically.

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Hazardous combustion products : No hazardous combustion products are known

# SAFETY DATA SHEET

## SikaBond®-58 Wood Floor



Version  
3.0

Revision Date:  
29.04.2022

SDS Number:  
100000010262

Date of last issue: 10.01.2018  
Date of first issue: 21.12.2017

---

Specific extinguishing methods : Standard procedure for chemical fires.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

---

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Store in accordance with local regulations.

---

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

# SAFETY DATA SHEET

## SikaBond®-58 Wood Floor



Version  
3.0

Revision Date:  
29.04.2022

SDS Number:  
100000010262

Date of last issue: 10.01.2018  
Date of first issue: 21.12.2017

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0.02 mg/m <sup>3</sup> (NCO)	AU OEL
	Further information: Category 2 (Carc. 2) Suspected human carcinogen, Sensitiser			
		STEL	0.07 mg/m <sup>3</sup> (NCO)	AU OEL
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	TWA	0.02 mg/m <sup>3</sup> (NCO)	AU OEL
	Further information: Sensitiser			
		STEL	0.07 mg/m <sup>3</sup> (NCO)	AU OEL
		TWA	0.02 mg/m <sup>3</sup> (NCO)	AU OEL
	Further information: Category 2 (Carc. 2) Suspected human carcinogen, Sensitiser			
		STEL	0.07 mg/m <sup>3</sup> (NCO)	AU OEL

**Appropriate engineering controls** : Use adequate ventilation and/or engineering controls to prevent exposure to vapours.

### Personal protective equipment

**Respiratory protection** : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  
Follow AS/NZS 1337.1  
Recommended: Butyl rubber/nitrile rubber gloves.  
Contaminated gloves should be removed.

**Eye protection** : Safety glasses

**Skin and body protection** : Protective clothing (e.g. safety shoes, long-sleeved working clothing, long trousers)  
Follow AS 2210:3

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** : paste

**Colour** : light brown

**Odour** : characteristic

# SAFETY DATA SHEET

## SikaBond®-58 Wood Floor



Version 3.0      Revision Date: 29.04.2022      SDS Number: 100000010262      Date of last issue: 10.01.2018  
Date of first issue: 21.12.2017

---

Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing point : No data available

Boiling point/boiling range : No data available

Flash point : ca. 150 °C (302 °F)  
(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : 0.01 hPa

Relative vapour density : No data available

Density : ca. 1.31 g/cm<sup>3</sup> (23 °C (73 °F))

Solubility(ies)

    Water solubility : insoluble

    Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

    Viscosity, dynamic : No data available

    Viscosity, kinematic : > 20.5 mm<sup>2</sup>/s ( 40 °C (104 °F))

Explosive properties : No data available

Oxidizing properties : No data available

|| Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

# SAFETY DATA SHEET

## SikaBond®-58 Wood Floor



Version 3.0	Revision Date: 29.04.2022	SDS Number: 100000010262	Date of last issue: 10.01.2018 Date of first issue: 21.12.2017
----------------	------------------------------	-----------------------------	---

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reactions : No hazards to be specially mentioned.

Conditions to avoid : No data available

Incompatible materials : see section 7.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **4,4'-methylenediphenyl diisocyanate:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1.5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgement

##### **Diphenylmethanediisocyanate, isomeres and homologues:**

Acute oral toxicity : LD50 Oral (Rat): > 10,000 mg/kg

Acute inhalation toxicity : LC50: 1.5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgement  
Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9,400 mg/kg

##### **Hardener LI (Isophoronedialdimine):**

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

#### **Skin corrosion/irritation**

Not classified based on available information.

#### **Serious eye damage/eye irritation**

Not classified based on available information.

# SAFETY DATA SHEET

## SikaBond®-58 Wood Floor



Version  
3.0

Revision Date:  
29.04.2022

SDS Number:  
100000010262

Date of last issue: 10.01.2018  
Date of first issue: 21.12.2017

### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

#### Respiratory sensitisation

Not classified based on available information.

### Chronic toxicity

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### Aspiration toxicity

Not classified based on available information.

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### Diphenylmethanediisocyanate, isomers and homologues:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l  
Exposure time: 96 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 1,640 mg/l  
Exposure time: 72 h

##### Hardener LI (Isophoronedialdimine):

Toxicity to fish : LC50 (Fish): 87.2 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): > 100 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 180.4 mg/l  
Exposure time: 72 h

##### Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane:

# SAFETY DATA SHEET

## SikaBond®-58 Wood Floor



Version 3.0	Revision Date: 29.04.2022	SDS Number: 100000010262	Date of last issue: 10.01.2018 Date of first issue: 21.12.2017
----------------	------------------------------	-----------------------------	---

---

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Additional ecological information : There is no data available for this product.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code



# SAFETY DATA SHEET

## SikaBond®-58 Wood Floor



Version 3.0	Revision Date: 29.04.2022	SDS Number: 100000010262	Date of last issue: 10.01.2018 Date of first issue: 21.12.2017
----------------	------------------------------	-----------------------------	---

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

#### ADG

Not regulated as a dangerous good

## SECTION 15. REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform Scheduling of Medicines and Poisons : No poison schedule number allocated

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors Prohibition/Licensing Requirements : There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.

### The components of this product are reported in the following inventories:

AICS : On the inventory, or in compliance with the inventory

## SECTION 16. OTHER INFORMATION

Revision Date : 29.04.2022  
Date format : dd.mm.yyyy

### Full text of other abbreviations

AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.  
AU OEL / TWA : Exposure standard - time weighted average  
AU OEL / STEL : Exposure standard - short term exposure limit  
ADG : Australian Dangerous Goods Code.  
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road  
CAS : Chemical Abstracts Service  
DNEL : Derived no-effect level  
EC50 : Half maximal effective concentration  
GHS : Globally Harmonized System  
IATA : International Air Transport Association  
IMDG : International Maritime Code for Dangerous Goods  
LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)  
LC50 : Median lethal concentration (concentrations of the chemical in

# SAFETY DATA SHEET

## SikaBond®-58 Wood Floor



Version  
3.0

Revision Date:  
29.04.2022

SDS Number:  
100000010262

Date of last issue: 10.01.2018  
Date of first issue: 21.12.2017

	air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: [aus.sika.com](http://aus.sika.com)

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

AU / EN