Sikadur®-330 Part A



Version 1.0	Revision Date: 30.11.2023		SDS Number: 100000040507	Date of last issue: - Date of first issue: 30.11.2023
SECTION	1. PRODUCT AND CO	MPA	NY IDENTIFICATION	
Produ	ict name	:	Sikadur [®] -330 Part A	
Manu	facturer or supplier's	deta	ils	
Comp	pany	:	Sika Australia Pty. Ltd. 55 Elizabeth Street Wetherill Park, NSW 2164	
Telep	hone	:	+61 2 9725 11 45	
Emer	gency telephone numbe	er :	+61 1800 033 111	
Telefa	ах	:	+61 2 9725 33 30	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification Skin corrosion/irritation	: Category 2	
Serious eye damage/eye irri- tation	: Category 1	
Skin sensitisation	: Category 1	
Short-term (acute) aquatic hazard	: Category 2	
Long-term (chronic) aquatic hazard	: Category 2	
GHS label elements Hazard pictograms		
Signal word	: Danger	
Hazard statements	 H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H411 Toxic to aquatic life with long lasting effects. 	
Precautionary statements	 Prevention: P261 Avoid breathing dust. 	

Sikadur®-330 Part A



Version 1.0	Revision Date: 30.11.2023	SDS Number: 100000040507	Date of last issue: - Date of first issue: 30.11.2023			
		the workplace. P273 Avoid release to the	clothing should not be allowed out of			
		 Response: P302 + P352 IF ON SKIN: Wash with plenty of water. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P362 + P364 Take off contaminated clothing and wash it before reuse. P391 Collect spillage. 				
		Disposal: P501 Dispose of contents/ disposal plant.	container to an approved waste			

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight	25068-38-6	>= 30 -< 60
≤ 700)		
calcium carbonate	471-34-1	>= 10 -< 30
1,4-bis(2,3 epoxypropoxy)butane	2425-79-8	>= 10 -< 25
Solvent naphtha (petroleum), heavy arom.	64742-94-5	>= 2.5 -< 10

SECTION 4. FIRST AID MEASURES

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water.

Sikadur[®]-330 Part A



Version 1.0	Revision Date: 30.11.2023		SDS Number: 100000040507	Date of last issue: - Date of first issue: 30.11.2023	
			If symptoms persist, call a physic	ian.	
In case of eye contact		:	Small amounts splashed into eyes can cause irreversible tis- sue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.		
lf swa	If swallowed		Clean mouth with water and drink afterwards plenty of water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.		
	mportant symptoms fects, both acute and ed	:	irritant effects sensitising effects Allergic reactions Excessive lachrymation Dermatitis See Section 11 for more detailed and symptoms. Causes skin irritation. May cause an allergic skin reaction Causes serious eye damage.		
Notes	to physician	:	Treat symptomatically.		

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
Specific extinguishing meth- ods	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Sikadur[®]-330 Part A



Version 1.0	Revision Date: 30.11.2023		SDS Number: 100000040507	Date of last issue: - Date of first issue: 30.11.2023
	ecial protective equipment firefighters	:	In the event of fire, wear s	elf-contained breathing apparatus.
Ha	zchem Code	:	•3Z	
SECTIO	DN 6. ACCIDENTAL RELE	AS	EMEASURES	
tive	rsonal precautions, protec- e equipment and emer- ncy procedures	:	Use personal protective ed Deny access to unprotecte	
En	vironmental precautions	:		vater or sanitary sewer system. s rivers and lakes or drains inform
	ethods and materials for ntainment and cleaning up	:	Pick up and arrange dispo Keep in suitable, closed co	
SECTIO	ON 7. HANDLING AND STO	DR/	AGE	
	vice on protection against and explosion	:	Normal measures for prev	entive fire protection.
Ad	vice on safe handling	:	section 8). Do not get in eyes, on skir For personal protection se Persons with a history of s ma, allergies, chronic or re not be employed in any pr used. Smoking, eating and drink plication area.	
			Do not breathe vapours/du	ust.
Hy	giene measures	:	practice. When using do not eat or When using do not smoke	
Co	nditions for safe storage	:	Keep container tightly clos place. Store in accordance with le	eed in a dry and well-ventilated ocal regulations.

Sikadur[®]-330 Part A



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.11.2023	10000040507	Date of first issue: 30.11.2023

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis		
		(Form of	ters / Permissible			
a a la investa a a de a via da	474.04.4	exposure)	concentration			
calcium carbonate	471-34-1	TWA	10 mg/m3	AU OEL		
			(Calcium car- bonate)			
	Eurthor inform	L ation: This value	is for inhalable dust	containing no		
		< 1% crystalline		containing no		
Appropriate engineering controls	Provide approis formed.	Provide appropriate exhaust ventilation at places where dust is formed.				
Personal protective equipment	nt					
Respiratory protection	 In case of inadequate ventilation wear respiratory p Respirator selection must be based on known or an exposure levels, the hazards of the product and the working limits of the selected respirator. 			nticipated		
Hand protection	approved star chemical proc essary.	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec- essary. Follow AS/NZS 1337.1				
Eye protection	: Safety glasse	Safety glasses				
Skin and body protection	clothing, long	Protective clothing (e.g. safety shoes, long-sleeved working clothing, long trousers) Follow AS 2210:3				

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	paste
Colour	:	white
Odour	:	slight
Odour Threshold	:	No data available

Sikadur[®]-330 Part A



Versi 1.0	on Revision Date: 30.11.2023		SDS Number: 100000040507	Date of last issue: - Date of first issue: 30.11.2023
	рН	:	No data available	
	Melting point/range / Freezing point	:	No data available	
	Boiling point/boiling range	:	No data available	
	Flash point	:	> 100 °C (212 °F) (Method: closed cup)	
	Evaporation rate	:	No data available	
	Flammability (solid, gas)	:	No data available	
	Upper explosion limit / Upper flammability limit	:	No data available	
	Lower explosion limit / Lower flammability limit	:	No data available	
	Vapour pressure	:	No data available	
	Relative vapour density	:	No data available	
	Density	:	ca. 1.35 g/cm3 (23 °C (73 °F))	
	Solubility(ies) Water solubility	:	No data available	
	Solubility in other solvents	:	No data available	
	Partition coefficient: n- octanol/water	:	No data available	
	Auto-ignition temperature	:	No data available	
	Decomposition temperature	:	No data available	
	Viscosity Viscosity, dynamic	:	No data available	
	Viscosity, kinematic	:	No data available	
	Explosive properties	:	No data available	
	Oxidizing properties	:	No data available	
	Volatile organic compounds	:	Directive 2010/75/EU of 24 Nover emissions (integrated pollution provided the value of the value	evention and control)

Sikadur®-330 Part A



Version 1.0	Revision Date: 30.11.2023		SDS Number: 100000040507	Date of last issue: - Date of first issue: 30.11.2023
SECTIO	N 10. STABILITY AND RE	AC	ΤΙVΙΤΥ	
Rea	activity	:	No dangerous reaction know	own under conditions of normal use.
Che	Chemical stability		The product is chemically	stable.
	Possibility of hazardous reac- tions		Stable under recommende	ed storage conditions.
Cor	nditions to avoid	:	No data available	
Inco	ompatible materials	:	see section 7.	

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity Not classified based on available information.

Components:							
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):							
Acute oral toxicity	: LD50 Oral (Rat): > 5,000 mg/kg						
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 20,000 mg/kg						
1,4-bis(2,3 epoxypropoxy)b Acute oral toxicity	utane: : LD50 Oral (Rat): 1,163 mg/kg						
Solvent naphtha (petroleum), heavy arom.: Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg							
Acute inhalation toxicity	 LC50 (Rat): > 4.7 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhala- tion toxicity 						

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Sikadur®-330 Part A



ersion .0	Revision Date: 30.11.2023	SDS Number: 100000040507	Date of last issue: - Date of first issue: 30.11.2023			
Respi	iratory or skin sensitisati	on				
Skin s	sensitisation					
May c	ause an allergic skin react	ion.				
Respi	iratory sensitisation					
Not cla	assified based on available	e information.				
Chror	nic toxicity					
Germ	cell mutagenicity					
Not classified based on available information.						
Carcinogenicity						
Not classified based on available information.						
Repro	oductive toxicity					
Not cla	assified based on available	e information.				
STOT	- single exposure					
Not cla	assified based on available	e information.				
STOT	- repeated exposure					
Not cla	assified based on available	e information.				
Aspira	ation toxicity					
Not cla	assified based on available	e information.				

Ecotoxicity Componente

<u>Components:</u>						
reaction product: bisphenol- weight ≤ 700):	-A-	(epichlorhydrin); epoxy resin (number average molecular				
Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h				
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1.8 mg/l Exposure time: 48 h				

Solvent naphtha (petroleum), heavy arom .:

Toxicity to daphnia and other	:	EC50 (Daphnia magna (Water flea)): 1.1 mg/l
aquatic invertebrates (Chron-		Exposure time: 48 h
ic toxicity)		

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Sikadur®-330 Part A



Version 1.0	Revision Date: 30.11.2023	SDS Number: 100000040507	Date of last issue: - Date of first issue: 30.11.2023
	ity in soil ta available		
Other	adverse effects		
<u>Produ</u>	<u>ict:</u>		
Addition mation	onal ecological infor- n	: An environmental hazard of unprofessional handling of Toxic to aquatic life with lo	
SECTION	13. DISPOSAL CONSI		

Disposal methods Waste from residues	:	Send to a licensed waste management company.
		The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemi- cal or used container.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product.
		Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR UN/ID No. Proper shipping name Class Packing group Labels Packing instruction (cargo aircraft) Packing instruction (passen- ger aircraft)	 UN 3082 Environmentally hazardous substance, liquid, n.o.s. (epoxy resin) 9 III Miscellaneous 964 964
IMDG-Code UN number Proper shipping name Class	 UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin) 9

Sikadur®-330 Part A



Version 1.0	Revision Date: 30.11.2023		SDS Number: 100000040507		Date of last issue: - Date of first issue: 30.11.2023
Labe EmS	ing group ls Code ne pollutant	: III : 9 : F-, : ye	A, S-F s		
	sport in bulk accordin	-		73/78 and th	ne IBC Code
	onal Regulations	Supplier			
Prope Class Pack Labe	umber er shipping name s ing group	: EN N.9	D.S. poxy resin)	Y HAZARDO	US SUBSTANCE, LIQUID,
Spec	ial precautions for us	er			
The t upon Trans	ransport classification(s the properties of the ur	s) provide Ipackage s may va	d material as it is o	described wit	urposes only, and solely based hin this Safety Data Sheet. ackage sizes, and variations in
SECTION	15. REGULATORY IN	FORMA	ΓΙΟΝ		
Stand	dard for the Uniform duling of Medicines and	: Sc	egulations/legisla hedule 6	tion specifie	c for the substance or mixture
Sche	national Chemical Weap dules of Toxic Chemica bition/Licensing Requin	ls and P	. ,	authoris requiren gens ref	icable no applicable prohibition, ation and restricted use nents, including for carcino- erred to in Schedule 10 of el WHS Act and Regula-

The components of this product are reported in the following inventories: AIIC

: On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date	:	30.11.2023
---------------	---	------------

: dd.mm.yyyy Date format

Sikadur®-330 Part A



Version 1.0	Revision Date: 30.11.2023		SDS Number: 10000040507	Date of last issue: - Date of first issue: 30.11.2023		
Full to	ext of other abbrevia	tions				
AU O	EL	:	Australia. Workplace Exposu taminants.	re Standards for Airborne Con-		
AU O	EL/TWA	:	Exposure standard - time we	ighted average		
ADG		:	Australian Dangerous Goods			
ADR		:	European Agreement concer Dangerous Goods by Road	ning the International Carriage of		
CAS		:	Chemical Abstracts Service			
DNEL		:	Derived no-effect level			
EC50		:	Half maximal effective concentration			
GHS		:	Globally Harmonized System			
IATA		:	International Air Transport As			
IMDG		:	International Maritime Code f			
LD50		:	Median lethal dosis (the amo once, which causes the death test animals)	ount of a material, given all at h of 50% (one half) of a group of		
LC50	LC50 MARPOL			(concentrations of the chemical in inimals during the observation		
MARF				the Prevention of Pollution from he Protocol of 1978		
OEL		:	Occupational Exposure Limit			
PBT		:	Persistent, bioaccumulative a			
PNEC)	:	Predicted no effect concentra	ation		
REAC	CH	:	and of the Council of 18 Dec istration, Evaluation, Authoris	06 of the European Parliament ember 2006 concerning the Reg- sation and Restriction of Chemi- a European Chemicals Agency		
SVHC vPvB	2	:	Substances of Very High Con Very persistent and very bioa	ncern		

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

AU / EN