

# ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A2

|                          |                                      |
|--------------------------|--------------------------------------|
| Owner of the Declaration | Sika Australia Pty Ltd               |
| Publisher                | Institut Bauen und Umwelt e.V. (IBU) |
| Programme holder         | Institut Bauen und Umwelt e.V. (IBU) |
| Declaration number       | EPD-SIK-20250438-CBA1-EN             |
| Issue date               | 22.07.2025                           |
| Valid to                 | 21.07.2030                           |

**SikaPlast®-300 E**

**Sika Australia Pty Ltd**

[www.ibu-epd.com](http://www.ibu-epd.com) | <https://epd-online.com>



## General Information

### Sika Australia Pty Ltd

#### Programme holder

IBU – Institut Bauen und Umwelt e.V.  
Hegelplatz 1  
10117 Berlin  
Germany

#### Declaration number

EPD-SIK-20250438-CBA1-EN

#### This declaration is based on the product category rules:

Concrete admixtures, 01.08.2021  
(PCR checked and approved by the SVR)

#### Issue date

22.07.2025

#### Valid to

21.07.2030



Dipl.-Ing. Hans Peters  
(Chairman of Institut Bauen und Umwelt e.V.)



Florian Pronold  
(Managing Director Institut Bauen und Umwelt e.V.)

### SikaPlast®-300 E

#### Owner of the declaration

Sika Australia Pty Ltd  
Elizabeth Street 55  
2164 Wetherill Park, NSW  
Australia

#### Declared product / declared unit

1 kg of SikaPlast®-300 E with a density of 1.04 kg/l.

#### Scope:

This verified EPD relates to 1 kg of SikaPlast®-300 E. It is manufactured at the plants of Sika Australia Pty Ltd in Wetherill Park (NSW 2164), Keysborough (VIC 3173), Pinkenba (QLD 4008), and Bibra Lake (WA 6163) in Australia. The production and transport data are representative for the year 2024. The results in this EPD are calculated using an LCA-tool verified by IBU in 2025.

The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

The EPD was created according to the specifications of EN 15804+A2. In the following, the standard will be simplified as *EN 15804*.

#### Verification

The standard EN 15804 serves as the core PCR


Independent verification of the declaration and data according to ISO 14025:2011

☐

internally

☒

externally



Matthias Schulz,  
(Independent verifier)

## Product

### Product description/Product definition

SikaPlast®-300 E is an advanced mid-range water reducer, based on an engineered blend of selected polymers. The product is a liquid agent that is introduced into concrete while it is being mixed. Depending on application, the typical dosage can range from 300 ml to 800 ml per 100 kg of total cementitious materials. Optimum dosage should be determined by site trials with the particular concrete mix design and materials. Users shall refer to the most recent Product Data Sheet for more information and advice.

SikaPlast®-300 E is accompanied by a declaration of performance, which conforms to the specifications outlined in Australian Standard AS 1478.1-2000, type MWR. The product is designed to improve the workability, finishability, and slump keeping capacity of fresh concrete; the mechanical properties and durability of hardened concrete. It can be used for most concrete applications including but not limited to precast, pumped, lightweight, and normal weight concrete.

### Application

SikaPlast®-300 E is used as a constituent material to produce concrete. It can be used in combination with other Sika admixtures. All admixtures must be added separately and trials are recommended before use.

### Technical Data

SikaPlast®-300 E meets the requirements of AS 1478.1-2000, type MWR.

### Constructional data

| Name                                                                    | Value     | Unit |
|-------------------------------------------------------------------------|-----------|------|
| pH of admixture (AS 1478.1)                                             | 3.5–5.5   | -    |
| Relative density of admixture (AS 1478.1)                               | 1.02–1.06 | kg/l |
| Non-volatile content of admixture (AS 1478.1)                           | 20.5–23.5 | %    |
| Chloride content of admixture (AS 1478.1)                               | ≤ 1.5     | g/l  |
| Water content of concrete as % of control (AS 1478.1)                   | 85–90     | %    |
| Initial setting time of concrete, deviation from control (AS 1012.18)   | -1 to +1  | hour |
| Final setting time of concrete, deviation from control (AS 1012.18)     | -1 to +1  | hour |
| Compressive strength of concrete as % of control at 3 days (AS 1012.9)  | ≥ 115     | %    |
| Compressive strength of concrete as % of control at 7 days (AS 1012.9)  | ≥ 115     | %    |
| Compressive strength of concrete as % of control at 28 days (AS 1012.9) | ≥ 110     | %    |
| Compressive strength of concrete as % of control at 90 days (AS 1012.9) | ≥ 105     | %    |

Additional technical data are not relevant for this product.

### Base materials/Ancillary materials

The raw materials and additives of SikaPlast®-300 E can be given as follows:

| Name                   | Value | Unit |
|------------------------|-------|------|
| Polycarboxylate(s) (*) | 25–50 | %    |
| Water                  | 45–70 | %    |
| Additives              | < 10  | %    |

(\*) Solid content of 50 %

With respect to international and local regulations:

- This product/article/at least one partial article contains substances listed in the 'Candidate List of Substances of Very High Concern (SVHC) for Authorisation' (date: 11/06/2025) exceeding 0.1 percentage by mass: No.
- Biocide products were added to this construction product or it has been treated with biocide products (this then concerns a treated product as defined by the (EU) Ordinance on Biocide Products No. 528/2012): Yes. The active substance in the biocide is octhilinone. The biocide was used as an in-can preservative.
- Any applicable prohibition, authorisation and restricted use requirements for this product, including for carcinogens referred to in Schedule 10 of the Australian Model Work Health and Safety Regulations (WHS): No.

### Reference service life

The durability of concrete admixtures is normally at least as long as the lifetime of the building in which it is used. The experimental data show that the reference life is greater than 50 years. The documentation of the Reference service life is not required for the EPDs calculated using the EPD tool from Sika since the entire life cycle is not declared. Only modules A1-A3, A4, A5, C1, C2, C3, C4, and D are considered.

## LCA: Calculation rules

### Declared Unit

The EPD refers to the declared unit of 1 kg of concrete admixture applied into the building with a density of 1.04 g/ml in accordance with *IBU PCR 04-2023 Part B* for concrete admixtures.

### Declared unit and mass reference

| Name          | Value | Unit              |
|---------------|-------|-------------------|
| Declared unit | 1     | kg                |
| Gross density | 1040  | kg/m <sup>3</sup> |

### System boundary

Declaration type with respect to life cycle stages covered according to clause 5.2 EN 15804+A2 is cradle to gate with modules C1–C4 and module D (A1–A3, A4, A5, C and D).

Modules taken into account:

- A1 Production of preliminary products
- A2 Transport to the plant
- A3 Production including provision of energy, production of auxiliaries and consumables and waste treatment
- A4 Transport from the construction site to the installation site
- A5 Installation, admixtures applied into the building during A5 phase operations. At this stage, an impact of the production and treatment of installation residue equal to 1 % of the product and the impact related to the packaging end-of-life treatment is considered.
- C1-C2-C3-C4-D

The building deconstruction (demolition process) takes place in C1 module which considers energy production and consumption in terms of diesel and all the emissions connected with the fuel-burning process. After the demolition, the admixture is transported to the end-of-life processing (C2 module) where all the impacts related to the transport

processes are considered.

One scenario is considered for the final treatment of the waste:

- 100 % disposal (C4), modelled by landfill process where admixtures end their life cycle.

Module D accounts for benefits that are beyond the defined system boundaries. Credits are generated during the incineration of the installation scrap and packaging in module A5.

### Geographic Representativeness

Land or region, in which the declared product system is manufactured, used or handled at the end of the product's lifespan: Australia

### Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account. Sphera *LCA for Expert* software (former GaBi) (version 10) and *Managed LCA Content* (2024.1) have been used.

## LCA: Scenarios and additional technical information

### Characteristic product properties of biogenic carbon

#### Information on describing the biogenic carbon content at factory gate

| Name                                              | Value  | Unit |
|---------------------------------------------------|--------|------|
| Biogenic carbon content in product                | 0.0043 | kg C |
| Biogenic carbon content in accompanying packaging | -      | kg C |

Note: 1 kg of biogenic carbon is equivalent to 44/12 kg of CO<sub>2</sub>.

For the preparation of building life cycle assessments, it must be taken into account that in modules A5 (installation in the building) and C4 (disposal) the biogenic amount of CO<sub>2</sub> of the packaging and product bound in modules A1-A3 is mathematically booked out.

The emission factor for electricity used in production is: 0.796 kg CO<sub>2</sub> eq/kWh.

### Transport from the gate to the site (A4)

| Name               | Value | Unit |
|--------------------|-------|------|
| Transport distance | 223   | km   |
| Gross weight       | 34–40 | t    |
| Payload capacity   | 27    | t    |

### Assembly (A5)

| Name            | Value | Unit |
|-----------------|-------|------|
| Material loss   | 0.01  | kg   |
| Other resources | -     | kg   |

Material loss regards the amount of product not used during the application phase into the building. This amount is 1 % of the product, impacts related to the production of this part are charged to the A5 module. This percentage is considered as waste to incineration since the product has a calorific value and impacts of its end of life have been considered in the LCA model and declared in A5.

### End of life (C1-C4)

C1: This module considers the use of machinery (7.5E-5 kg of diesel for kg handled) to dismantle the product to enable its subsequent transport.

C2: The concrete demolition waste is transported from the building site to a treatment plant or disposal site by truck and an average distance of 50 km is considered.

C4: The results for the end-of-life are declared for one scenario:

| Name                                  | Value | Unit |
|---------------------------------------|-------|------|
| Collected as mixed construction waste | 1     | kg   |
| Landfill percentage                   | 100   | %    |
| Material to landfill                  | 1     | kg   |

## LCA: Results

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

| Product stage       |           |               | Construction process stage          |          | Use stage |             |        |             |               |                        |                       | End of life stage          |           |                  |          | Benefits and loads beyond the system boundaries |
|---------------------|-----------|---------------|-------------------------------------|----------|-----------|-------------|--------|-------------|---------------|------------------------|-----------------------|----------------------------|-----------|------------------|----------|-------------------------------------------------|
| Raw material supply | Transport | Manufacturing | Transport from the gate to the site | Assembly | Use       | Maintenance | Repair | Replacement | Refurbishment | Operational energy use | Operational water use | De-construction demolition | Transport | Waste processing | Disposal | Reuse-Recovery-Recycling-potential              |
| A1                  | A2        | A3            | A4                                  | A5       | B1        | B2          | B3     | B4          | B5            | B6                     | B7                    | C1                         | C2        | C3               | C4       | D                                               |
| X                   | X         | X             | X                                   | X        | MND       | MND         | MNR    | MNR         | MNR           | MND                    | MND                   | X                          | X         | X                | X        | X                                               |

### RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 kg SikaPlast®-300 E

| Parameter      | Unit                             | A1-A3    | A4       | A5       | C1       | C2       | C3 | C4       | D         |
|----------------|----------------------------------|----------|----------|----------|----------|----------|----|----------|-----------|
| GWP-total      | kg CO <sub>2</sub> eq            | 6.17E-01 | 1.8E-02  | 1.73E-02 | 2.84E-04 | 7.27E-03 | 0  | 3.75E-02 | -1.86E-03 |
| GWP-fossil     | kg CO <sub>2</sub> eq            | 6.22E-01 | 1.8E-02  | 1.15E-02 | 2.84E-04 | 7.27E-03 | 0  | 2.15E-02 | -1.85E-03 |
| GWP-biogenic   | kg CO <sub>2</sub> eq            | -8.7E-03 | 8.57E-06 | 5.8E-03  | 1.35E-07 | 3.46E-06 | 0  | 1.6E-02  | -1.47E-05 |
| GWP-luluc      | kg CO <sub>2</sub> eq            | 4.29E-03 | 8.21E-07 | 4.35E-05 | 1.3E-08  | 3.31E-07 | 0  | 1E-05    | -2.56E-07 |
| ODP            | kg CFC11 eq                      | 3.7E-10  | 1.11E-15 | 3.7E-12  | 1.76E-17 | 4.49E-16 | 0  | 5.2E-14  | -3.63E-14 |
| AP             | mol H <sup>+</sup> eq            | 2.43E-03 | 6.05E-05 | 3.14E-05 | 3.62E-06 | 2.44E-05 | 0  | 1.29E-04 | -3.21E-06 |
| EP-freshwater  | kg P eq                          | 3.91E-06 | 2.18E-09 | 3.97E-08 | 3.45E-11 | 8.81E-10 | 0  | 3.91E-08 | -6.66E-09 |
| EP-marine      | kg N eq                          | 7.34E-04 | 2.93E-05 | 1.01E-05 | 1.66E-06 | 1.17E-05 | 0  | 3.2E-05  | -8.25E-07 |
| EP-terrestrial | mol N eq                         | 8.01E-03 | 3.23E-04 | 1.14E-04 | 1.82E-05 | 1.3E-04  | 0  | 3.51E-04 | -8.67E-06 |
| POCP           | kg NMVOC eq                      | 2.12E-03 | 5.91E-05 | 2.83E-05 | 4.98E-06 | 2.39E-05 | 0  | 9.84E-05 | -2.21E-06 |
| ADPE           | kg Sb eq                         | 1.04E-07 | 2.75E-10 | 1.07E-09 | 4.34E-12 | 1.11E-10 | 0  | 2.21E-09 | -3.05E-10 |
| ADPF           | MJ                               | 1.48E+01 | 2.4E-01  | 1.57E-01 | 3.78E-03 | 9.67E-02 | 0  | 3.28E-01 | -3.75E-02 |
| WDP            | m <sup>3</sup> world eq deprived | 1.92E-01 | 7.58E-05 | 3.11E-03 | 1.2E-06  | 3.06E-05 | 0  | 1.18E-03 | -4.43E-04 |

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources; WDP = Water (user) deprivation potential)

### RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 kg SikaPlast®-300 E

| Parameter | Unit           | A1-A3    | A4       | A5       | C1       | C2       | C3 | C4       | D         |
|-----------|----------------|----------|----------|----------|----------|----------|----|----------|-----------|
| PERE      | MJ             | 9.88E-01 | 8.05E-04 | 1.22E-02 | 1.27E-05 | 3.25E-04 | 0  | 4.06E-02 | -2.43E-02 |
| PERM      | MJ             | 1.76E-01 | 0        | 0        | 0        | 0        | 0  | 0        | 0         |
| PERT      | MJ             | 1.16E+00 | 8.05E-04 | 1.22E-02 | 1.27E-05 | 3.25E-04 | 0  | 4.06E-02 | -2.43E-02 |
| PENRE     | MJ             | 9.58E+00 | 2.4E-01  | 1.57E-01 | 3.78E-03 | 9.67E-02 | 0  | 3.28E-01 | -3.75E-02 |
| PENRM     | MJ             | 5.25E+00 | 0        | 0        | 0        | 0        | 0  | 0        | 0         |
| PENRT     | MJ             | 1.48E+01 | 2.4E-01  | 1.57E-01 | 3.78E-03 | 9.67E-02 | 0  | 3.28E-01 | -3.75E-02 |
| SM        | kg             | 0        | 0        | 0        | 0        | 0        | 0  | 0        | 0         |
| RSF       | MJ             | 0        | 0        | 0        | 0        | 0        | 0  | 0        | 0         |
| NRSF      | MJ             | 0        | 0        | 0        | 0        | 0        | 0  | 0        | 0         |
| FW        | m <sup>3</sup> | 5.5E-03  | 2.03E-06 | 8.28E-05 | 3.2E-08  | 8.19E-07 | 0  | 4.23E-05 | -1.86E-05 |

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

### RESULTS OF THE LCA - WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2:

1 kg SikaPlast®-300 E

| Parameter | Unit | A1-A3    | A4       | A5       | C1       | C2       | C3 | C4       | D         |
|-----------|------|----------|----------|----------|----------|----------|----|----------|-----------|
| HWD       | kg   | 2.3E-09  | 4.77E-12 | 2.45E-11 | 7.53E-14 | 1.92E-12 | 0  | 8.09E-11 | -4.86E-11 |
| NHWD      | kg   | 4.56E-02 | 9.67E-06 | 2.27E-03 | 1.53E-07 | 3.9E-06  | 0  | 1E+00    | -2.87E-05 |
| RWD       | kg   | 1.75E-04 | 9.53E-08 | 1.93E-06 | 1.51E-09 | 3.85E-08 | 0  | 3.48E-06 | -5.37E-06 |
| CRU       | kg   | 0        | 0        | 0        | 0        | 0        | 0  | 0        | 0         |
| MFR       | kg   | 0        | 0        | 0        | 0        | 0        | 0  | 0        | 0         |
| MER       | kg   | 0        | 0        | 0        | 0        | 0        | 0  | 0        | 0         |
| EEE       | MJ   | 9.21E-04 | 0        | 1.93E-02 | 0        | 0        | 0  | 0        | 0         |
| EET       | MJ   | 0        | 0        | 3.49E-03 | 0        | 0        | 0  | 0        | 0         |

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy



**RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional:  
1 kg SikaPlast®-300 E**

| Parameter | Unit              | A1-A3    | A4       | A5       | C1       | C2       | C3 | C4       | D         |
|-----------|-------------------|----------|----------|----------|----------|----------|----|----------|-----------|
| PM        | Disease incidence | 4.53E-08 | 4.24E-10 | 4.97E-10 | 1.94E-10 | 1.88E-10 | 0  | 1.47E-09 | -2.68E-11 |
| IR        | kBq U235 eq       | 1.57E-02 | 6.62E-06 | 1.72E-04 | 1.05E-07 | 2.67E-06 | 0  | 3.35E-04 | -8.84E-04 |
| ETP-fw    | CTUe              | 6.91E+00 | 2.82E-01 | 7.47E-02 | 4.46E-03 | 1.14E-01 | 0  | 1.54E-01 | -9.79E-03 |
| HTP-c     | CTUh              | 1.09E-09 | 4.43E-12 | 1.15E-11 | 7E-14    | 1.79E-12 | 0  | 3.57E-12 | -5.75E-13 |
| HTP-nc    | CTUh              | 1.15E-07 | 8.61E-11 | 1.21E-09 | 1.39E-12 | 3.47E-11 | 0  | 1.09E-10 | -9.49E-12 |
| SQP       | SQP               | 9.04E-01 | 5.89E-04 | 9.98E-03 | 9.31E-06 | 2.38E-04 | 0  | 2.94E-02 | -1.42E-02 |

PM = Potential incidence of disease due to PM emissions; IR = Potential Human exposure efficiency relative to U235; ETP-fw = Potential comparative Toxic Unit for ecosystems; HTP-c = Potential comparative Toxic Unit for humans (cancerogenic); HTP-nc = Potential comparative Toxic Unit for humans (not cancerogenic); SQP = Potential soil quality index

Disclaimer 1 – for the indicator 'Potential Human exposure efficiency relative to U235'. This impact category deals mainly with the eventual impact of low-dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure or radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, radon and from some construction materials is also not measured by this indicator.

Disclaimer 2 – for the indicators 'abiotic depletion potential for non-fossil resources', 'abiotic depletion potential for fossil resources', 'water (user) deprivation potential, deprivation-weighted water consumption', 'potential comparative toxic unit for ecosystems', 'potential comparative toxic unit for humans – cancerogenic', 'Potential comparative toxic unit for humans - not cancerogenic', 'potential soil quality index'. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high as there is limited experience with the indicator. This EPD was created using a software tool.

## References

### AS 1012.9:2014

Methods of testing concrete - Method 9: Determination of the compressive strength of concrete specimens

### AS 1012.18-1996 (R-2014)

Methods of testing concrete - Method 18: Determination of setting time of fresh concrete, mortar and grout by penetration resistance

### AS 1478.1-2000

Chemical admixtures for concrete, mortar and grout - Part 1: Admixtures for concrete

### Candidate List of SVHC

Candidate List of Substances of Very High Concern for Authorisation, European Chemicals Agency (ECHA), 2025, <https://echa.europa.eu/candidate-list-table>

### EN 15804:2012+A2:2019+AC:2021

Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products

### ISO 14025:2011

Environmental labels and declarations — Type III environmental declarations — Principles and procedures

### Model WHS Regulations

Schedule 10 Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals, Australian Model Work Health and Safety Regulations, 08-2023

### Further References

### IBU General Instructions

General Instructions for the EPD programme of Institut Bauen und Umwelt e.V., Version 2.1, Berlin: Institut Bauen und Umwelt e.V., 2022, [www.ibu-epd.com](http://www.ibu-epd.com)

### LCA Calculator

LCA Calculator software, by Sphera Solutions GmbH, Leinfelden-Echterdingen, 2025

### LCA for Expert

Life cycle assessment software (version 10), by Sphera Solutions GmbH, Leinfelden-Echterdingen, 2022, <https://sphera.com/life-cycle-assessment-lca-software/>

### Managed LCA Content

Life Cycle Assessment databases, Sphera Solutions GmbH, Leinfelden-Echterdingen, 2024, <https://lcadatabase.sphera.com/>

### PCR Part A

PCR - Part A: Calculation rules for the Life Cycle Assessment and Requirements on the Background Report, version 1.4, Institut Bauen und Umwelt e.V., 04-2024

### PCR Part B

PCR – Part B: Requirements on the EPD for Concrete admixtures, Institut Bauen und Umwelt e.V., 04-2023

### VKF Fire Protection Clarification

Assessment of Fire Compartment Sizes, Appendix D, Association of Cantonal Fire Insurers [Brandschutzerläuterung: Bewertung Brandabschnittsgrößen, Anhang D, Vereinigung Kantonalen Feuerversicherungen - VKF], 12-2007



**Publisher**

Institut Bauen und Umwelt e.V.  
Hegelplatz 1  
10117 Berlin  
Germany

+49 (0)30 3087748- 0  
info@ibu-epd.com  
www.ibu-epd.com



**Programme holder**

Institut Bauen und Umwelt e.V.  
Hegelplatz 1  
10117 Berlin  
Germany

+49 (0)30 3087748- 0  
info@ibu-epd.com  
www.ibu-epd.com



**Author of the Life Cycle Assessment**

Sphera Solutions GmbH  
Hauptstraße 111- 113  
70771 Leinfelden-Echterdingen  
Germany

+49 (0)711 341817-0  
info@sphera.com  
www.sphera.com

**Owner of the Declaration**

Sika Australia Pty Ltd  
Elizabeth Street 55  
2164 Wetherill Park, NSW  
Australia

+61 2 9725 1145  
sustainability@au.sika.com  
aus.sika.com