

## PRODUCT DATA SHEET

# SikaCeram<sup>®</sup>-960 Epoxy Finish

## Washing aid for epoxy joint grouting

### DESCRIPTION

SikaCeram<sup>®</sup>-960 Epoxy Finish is a powder concentrate to be added to the wash water after grouting tiles with epoxy resin. It removes residual epoxy grout haze.

### USES

SikaCeram<sup>®</sup>-960 Epoxy Finish is used as an added cleaning solution added to the wash water when using epoxy grouting.

Please note:

- The Product may be used for interior and exterior applications.
- The Product may only be used by experienced professionals.

### FEATURES

- Assist with easy removes epoxy grout haze
- Easy to handle and use
- Simply add the powder to the wash water

### PRODUCT INFORMATION

<b>Packaging</b>	750 g plastic container Refer to the current price list for available packaging variations.
<b>Colour</b>	White
<b>Shelf life</b>	18 months from date of production
<b>Storage conditions</b>	The Product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between 0 °C and +30 °C. Always refer to the packaging. Refer to the current Safety Data Sheet for information on safe handling and storage.
<b>Appearance</b>	Powder

### TECHNICAL INFORMATION

<b>Temperature resistance</b>	Maximum	+80 °C
	Minimum	-20 °C

## APPLICATION INFORMATION

Mixing ratio	1 : 100	
Yield	75–150 m <sup>2</sup> per container Note: Consumption data is theoretical and does not allow for any additional material due to surface porosity, surface profile, variations in level, wastage or any other variations. Apply the Product to a test area to calculate the exact consumption for the specific substrate conditions and proposed application equipment.	
Substrate temperature	Maximum	+25°C
	Minimum	+10°C

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

## APPLICATION INSTRUCTIONS

### EQUIPMENT

- Sponge float
- Bucket with rollers
- Grout finishing tool

### MIXING

1. Follow the mixing ratio of 1 : 100, for example, 50 g of Product to 5 litres of water.
2. Measure out the Product and pour into a bucket of clean water.
3. Stir manually using a clean tool.

## APPLICATION

### IMPORTANT

#### Risk of staining on natural stone

Using the Product on natural stone may result in surface staining.

1. Do not use the Product in combination with natural stone.
2. Apply on a test area if in doubt.

#### Protect the Product from moisture

Note:

1. Reseal open containers.

Preconditions

Observe information such as waiting times in the Product Data Sheet of the joint grouting product.

1. Use a sponge float to wash the surface of the tiles.
2. IMPORTANT Rinse the sponge and change the wash water frequently. Remove any smears or remaining haze.
3. Allow the surface to dry.
4. Repeat the cleaning process if there is any remaining epoxy grout haze.

### CLEANING OF EQUIPMENT

Clean all tools and application equipment with water immediately after use. Hardened material can only be removed mechanically.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**Sika Australia Pty Limited**

ABN 12 001 342 329

[aus.sika.com](http://aus.sika.com)

Tel: 1300 22 33 48

**Product Data Sheet**

SikaCeram®-960 Epoxy Finish

December 2025, Version 01.01

02179060000000052

SikaCeram-960EpoxyFinish-en-AU-(12-2025)-1-1.pdf

