

# SAFETY DATA SHEET

## SikaTack®-Panel



Version  
3.0

Revision Date:  
18.10.2024

SDS Number:  
000000019870

Date of last issue: 07.07.2022  
Date of first issue: 12.02.2021

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SikaTack®-Panel

#### Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.  
55 Elizabeth Street  
Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45

Emergency telephone number : +61 1800 033 111

Telefax : +61 2 9725 33 30

#### Recommended use of the chemical and restrictions on use

Product use : Sealant/adhesive, For professional users only.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Flammable liquids : Category 4

Serious eye damage/eye irritation : Category 2A

Skin sensitisation : Category 1

Short-term (acute) aquatic hazard : Category 3

#### GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H227 Combustible liquid.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H402 Harmful to aquatic life.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing mist or vapours.

# SAFETY DATA SHEET

## SikaTack®-Panel



Version  
3.0

Revision Date:  
18.10.2024

SDS Number:  
000000019870

Date of last issue: 07.07.2022  
Date of first issue: 12.02.2021

P264 Wash skin thoroughly after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

### Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### Storage:

P403 Store in a well-ventilated place.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards which do not result in classification

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

| Chemical name   | CAS-No.     | Concentration (% w/w) |
|---|-------------|-----------------------|
| Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-  | 77703-56-1  | >= 2.5 -< 10          |
| xylene  | 1330-20-7   | >= 0.25 -< 2.5        |
| calcium oxide   | 1305-78-8   | >= 1 -< 3             |
| 4,4'-methylenediphenyl diisocyanate   | 101-68-8    | 0 -< 1                |
| Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane | 252047-49-7 | >= 0.25 -< 2.5        |
| 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate                                       | 4098-71-9   | >= 0.025 -< 0.25      |
| dibutyltin dichloride   | 683-18-1    | >= 0.0025 -< 0.025    |

## SECTION 4. FIRST AID MEASURES

# SAFETY DATA SHEET

## SikaTack®-Panel



|                |                              |                             |   |
|----------------|------------------------------|-----------------------------|---|
| Version<br>3.0 | Revision Date:<br>18.10.2024 | SDS Number:<br>000000019870 | Date of last issue: 07.07.2022<br>Date of first issue: 12.02.2021 |
|----------------|------------------------------|-----------------------------|---|

- |   |   |
|---|---|
| General advice  | : Move out of dangerous area.<br>Consult a physician.<br>Show this safety data sheet to the doctor in attendance.   |
| If inhaled  | : Move to fresh air.<br>Consult a physician after significant exposure.   |
| In case of skin contact                                     | : Take off contaminated clothing and shoes immediately.<br>Wash off with soap and plenty of water.<br>If symptoms persist, call a physician.  |
| In case of eye contact                                      | : Immediately flush eye(s) with plenty of water.<br>Remove contact lenses.<br>Keep eye wide open while rinsing.<br>If eye irritation persists, consult a specialist.  |
| If swallowed  | : Clean mouth with water and drink afterwards plenty of water.<br>Do not give milk or alcoholic beverages.<br>Never give anything by mouth to an unconscious person.<br>Obtain medical attention.   |
| Most important symptoms and effects, both acute and delayed | : irritant effects<br>sensitising effects<br>Allergic reactions<br>Excessive lachrymation<br>See Section 11 for more detailed information on health effects and symptoms.<br>May cause an allergic skin reaction.<br>Causes serious eye irritation. |
| Notes to physician  | : Treat symptomatically.  |

### SECTION 5. FIREFIGHTING MEASURES

- |   |  |
|---|--|
| Suitable extinguishing media                  | : Carbon dioxide (CO <sub>2</sub> )                              |
| Unsuitable extinguishing media                | : Water  |
| Hazardous combustion products                 | : No hazardous combustion products are known                     |
| Specific extinguishing methods                | : Standard procedure for chemical fires.                         |
| Special protective equipment for firefighters | : In the event of fire, wear self-contained breathing apparatus. |

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- |   |   |
|---|---|
| Personal precautions, protective equipment and emergency measures | : Use personal protective equipment.<br>Deny access to unprotected persons. |
|---|---|

# SAFETY DATA SHEET

## SikaTack®-Panel



Version  
3.0

Revision Date:  
18.10.2024

SDS Number:  
000000019870

Date of last issue: 07.07.2022  
Date of first issue: 12.02.2021

gency procedures

Environmental precautions : Do not flush into surface water or sanitary sewer system.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.  
Keep in a well-ventilated place.  
Observe label precautions.  
Store in accordance with local regulations.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

| Components                          | CAS-No.   | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis  |
|-------------------------------------|-----------|-------------------------------|--|--------|
| xylene                              | 1330-20-7 | STEL                          | 150 ppm<br>655 mg/m <sup>3</sup>               | AU OEL |
|                                     |           | TWA                           | 80 ppm<br>350 mg/m <sup>3</sup>                | AU OEL |
| calcium oxide                       | 1305-78-8 | TWA                           | 2 mg/m <sup>3</sup>                            | AU OEL |
| 4,4'-methylenediphenyl diisocyanate | 101-68-8  | TWA                           | 0.02 mg/m <sup>3</sup><br>(NCO)                | AU OEL |

# SAFETY DATA SHEET

## SikaTack®-Panel



Version  
3.0

Revision Date:  
18.10.2024

SDS Number:  
000000019870

Date of last issue: 07.07.2022  
Date of first issue: 12.02.2021

|   |  |      |                              |        |
|---|--|------|------------------------------|--------|
|   | Further information: Category 2 (Carc. 2) Suspected human carcinogen, Sensitiser |      |                              |        |
|   |  | STEL | 0.07 mg/m <sup>3</sup> (NCO) | AU OEL |
| 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate | 4098-71-9  | TWA  | 0.02 mg/m <sup>3</sup> (NCO) | AU OEL |
|   | Further information: Sensitiser  |      |                              |        |
|   |  | STEL | 0.07 mg/m <sup>3</sup> (NCO) | AU OEL |

### Biological occupational exposure limits

| Components | CAS-No.   | Control parameters   | Biological specimen | Sampling time  | Permissible concentration | Basis     |
|------------|-----------|----------------------|---------------------|--|---------------------------|-----------|
| xylene     | 1330-20-7 | Methylhippuric acids | Urine               | End of shift (As soon as possible after exposure ceases) | 1.5 g/g creatinine        | ACGIH BEI |

**Appropriate engineering controls** : Use adequate ventilation and/or engineering controls to prevent exposure to vapours.

### Personal protective equipment

**Respiratory protection** : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  
Follow AS/NZS 1337.1  
Recommended: Butyl rubber/nitrile rubber gloves.  
Contaminated gloves should be removed.

**Eye protection** : Safety glasses

**Skin and body protection** : Protective clothing (e.g. safety shoes, long-sleeved working clothing, long trousers)  
Follow AS 2210:3  
Protective clothing needs to be made of cotton.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** : paste

**Colour** : beige

**Odour** : characteristic

# SAFETY DATA SHEET

## SikaTack®-Panel



Version  
3.0

Revision Date:  
18.10.2024

SDS Number:  
000000019870

Date of last issue: 07.07.2022  
Date of first issue: 12.02.2021

|  |   |  |
|--|---|--|
| Odour Threshold                                  | : | No data available  |
| pH   | : | No data available  |
| Melting point/ range / Freezing point            | : | No data available  |
| Boiling point/boiling range                      | : | No data available  |
| Flash point                                      | : | ca. 80 °C (176 °F)<br>(Method: closed cup)   |
| Evaporation rate                                 | : | No data available  |
| Flammability (solid, gas)                        | : | No data available  |
| Upper explosion limit / Upper flammability limit | : | No data available  |
| Lower explosion limit / Lower flammability limit | : | No data available  |
| Vapour pressure                                  | : | 0.01 hPa   |
| Relative vapour density                          | : | No data available  |
| Density  | : | ca. 1.15 g/cm <sup>3</sup> (20 °C (68 °F))   |
| Solubility(ies)                                  |   |  |
| Water solubility                                 | : | insoluble  |
| Solubility in other solvents                     | : | No data available  |
| Partition coefficient: n-octanol/water           | : | No data available  |
| Auto-ignition temperature                        | : | No data available  |
| Decomposition temperature                        | : | No data available  |
| Viscosity  |   |  |
| Viscosity, dynamic                               | : | No data available  |
| Viscosity, kinematic                             | : | > 20.5 mm <sup>2</sup> /s ( 40 °C (104 °F))  |
| Explosive properties                             | : | No data available  |
| Oxidizing properties                             | : | No data available  |
| Volatile organic compounds                       | : | Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)<br>Volatile organic compounds (VOC) content: 3.1% w/w |

# SAFETY DATA SHEET

## SikaTack®-Panel



Version  
3.0

Revision Date:  
18.10.2024

SDS Number:  
000000019870

Date of last issue: 07.07.2022  
Date of first issue: 12.02.2021

---

### SECTION 10. STABILITY AND REACTIVITY

|                                    |   |
|------------------------------------|---|
| Reactivity                         | : No dangerous reaction known under conditions of normal use. |
| Chemical stability                 | : The product is chemically stable.                           |
| Possibility of hazardous reactions | : No hazards to be specially mentioned.                       |
| Conditions to avoid                | : No data available   |
| Incompatible materials             | : see section 7.  |
| Hazardous decomposition products   | : No decomposition if stored and applied as directed.         |

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **xylene:**

Acute oral toxicity : LD50 Oral (Rat): 3,523 mg/kg

##### **4,4'-methylenediphenyl diisocyanate:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1.5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgement

##### **3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:**

Acute oral toxicity : LD50 Oral (Rat): 4,814 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.031 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): > 7,000 mg/kg

##### **dibutyltin dichloride:**

Acute oral toxicity : LD50 Oral (Rat): 219 mg/kg

#### **Skin corrosion/irritation**

Not classified based on available information.

# SAFETY DATA SHEET

## SikaTack®-Panel



Version  
3.0

Revision Date:  
18.10.2024

SDS Number:  
000000019870

Date of last issue: 07.07.2022  
Date of first issue: 12.02.2021

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

#### Respiratory sensitisation

Not classified based on available information.

### Chronic toxicity

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### Aspiration toxicity

Not classified based on available information.

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### **Urea,N,N''-(methylenedi-4,1-phenylene)bis[N'-butyl-:**

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EC50 (Raphidocelis subcapitata (freshwater green alga)): >  
plants 100 mg/l  
Exposure time: 72 h

##### **xylene:**

Toxicity to fish (Chronic tox- : NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l  
icity) Exposure time: 56 d

Toxicity to daphnia and other : NOEC (Daphnia (water flea)): 1.17 mg/l  
aquatic invertebrates (Chron- Exposure time: 7 d



# SAFETY DATA SHEET

## SikaTack®-Panel



Version  
3.0

Revision Date:  
18.10.2024

SDS Number:  
000000019870

Date of last issue: 07.07.2022  
Date of first issue: 12.02.2021

ic toxicity)

**Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane:**

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

**dibutyltin dichloride:**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 1.4 mg/l  
Exposure time: 48 h

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 10

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

**Product:**

Additional ecological information : There is no data available for this product.

## SECTION 13. DISPOSAL CONSIDERATIONS

**Disposal methods**

Waste from residues : Send to a licensed waste management company.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.

Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

# SAFETY DATA SHEET

## SikaTack®-Panel



Version  
3.0

Revision Date:  
18.10.2024

SDS Number:  
000000019870

Date of last issue: 07.07.2022  
Date of first issue: 12.02.2021

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

UN/ID No. : Not applicable  
Proper shipping name : Not applicable  
Class : Not applicable  
Subsidiary risk : Not applicable  
Packing group : Not applicable  
Labels : Not applicable  
Packing instruction (cargo aircraft) : Not applicable  
Packing instruction (passenger aircraft) : Not applicable

##### IMDG-Code

UN number : Not applicable  
Proper shipping name : Not applicable  
Class : Not applicable  
Subsidiary risk : Not applicable  
Packing group : Not applicable  
Labels : Not applicable  
EmS Code : Not applicable  
Marine pollutant : Not applicable

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### National Regulations

##### ADG

UN number : Not applicable  
Proper shipping name : Not applicable  
Class : Not applicable  
Subsidiary risk : Not applicable  
Packing group : Not applicable  
Labels : Not applicable  
Hazchem Code : Not applicable

#### Special precautions for user

Not applicable

### SECTION 15. REGULATORY INFORMATION

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

Therapeutic Goods (Poisons Standard) Instrument : No poison schedule number allocated

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors  
Prohibition/Licensing Requirements : There is no applicable prohibition,

# SAFETY DATA SHEET

## SikaTack®-Panel



Version  
3.0

Revision Date:  
18.10.2024

SDS Number:  
000000019870

Date of last issue: 07.07.2022  
Date of first issue: 12.02.2021

authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.

### The components of this product are reported in the following inventories:

AIIC : On the inventory, or in compliance with the inventory

## SECTION 16. OTHER INFORMATION

Revision Date : 18.10.2024  
Date format : dd.mm.yyyy

### Full text of other abbreviations

ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.  
AU OEL / TWA : Exposure standard - time weighted average  
AU OEL / STEL : Exposure standard - short term exposure limit  
ADG : Australian Dangerous Goods Code.  
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road  
CAS : Chemical Abstracts Service  
DNEL : Derived no-effect level  
EC50 : Half maximal effective concentration  
GHS : Globally Harmonized System  
IATA : International Air Transport Association  
IMDG : International Maritime Code for Dangerous Goods  
LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)  
LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)  
MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978  
OEL : Occupational Exposure Limit  
PBT : Persistent, bioaccumulative and toxic  
PNEC : Predicted no effect concentration  
REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency  
SVHC : Substances of Very High Concern  
vPvB : Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: [aus.sika.com](http://aus.sika.com)

# SAFETY DATA SHEET

## SikaTack®-Panel



Version  
3.0

Revision Date:  
18.10.2024

SDS Number:  
000000019870

Date of last issue: 07.07.2022  
Date of first issue: 12.02.2021

---

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

AU / EN