## Sikaflex®-221



Version **Revision Date:** SDS Number: Date of last issue: 27.03.2023 12.05.2025 000000601552 Date of first issue: 21.12.2015 4.0

### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : Sikaflex®-221

Manufacturer or supplier's details

Sika Australia Pty. Ltd. Company

55 Elizabeth Street

Wetherill Park, NSW 2164

+61 2 9725 11 45 Telephone

Emergency telephone number: +61 1800 033 111

Telefax +61 2 9725 33 30

Recommended use of the chemical and restrictions on use

: Sealant/adhesive Product use

### **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Flammable liquids Category 4

repeated exposure (Inhala-

tion)

Specific target organ toxicity - : Category 2 (Central nervous system)

### **GHS** label elements

Hazard pictograms



Signal word Warning

H227 Combustible liquid. Hazard statements

H373 May cause damage to organs (Central nervous system)

through prolonged or repeated exposure if inhaled.

Precautionary statements Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking. P260 Do not breathe mist or vapours.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection/ hearing protection.

# Sikaflex®-221



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.03.2023

 4.0
 12.05.2025
 000000601552
 Date of first issue: 21.12.2015

Response:

P314 Get medical advice/ attention if you feel unwell. P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P403 Store in a well-ventilated place.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards which do not result in classification

None known.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-	77703-56-1	>= 2.5 -< 10
butyl-		
xylene	1330-20-7	>= 0.25 -< 2.5
Stoddard solvent	8052-41-3	>= 1 -< 2.5
4,4'-methylenediphenyl diisocyanate	101-68-8	0 -< 1

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

## Sikaflex®-221



Date of last issue: 27.03.2023 Version Revision Date: SDS Number: 12.05.2025 000000601552 Date of first issue: 21.12.2015 4.0

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

No known significant effects or hazards.

See Section 11 for more detailed information on health effects

and symptoms.

May cause damage to organs through prolonged or repeated

exposure if inhaled.

Notes to physician Treat symptomatically.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media Carbon dioxide (CO2)

Unsuitable extinguishing

media

Water

Hazardous combustion prod- :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

Standard procedure for chemical fires.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec: :

tive equipment and emergency procedures

Use personal protective equipment. Deny access to unprotected persons.

Try to prevent the material from entering drains or water **Environmental precautions** 

courses.

No special environmental precautions required.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against : Normal measures for preventive fire protection.

# Sikaflex®-221



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.03.2023

 4.0
 12.05.2025
 000000601552
 Date of first issue: 21.12.2015

fire and explosion

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis	
xylene	1330-20-7	STEL	150 ppm 655 mg/m3	AU OEL	
		TWA	80 ppm 350 mg/m3	AU OEL	
Stoddard solvent	8052-41-3	TWA	790 mg/m3	AU OEL	
	Further information: Category 1B (Carc. 1B) Presumed to have carcinogenic potential for humans				
4,4'-methylenediphenyl diiso- cyanate	101-68-8	TWA	0.02 mg/m3 (NCO)	AU OEL	
	Further information: Category 2 (Carc. 2) Suspected human carcinogen, Sensitiser				
		STEL	0.07 mg/m3 (NCO)	AU OEL	

### **Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
xylene	1330-20-7	Methylhip- puric acids	Urine	End of shift (As soon as possible	1.5 g/g creat- inine	ACGIH BEI

## Sikaflex®-221



Version Revision Date: SDS Number: Date of last issue: 27.03.2023 4.0 12.05.2025 000000601552 Date of first issue: 21.12.2015

after exposure ceases)

Appropriate engineering

controls

Use adequate ventilation and/or engineering controls to pre-

vent exposure to vapours.

Personal protective equipment

Respiratory protection In case of inadequate ventilation wear respiratory protection.

> Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Hand protection Chemical-resistant, impervious gloves complying with an

> approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Follow AS/NZS 1337.1

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Eye protection Safety glasses

Skin and body protection Protective clothing (e.g. safety shoes, long-sleeved working

> clothing, long trousers) Follow AS 2210:3

Protective clothing needs to be made of cotton.

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance paste

Colour various

Odour characteristic

Odour Threshold No data available

pΗ Not applicable

Melting point/ range / Freez-

ing point

No data available

Boiling point/boiling range No data available

## Sikaflex®-221



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.03.2023

 4.0
 12.05.2025
 000000601552
 Date of first issue: 21.12.2015

Flash point : ca. 64.6 °C (148.3 °F)

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : 0.01 hPa

Relative vapour density : No data available

Density : 1.26 g/cm3 (23 °C (73 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : ca. > 20.5 mm2/s (  $40 \, ^{\circ}\text{C} \, (104 \, ^{\circ}\text{F}))$ 

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and

livestock rearing emissions (integrated pollution prevention

and control)

Volatile organic compounds (VOC) content: 4.1% w/w

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

# Sikaflex®-221



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.03.2023

 4.0
 12.05.2025
 000000601552
 Date of first issue: 21.12.2015

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

No hazards to be specially mentioned.

Conditions to avoid : No data available

Incompatible materials : see section 7.

Hazardous decomposition

products

No hazardous decomposition products are known.

### **SECTION 11. TOXICOLOGICAL INFORMATION**

### **Acute toxicity**

Not classified due to lack of data.

**Components:** 

xylene:

Acute oral toxicity : LD50 Oral (Rat): 3,523 mg/kg

4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

## Sikaflex®-221



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.03.2023

 4.0
 12.05.2025
 000000601552
 Date of first issue: 21.12.2015

### **Chronic toxicity**

### Germ cell mutagenicity

Not classified due to lack of data.

## Carcinogenicity

Not classified due to lack of data.

#### Reproductive toxicity

Not classified due to lack of data.

### STOT - single exposure

Not classified due to lack of data.

## STOT - repeated exposure

May cause damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

### **Aspiration toxicity**

Not classified due to lack of data.

### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

#### Components:

### **Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:**

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: EC50 (Raphidocelis subcapitata (freshwater green alga)): >

100 mg/l

Exposure time: 72 h

xylene:

Toxicity to fish (Chronic tox-

icity)

NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l

Exposure time: 56 d

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia (water flea)): 1.17 mg/l

Exposure time: 7 d

## Persistence and degradability

No data available

#### Bioaccumulative potential

No data available

### Mobility in soil

No data available

## Sikaflex®-221



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.03.2023

 4.0
 12.05.2025
 000000601552
 Date of first issue: 21.12.2015

### Other adverse effects

**Product:** 

Additional ecological infor-

mation

: There is no data available for this product.

### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Send to a licensed waste management company.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

### **SECTION 14. TRANSPORT INFORMATION**

### **International Regulations**

**IATA-DGR** 

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo : Not applicable

aircraft)

Packing instruction (passen-

Not applicable

ger aircraft)

**IMDG-Code** 

Not applicable **UN** number Proper shipping name Not applicable Class Not applicable Subsidiary risk Not applicable Packing group Not applicable Labels Not applicable Not applicable EmS Code Marine pollutant Not applicable

## Sikaflex®-221



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.03.2023

 4.0
 12.05.2025
 000000601552
 Date of first issue: 21.12.2015

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## **National Regulations**

**ADG** 

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Hazchem Code : Not applicable

Special precautions for user

Not applicable

#### **SECTION 15. REGULATORY INFORMATION**

### Safety, health and environmental regulations/legislation specific for the substance or mixture

Therapeutic Goods (Poisons:

Standard) Instrument

No poison schedule number allocated (Please use the original publication to check for specific uses, specific conditions or

threshold limits that might apply for this chemical)

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements

: Not applicable

There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions

### The components of this product are reported in the following inventories:

AllC : On the inventory, or in compliance with the inventory

### **SECTION 16. OTHER INFORMATION**

Revision Date : 12.05.2025

Date of last issue : 27.03.2023

Date format : dd.mm.yyyy

### Full text of other abbreviations

ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

AU OEL : Australia. Workplace Exposure Standards for Airborne Con-

taminants.

AU OEL / TWA : Exposure standard - time weighted average

## Sikaflex®-221



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.03.2023

 4.0
 12.05.2025
 000000601552
 Date of first issue: 21.12.2015

AU OEL / STEL : Exposure standard - short term exposure limit

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road Chemical Abstracts Service

CAS : Chemical Abstracts Servi

DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN