Sikafloor®-220 W Conductive Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 24.11.2024 000000043567 Date of first issue: 24.11.2024

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikafloor®-220 W Conductive Part A

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street

Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45

Emergency telephone number: +61 1800 033 111

Telefax : +61 2 9725 33 30

Recommended use of the chemical and restrictions on use

Product use : Epoxy coating

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Serious eye damage/eye irri-

tation

: Category 1

GHS label elements

Hazard pictograms :

正型

Signal word : Danger

Hazard statements : H318 Causes serious eye damage.

Precautionary statements : Prevention:

P280 Wear eye protection/ face protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/ doctor.

Other hazards which do not result in classification

None known.

Sikafloor®-220 W Conductive Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 24.11.2024 000000043567 Date of first issue: 24.11.2024

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)	
Epoxy resin/polyamine adduct	238080-05-2	>= 3 -< 10	
Quartz (SiO2)	14808-60-7	0 -< 10	
(2-methoxymethylethoxy)propanol	34590-94-8	0 -< 10	

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

Excessive lachrymation

See Section 11 for more detailed information on health effects

and symptoms. irritant effects

Causes serious eye damage.

Notes to physician : Treat symptomatically.

Sikafloor®-220 W Conductive Part A



Version Revision Date: SDS Number: Date of last issue: -

24.11.2024 000000043567 Date of first issue: 24.11.2024 1.0

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Hazardous combustion prod- :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

Standard procedure for chemical fires.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec: :

Environmental precautions

tive equipment and emergency procedures

Use personal protective equipment. Deny access to unprotected persons.

Try to prevent the material from entering drains or water

courses.

No special environmental precautions required.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Advice on safe handling

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Handle in accordance with good industrial hygiene and safety Hygiene measures

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Sikafloor®-220 W Conductive Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 24.11.2024 000000043567 Date of first issue: 24.11.2024

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis	
		(Form of	ters / Permissible		
		exposure)	concentration		
Quartz (SiO2)	14808-60-7	TWA (Res-	0.05 mg/m3	AU OEL	
		pirable dust)			
	Further information: Category 1A (Carc. 1A) Known to have car-				
	cinogenic potential for humans				
(2-	34590-94-8	TWA	50 ppm	AU OEL	
methoxymethyleth-			308 mg/m3		
oxy)propanol			_		
	Further information: Skin absorption				

Appropriate engineering

controls

Use adequate ventilation and/or engineering controls to pre-

vent exposure to vapours.

Personal protective equipment

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Follow AS/NZS 1337.1

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Eye protection : Safety glasses

Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working

clothing, long trousers)

Follow AS 2210:3

Sikafloor®-220 W Conductive Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 24.11.2024 000000043567 Date of first issue: 24.11.2024

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : black

Odour : amine-like

Odour Threshold : No data available

pH : ca. 9

Concentration: 100 %

Melting point/ range / Freez-

ing point

No data available

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : 23 hPa

Relative vapour density : No data available

Density : ca. 1.2 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Sikafloor®-220 W Conductive Part A



Version **Revision Date:** SDS Number: Date of last issue: -

24.11.2024 000000043567 Date of first issue: 24.11.2024 1.0

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic > 20.5 mm2/s (40 °C (104 °F))

Explosive properties No data available

Oxidizing properties No data available

Directive 2010/75/EU of 24 November 2010 on industrial Volatile organic compounds

> emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 2% w/w

SECTION 10. STABILITY AND REACTIVITY

Reactivity No dangerous reaction known under conditions of normal use.

Chemical stability The product is chemically stable.

tions

Possibility of hazardous reac- : No hazards to be specially mentioned.

Conditions to avoid No data available

Incompatible materials see section 7.

Hazardous decomposition

products

: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

(2-methoxymethylethoxy)propanol:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Not classified due to lack of data.

Sikafloor®-220 W Conductive Part A



Version **Revision Date:** SDS Number: Date of last issue: -

24.11.2024 000000043567 Date of first issue: 24.11.2024 1.0

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Chronic toxicity

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor- : There is no data available for this product.

mation

Sikafloor®-220 W Conductive Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 24.11.2024 000000043567 Date of first issue: 24.11.2024

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Send to a licensed waste management company.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo : Not applicable

aircraft)

Packing instruction (passen-

Not applicable

ger aircraft)

IMDG-Code

UN number Not applicable Not applicable Proper shipping name Class Not applicable Not applicable Subsidiary risk Packing group Not applicable Labels Not applicable **EmS Code** Not applicable Not applicable Marine pollutant

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable

Sikafloor®-220 W Conductive Part A



Version **Revision Date:** SDS Number: Date of last issue: -

24.11.2024 000000043567 Date of first issue: 24.11.2024 1.0

Subsidiary risk Not applicable Packing group Not applicable Labels Not applicable Not applicable Hazchem Code

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard) Instrument

Therapeutic Goods (Poisons : No poison schedule number allocated (Please use the original publication to check for specific uses, specific conditions or

threshold limits that might apply for this chemical)

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements

Not applicable

There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

The components of this product are reported in the following inventories:

AIIC : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date 24.11.2024

Date format dd.mm.yyyy

Full text of other abbreviations

AU OEL Australia. Workplace Exposure Standards for Airborne Con-

taminants.

AU OEL / TWA Exposure standard - time weighted average

Australian Dangerous Goods Code. **ADG**

European Agreement concerning the International Carriage of **ADR**

Dangerous Goods by Road

Chemical Abstracts Service CAS Derived no-effect level **DNEL**

Half maximal effective concentration EC50

GHS Globally Harmonized System

IATA International Air Transport Association

IMDG International Maritime Code for Dangerous Goods

LD50 Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

Sikafloor®-220 W Conductive Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 24.11.2024 000000043567 Date of first issue: 24.11.2024

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN