Sikafloor®-376 Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 15.11.2019

 3.0
 11.08.2023
 000000121096
 Date of first issue: 16.08.2016

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikafloor®-376 Part A

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street

Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45

Emergency telephone number: +61 1800 033 111

Telefax : +61 2 9725 33 30

Recommended use of the chemical and restrictions on use

Product use : Polyurethane coating

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 4

Skin sensitisation : Category 1

Short-term (acute) aquatic

hazard

Category 2

Long-term (chronic) aquatic

hazard

Category 2

GHS label elements

Hazard pictograms :





Signal word : Warning

Hazard statements : H227 Combustible liquid.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

Sikafloor®-376 Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 15.11.2019

 3.0
 11.08.2023
 000000121096
 Date of first issue: 16.08.2016

P261 Avoid breathing mist or vapours.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection/ hearing protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P333 + P313 If skin irritation or rash occurs: Get medical ad-

vice/ attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse

P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

P391 Collect spillage.

Storage:

P403 Store in a well-ventilated place.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
6-methyl-2,4-bis(methylthio)phenylene-1,3-	106264-79-3	>= 10 -< 25
diamine		
Hydrocarbons, C9, aromatics	64742-95-6	>= 2.5 -< 10
N-methyl-2-pyrrolidone	872-50-4	0 -< 0.3

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Sikafloor®-376 Part A



Revision Date: Date of last issue: 15.11.2019 Version SDS Number: 11.08.2023 000000121096 Date of first issue: 16.08.2016 3.0

If symptoms persist, call a physician.

In case of eye contact Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

sensitising effects Allergic reactions

See Section 11 for more detailed information on health effects

and symptoms.

May cause an allergic skin reaction.

Treat symptomatically. Notes to physician

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Carbon dioxide (CO2)

Unsuitable extinguishing

media

Water

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod: :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Hazchem Code •3Z

Sikafloor®-376 Part A



Revision Date: Date of last issue: 15.11.2019 Version SDS Number: 11.08.2023 000000121096 Date of first issue: 16.08.2016 3.0

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

Environmental precautions

gency procedures

Use personal protective equipment. Deny access to unprotected persons.

Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Hygiene measures Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage Store in original container.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Sikafloor®-376 Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 15.11.2019

 3.0
 11.08.2023
 000000121096
 Date of first issue: 16.08.2016

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis	
Hydrocarbons, C9, aromatics	64742-95-6	TWA	900 mg/m3	AU OEL	
N-methyl-2-pyrrolidone	872-50-4	STEL	75 ppm 309 mg/m3	AU OEL	
	Further information: Skin absorption				
		TWA	25 ppm 103 mg/m3	AU OEL	

Biological occupational exposure limits

Components	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
N-methyl-2-pyrrolidone	872-50-4	5-Hydroxy-	Urine	End of	100 mg/l	ACGIH
		N-methyl-2-		shift (As		BEI
		pyrrolidone		soon as		
				possible		
				after ex-		
				posure		
				ceases)		

Appropriate engineering

controls

Use adequate ventilation and/or engineering controls to pre-

vent exposure to vapours.

Personal protective equipment

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Follow AS/NZS 1337.1

Recommended: Butyl rubber/nitrile rubber gloves.

Contaminated gloves should be removed.

Eye protection : Safety glasses

Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working

clothing, long trousers) Follow AS 2210:3

Protective clothing needs to be made of cotton.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Sikafloor®-376 Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 15.11.2019

 3.0
 11.08.2023
 000000121096
 Date of first issue: 16.08.2016

Appearance : viscous

Colour : various

Odour : amine-like

Odour Threshold : No data available

pH : ca. 7

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

Flash point : ca. 71 °C (160 °F)

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : 0.01 hPa

Relative vapour density : No data available

Density : ca. 1.76 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : ca. 450 °C (842 °F)

Decomposition temperature : No data available

Viscosity

Sikafloor®-376 Part A



Version **Revision Date:** SDS Number: Date of last issue: 15.11.2019 11.08.2023 000000121096 Date of first issue: 16.08.2016 3.0

Viscosity, dynamic : ca. 4,200 mPa.s (20 °C (68 °F))

Viscosity, kinematic > 20.5 mm2/s (40 °C (104 °F))

Explosive properties No data available

Oxidizing properties No data available

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

> emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 3.5% w/w

SECTION 10. STABILITY AND REACTIVITY

Reactivity No dangerous reaction known under conditions of normal use.

Chemical stability The product is chemically stable.

tions

Possibility of hazardous reac- : Stable under recommended storage conditions.

Conditions to avoid No data available

Incompatible materials see section 7.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine:

Acute oral toxicity : LD50 Oral (Rat): 1,515 mg/kg

Hydrocarbons, C9, aromatics:

LD50 Oral (Rat): > 2,000 mg/kg Acute oral toxicity

Acute dermal toxicity LD50 Dermal (Rabbit): > 2,000 mg/kg

N-methyl-2-pyrrolidone:

Acute oral toxicity LD50 Oral (Rat): 4,150 mg/kg

Acute inhalation toxicity LC50 (Rat): 5.1 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Sikafloor®-376 Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 15.11.2019

 3.0
 11.08.2023
 000000121096
 Date of first issue: 16.08.2016

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Hydrocarbons, C9, aromatics:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Hydrocarbons, C9, aromatics:

Toxicity to algae/aquatic : (Pseudokirchneriella subcapitata (green algae)): 2.6 - 2.9

plants mg/l

Exposure time: 72 h

Sikafloor®-376 Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 15.11.2019

 3.0
 11.08.2023
 000000121096
 Date of first issue: 16.08.2016

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo

aircraft)

: 964

964

Packing instruction (passen-

er aircraft)

ger aircraft)

Remarks : Transport in accordance with special regulation A 197

IMDG-Code

UN number : UN 3082

Sikafloor®-376 Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 15.11.2019

 3.0
 11.08.2023
 000000121096
 Date of first issue: 16.08.2016

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : ves

Remarks : Transport in accordance with 2.10.2.7 of the IMDG-Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine)

Class : 9
Packing group : III
Labels : 9
Hazchem Code : •3Z

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform Scheduling of Medicines and

No poison schedule number allocated

Poisons

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements

Not applicable

There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions

The components of this product are reported in the following inventories:

AIIC : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Sikafloor®-376 Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 15.11.2019

 3.0
 11.08.2023
 000000121096
 Date of first issue: 16.08.2016

Revision Date : 11.08.2023

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

AU OEL : Australia. Workplace Exposure Standards for Airborne Con-

taminants.

AU OEL / TWA : Exposure standard - time weighted average AU OEL / STEL : Exposure standard - short term exposure limit

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN