Sikagard 6470S



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.10.2016

 2.0
 02.09.2021
 100000001235
 Date of first issue: 04.10.2016

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikagard 6470S

Product code : 100000001235

Manufacturer or supplier's details

Company : Sika Australia Pty. Ltd.

55 Elizabeth Street

Wetherill Park, NSW 2164

Telephone : +61 2 9725 11 45 Telefax : +61 2 9725 33 30 Emergency telephone num- : +61 1800 033 111

ber

Recommended use of the chemical and restrictions on use

Product use : Surfaces protection

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Aerosols : Category 1

Skin corrosion/irritation : Category 2

Specific target organ toxicity - :

single exposure

Category 3 (Central nervous system)

Short-term (acute) aquatic

hazard

: Category 2

Long-term (chronic) aquatic

hazard

: Category 2

GHS label elements

Hazard pictograms



(!)



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

Sikagard 6470S



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.10.2016

 2.0
 02.09.2021
 100000001235
 Date of first issue: 04.10.2016

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing mist.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P332 + P313 If skin irritation occurs: Get medical advice/ atten-

111. 200 - D204 T-L

P362 + P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

•

Substance / Mixture

Mixture

Components

| Chemical name | CAS-No. | Concentration (% w/w) | |
|---|------------|-----------------------|--|
| dimethyl ether | 115-10-6 | >= 10 -< 30 | |
| pentane | 109-66-0 | >= 10 -< 20 | |
| Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics | 64742-49-0 | >= 10 -< 20 | |
| Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane | 64742-49-0 | < 10 | |
| ethyl acetate | 141-78-6 | < 10 | |
| Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics | 64742-49-0 | < 10 | |
| cyclohexane | 110-82-7 | < 10 | |

Sikagard 6470S



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.10.2016

 2.0
 02.09.2021
 100000001235
 Date of first issue: 04.10.2016

Hydrocarbons, C9, aromatics 64742-95-6 < 10

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

irritant effects Dermatitis Loss of balance

Vertigo

See Section 11 for more detailed information on health effects

and symptoms.
Causes skin irritation.

May cause drowsiness or dizziness.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray jet

Dry powder

Foam

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod- :

ucts

No hazardous combustion products are known

Specific extinguishing meth- : Use water spray to cool unopened containers.

Sikagard 6470S



Date of last issue: 04.10.2016 Version Revision Date: SDS Number: 100000001235 02.09.2021 Date of first issue: 04.10.2016 2.0

Collect contaminated fire extinguishing water separately. This ods

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Hazchem Code 2YE

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment. Deny access to unprotected persons.

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Keep away from heat/ sparks/ open flames/ hot surfaces. No

smoking.

Do not spray on a naked flame or any incandescent material. Take precautionary measures against electrostatic discharg-

Advice on safe handling Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Follow standard hygiene measures when handling chemical

products

Hygiene measures Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

Conditions for safe storage BEWARE: Aerosol is pressurized. Keep away from direct sun

> exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects.

Store in original container.

Sikagard 6470S



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.10.2016

 2.0
 02.09.2021
 100000001235
 Date of first issue: 04.10.2016

Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|---|------------|-------------------------------------|--|--------|
| dimethyl ether | 115-10-6 | STEL | 500 ppm 950 mg/m3 | AU OEL |
| | | TWA | 400 ppm 760 mg/m3 | AU OEL |
| pentane | 109-66-0 | TWA | 600 ppm 1,770 mg/m3 | AU OEL |
| | | STEL | 750 ppm 2,210 mg/m3 | AU OEL |
| Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics | 64742-49-0 | TWA | 900 mg/m3 | AU OEL |
| Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane | 64742-49-0 | TWA | 900 mg/m3 | AU OEL |
| ethyl acetate | 141-78-6 | STEL | 400 ppm 1,440 mg/m3 | AU OEL |
| | | TWA | 200 ppm 720 mg/m3 | AU OEL |
| cyclohexane | 110-82-7 | TWA | 100 ppm 350 mg/m3 | AU OEL |
| | | STEL | 300 ppm 1,050 mg/m3 | AU OEL |
| Hydrocarbons, C9, aromatics | 64742-95-6 | TWA | 900 mg/m3 | AU OEL |

Appropriate engineering

controls

Use adequate ventilation and/or engineering controls to pre-

vent exposure to vapours.

Personal protective equipment

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Follow AS/NZS 1337.1

Eye protection : Safety glasses

Skin and body protection : Protective clothing (e.g. safety shoes, long-sleeved working

Sikagard 6470S



Version Date of last issue: 04.10.2016 Revision Date: SDS Number: 10000001235 Date of first issue: 04.10.2016 02.09.2021 2.0

> clothing, long trousers) Follow AS 2210:3

Protective clothing needs to be made of cotton.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance aerosol

Colour various

Odour solvent-like

Odour Threshold No data available

not determined рΗ

Melting point/range / Freezing :

No data available

Boiling point/boiling range : ca. -25 °C (-13 °F)

: ca. < -20 °C (< -4 °F) Flash point

(Method: closed cup)

Evaporation rate No data available

Flammability (solid, gas) No data available

Upper explosion limit / Upper

flammability limit

18 %(V)

Lower explosion limit / Lower : 0.6 %(V)

flammability limit

Vapour pressure : ca. 4,910 hPa (25 °C (77 °F))

Relative vapour density No data available

ca. 0.82 g/cm3 (20 °C (68 °F)) Density

Solubility(ies)

insoluble Water solubility

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature > 200 °C (> 392 °F)

Decomposition temperature No data available

Viscosity

Viscosity, dynamic : No data available

Sikagard 6470S



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.10.2016

 2.0
 02.09.2021
 100000001235
 Date of first issue: 04.10.2016

Viscosity, kinematic : No data available

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 76% w/w

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : see section 7.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components: ethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): ca. 1,600 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 23.3 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,800 mg/kg

Hydrocarbons, C9, aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

Sikagard 6470S



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.10.2016

 2.0
 02.09.2021
 100000001235
 Date of first issue: 04.10.2016

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

Hydrocarbons, C9, aromatics:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Hydrocarbons, C9, aromatics:

Toxicity to algae/aquatic : (Pseudokirchneriella subcapitata (green algae)): 2.6 - 2.9

plants r

Exposure time: 72 h

Sikagard 6470S



Version Date of last issue: 04.10.2016 Revision Date: SDS Number: 10000001235 Date of first issue: 04.10.2016 02.09.2021 2.0

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. UN 1950

Aerosols, flammable Proper shipping name

Class 2.1

Packing group Not assigned by regulation

Flammable Gas Labels

Packing instruction (cargo

aircraft)

203

Packing instruction (passen-

ger aircraft)

203

IMDG-Code

UN 1950 **UN** number **AEROSOLS** Proper shipping name

Sikagard 6470S



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.10.2016

 2.0
 02.09.2021
 100000001235
 Date of first issue: 04.10.2016

(cyclohexane, naphtha (petroleum))

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number : UN 1950 Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 Hazchem Code : 2YE

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : No poison schedule number allocated

Scheduling of Medicines and

Poisons

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Prohibition/Licensing Requirements

: Not applicable

 There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions.

The components of this product are reported in the following inventories:

AICS : On the inventory, or in compliance with the inventory

AIIC : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date : 02.09.2021 Date format : dd.mm.yyyy

Sikagard 6470S



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.10.2016

 2.0
 02.09.2021
 100000001235
 Date of first issue: 04.10.2016

Full text of other abbreviations

AU OEL : Australia. Workplace Exposure Standards for Airborne Con-

taminants.

AU OEL / TWA : Exposure standard - time weighted average AU OEL / STEL : Exposure standard - short term exposure limit

ADG : Australian Dangerous Goods Code.

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration
GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

AU / EN